
Project Memorandum

To:	KGHM Ajax Mining Inc.	Doc. No.:	BGC-007
Attention:	Nettie Ore	cc:	
From:	Cassandra Koenig	Date:	April 22, 2016
Subject:	Ajax Project EA/EIS - Responses to Information Requests from ECCC on Post-Closure Net Groundwater Flux		
Project No.:	1125011		

1.0 INTRODUCTION

The *Ajax Project Environmental Assessment Certificate Application / Environmental Impact Statement for a Comprehensive Study* was issued in September 2015 (KAM, 2015). Comments, Permit Conditions, and Permit Information Requirements (IRs) were provided to KAM on February 22, 2016 by the Ministry of Forests, Lands & Natural Resource Operations (FLNRO) and Environment and Climate Change Canada (ECCC) following a review of the Application and supporting documents. This memorandum documents the response to IR# ECCC-019.

2.0 PERMIT INFORMATION REQUIREMENT RESPONSES

2.1. Information Requirement Issue ID # ECCC-019

This net groundwater flux figure [Figure 6.6-14] doesn't show a high discharge flux rate (e.g., purple) for the open pit as expected from the text. MRSFs are light green, as expected from text description. TSF shows dark green in area of north embankment. This high groundwater recharge flux is not expected based on the description in the text. Resolve or explain the groundwater flux presented in the figure compared to the description in the text.

Response:

Discharge to the open pit is predicted to occur at a low to negligible rate throughout most of the pit footprint as shown in Figure 6.6-14 of the EA/EIS Application due to reduced groundwater levels around the pit and the generally low hydraulic conductivity of the bedrock. Zones of higher discharge are restricted to the footprint of the simulated pit lake (i.e., simulated stage of 500 masl) and along the southwestern pit wall. The reviewer is correct that these zones did not get incorporated into Figure 6.6-14 of the EA/EIS. This figure has been updated and is included here as Drawing 01.

Seepage from the TSF is predicted to vary across its footprint in response to hydraulic gradients. Higher seepage rates (and thus darker green colors) are predicted adjacent to embankments

where larger hydraulic gradients are present due to the presence of the low hydraulic conductivity embankment liner simulated using the horizontal flow barrier package (Section 6.4.7, Appendix 6.6-D). Lower seepage rates (i.e., approaching zero) are predicted in the central portion of the TSF where lower hydraulic gradients are predicted.

3.0 CLOSURE

BGC Engineering Inc. (BGC) prepared this document for the account of KGHM Ajax Mining Inc. The material in it reflects the judgment of BGC staff in light of the information available to BGC at the time of document preparation. Any use which a third party makes of this document or any reliance on decisions to be based on it is the responsibility of such third parties. BGC accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this document.

As a mutual protection to our client, the public, and ourselves all documents and drawings are submitted for the confidential information of our client for a specific project. Authorization for any use and/or publication of this document or any data, statements, conclusions or abstracts from or regarding our documents and drawings, through any form of print or electronic media, including without limitation, posting or reproduction of same on any website, is reserved pending BGC's written approval. A record copy of this document is on file at BGC. That copy takes precedence over any other copy or reproduction of this document.

Yours sincerely,

BGC ENGINEERING INC.
per:

Cassandra Koenig, M.Sc., P.Geo.
Project Manager / Hydrogeologist


Craig Thompson, M.Sc., GIT
Hydrogeologist

Reviewed by:

Trevor W. Crozier, M.Eng., P.Eng.
Principal Hydrogeological Engineer

CK/TWC/vg

X:\Projects\1125_AJAX\07\GIS\Production\Report\2015\0319_AJAX_Project_EA_Numerical_Groundwater_Flow_Model\01_Simulated_Net_Groundwater_Flux_PostClosure_Apr2016.mxd Date: April 20, 2016 Time: 2:44 PM



NOTES:

1. ALL DIMENSIONS ARE IN METRES UNLESS OTHERWISE NOTED.
2. THIS DRAWING MUST BE READ IN CONJUNCTION WITH BGC'S REPORT TITLED "AJAX PROJECT ENVIRONMENTAL ASSESSMENT NUMERICAL GROUNDWATER FLOW MODEL," AND DATED APRIL 2016.
3. GENERAL ARRANGEMENT OF MINE SITE FACILITIES PROVIDED BY KAM ON APRIL 15, 2015.
4. PROJECTION IS NAD 1983 UTM ZONE 10N.
5. THESE RESULTS ARE BASED ON CLOSURE MODEL WITH PIT LAKE ELEVATION OF 500 MASL.
6. POSITIVE NUMBERS INDICATE NET GAIN TO THE GROUNDWATER SYSTEM (RECHARGE) AND NEGATIVE NUMBERS INDICATE NET LOSS TO THE GROUNDWATER SYSTEM (DISCHARGE).

7. UNLESS BGC AGREES OTHERWISE IN WRITING, THIS DRAWING SHALL NOT BE MODIFIED OR USED FOR ANY PURPOSE OTHER THAN THE PURPOSE FOR WHICH BGC GENERATED IT. BGC SHALL HAVE NO LIABILITY FOR ANY DAMAGES OR LOSS ARISING IN ANY WAY FROM ANY USE OR MODIFICATION OF THIS DOCUMENT NOT AUTHORIZED BY BGC. ANY USE OF OR RELIANCE UPON THIS DOCUMENT OR ITS CONTENT BY THIRD PARTIES SHALL BE AT SUCH THIRD PARTIES' SOLE RISK.

SCALE:	1:50,000
DATE:	APR 2016
DRAWN:	MIB
CHECKED:	RC/BM
APPROVED:	TWC

BIGC	BGC ENGINEERING INC. AN APPLIED EARTH SCIENCES COMPANY
CLIENT:	KGHM AJAX MINING INC.

PROJECT:	AJAX PROJECT ENVIRONMENTAL ASSESSMENT NUMERICAL GROUNDWATER FLOW MODEL	
TITLE:	SIMULATED NET GROUNDWATER FLUX (POST-CLOSURE)	
PROJECT No.:	1125007-04	DWG No.: 01