

**APPENDIX 22-C
HIGHWAYS 37 AND 37A TRAFFIC
EFFECTS ASSESSMENT**



Seabridge Gold Inc.

KSM PROJECT Highways 37 and 37A Traffic Effects Assessment

SEABRIDGE GOLD



Rescan™ Environmental Services Ltd.
Rescan Building, Sixth Floor - 1111 West Hastings Street
Vancouver, BC Canada V6E 2J3
Tel: (604) 689-9460 Fax: (604) 687-4277

July 2013

KSM PROJECT HIGHWAYS 37 AND 37A TRAFFIC EFFECTS ASSESSMENT

July 2013
Project #0868-022-57

Citation:

Rescan. 2013. *KSM Project: Highways 37 and 37A Traffic Effects Assessment*. Prepared for Seabridge Gold Inc. by Rescan Environmental Services Ltd.: Vancouver, British Columbia.

Prepared for:

SEABRIDGE GOLD

Seabridge Gold Inc.

Prepared by:



Engineers and Scientists

Rescan™ Environmental Services Ltd.
Vancouver, British Columbia

Executive Summary

The KSM Project (the Project) is owned by Seabridge Gold Inc. (Seabridge). The Project is a proposed gold, copper, silver and molybdenum mine located in the mountainous terrain of northwestern British Columbia (BC), approximately 950 km northwest of Vancouver, and approximately 65 km northwest of Stewart, BC. The Project is subject to the British Columbia *Environmental Assessment Act* (BCEAA) and the *Canadian Environmental Assessment Act* (CEAA).

This report meets the requirements of the Section 13 order issued by the BC Environmental Assessment Office (BCEAO) on September 29, 2011, which amended the Section 11 order issued on November 6, 2009. The Section 13 order requires Seabridge to assess the potential effects arising from the transport of people, goods and materials, including, but not limited to fuel, hazardous cargos and explosives along access roads and Highway 37 between the proposed Project site and its junction with Highway 16 at Kitwanga. This report focuses on potential effects of Project-related traffic travelling on highways 37 and 37A. The use of existing and proposed access roads to the Project site will be assessed in Seabridge's Application for an Environmental Assessment Certificate / Environmental Impact Statement (Application/EIS).

This report has considered the input from government, Nisga'a Nation, and First Nations as a result of Traffic Working Group meeting was held on July 9, 2012 in Terrace, BC and in subsequent correspondence (Appendix F).

The KSM Highways 37 and 37A Traffic Assessment Study Area (the Study Area) encompasses approximately 300 km of Highway 37 from the Eskay Creek Mine access road junction, southeast to its junction with Highway 16 in Kitwanga; and approximately 65 km of Highway 37A from Meziadin Junction to the District of Stewart. The Study Area includes 500 metres on either side of the highways.

A risk assessment methodology is used to estimate the likelihood or probability of potentially adverse environmental effects resulting from increased Project-traffic within the Study Area, and is complementary to methods used in Application/EIS where significance determinations are made. Risk assessment methods are commonly used in land use and resource management planning, and when assessing risks associated hazards, accidents and malfunctions.

Valued Components (VCs) are those parts of the biophysical or human environment deemed important based on social values or scientific concerns. Potential traffic-associated risks to the VCs are identified for each environmental topic and selected for further analysis. Potential risks are then characterized by: (1) the likelihood, ranging from rare to certain; and (2) the severity, ranging from negligible to catastrophic. Potential effect/risk ratings were characterized post-mitigation for the following topics:

- Socio-economics;
- Fish and Aquatic Habitat;
- Terrestrial Ecosystems;
- Wetlands;
- Noise;
- Climate and Air Quality;
- Human Health; and
- Heritage.

Figure 1 summarizes the conclusions of potential risks associated with Project-related traffic. Effects resulting from normal Project traffic activities range in likelihood from rare to certain, with a predominant expectation of minor severity. For example, highway transportation activities are certain to affect ambient air quality because all vehicles will require fuel to operate. The maximum amount of traffic engine combustion will occur during operation, but the contribution of Criteria Air Contaminants (CACs) from engine combustion to ambient air quality is expected to be minor. Or in another example, the potential effect of direct mortality to wildlife (bears and birds) caused by vehicle collisions on highways 37 and 37A could occur during all Project phases, but is expected to be of minor severity.

In order to assess the potential effects of increased traffic on direct mortality of moose, a population viability assessment was conducted using a population dynamics model of the Nass moose population. A moose vehicle collision model was imbedded into the population dynamics model to emulate the fraction of moose mortality that could be explained by the current level of vehicle collisions. Results indicate that the addition of traffic from the KSM project is projected to cause an additional <1% mortality to the moose population at the current population size, a mortality rate that does not predict a substantial decline. After mitigation, it is possible that vehicle/moose collisions will occur resulting in direct mortality due to increased traffic on the highways (particularly Highway 37), and severity is expected to be moderate (Figure 1).


A British Columbia Ministry of Transportation and Infrastructure (BC MOTI) collision prediction model was used to predict the annual number of collisions on highways 37 and 37A associated with the additional traffic volumes expected for each of the Project phases. The analysis for this model utilized historical police data on traffic accidents in the Study Area between 1996 and 2011. The potential for Project-related traffic accidents is expected to be rare. Potential social and environmental risks from traffic accidents are expected to be rare and unlikely occurrences (Figure 1).

Effects of traffic accidents characterized as possible and catastrophic are those resulting in human injury or death, while unlikely accidents with major/moderate severity are those that involve the potential release of hazardous cargo or deleterious substances into the environment (Figure 1). For example, wetland function could be compromised if a hazardous cargo spill extends beyond the road surface, resulting in the deposition of deleterious substances into a wetland.

A summary of Project-specific mitigation and management actions is provided in this document. The objective of these measures is to minimize potential harm to people and the environment. These actions are included in Seabridge's Traffic and Access Management Plan, Dangerous Goods and Hazardous Materials Management Plan, Emergency Response Plan (for emergencies other than spills), and Spill Prevention and Emergency Response Plan, all of which are included in the Project's Application/EIS. A more detailed framework for monitoring risk mitigations, and adapting actions if required, is included in the Application / EIS.

Finally, the analysis of cumulative risk of the KSM Project combined with highway traffic effects from other present and reasonably foreseeable future projects is included. The cumulative effects assessment shows that, assuming other projects adopt similar mitigation measures as the KSM Project, the likelihood and severity of risks to VCs should not increase beyond the incremental risk posed by the KSM Project, despite potential increases in traffic along highways 37 and 37A.

Likelihood



Project Traffic	Traffic Accidents	Topic
●	●	Socio-economics and Land Use
	●	Fish and Aquatic Habitat
●	●	Wildlife
●	●	Terrestrial Ecosystems
	●	Wetlands
●	●	Climate and Air Quality
●	●	Human Health
	●	Heritage




Figure 1

KSM PROJECT

HIGHWAYS 37 AND 37A TRAFFIC

EFFECTS ASSESSMENT

Table of Contents

- Executive Summary i
- Table of Contents v
 - List of Figuresxii
 - List of Tablesxiii
 - List of Plates xvii
 - List of Appendices xviii
- Glossary and Abbreviations xix
- 1. Introduction1-1
 - 1.1 Overview1-1
 - 1.2 Scope1-2
- 2. Project Description.....2-4
 - 2.1 Highways 37 and 37A Description.....2-4
 - 2.1.1 Highway Condition2-4
 - 2.1.2 Highway Services2-6
 - 2.1.3 Historical Traffic2-6
 - 2.1.3.1 Mining Haul Traffic 2-11
 - 2.1.3.2 Forestry Traffic..... 2-12
 - 2.1.3.3 Commercial Traffic 2-15
 - 2.1.3.4 Average Commercial Truck Speed 2-16
 - 2.1.4 Highway Capacity 2-16
 - 2.2 KSM Project Overview 2-17
 - 2.3 Transportation Requirements 2-17
 - 2.4 Projected Traffic Volumes 2-20
 - 2.4.1 Construction Phase Activities 2-22
 - 2.4.2 Operation Phase Activities 2-25
 - 2.4.3 Closure Phase Activities 2-25
 - 2.4.4 Post-closure Phase Activities 2-25
 - 2.4.5 Hazardous Cargo 2-25
 - 2.4.5.1 Fuel and Lubricants 2-25
 - 2.4.5.2 Concentrate 2-26

2.4.5.3	Lime and Reagents.....	2-26
2.4.5.4	Explosives	2-28
2.5	Summary of Predicted Traffic Volumes	2-28
3.	Vehicle Accidents on Highways 37 and 37A.....	3-1
3.1	Historical Vehicle Accident Statistics.....	3-1
3.1.1	Vehicle Collision Location Analysis	3-3
3.1.2	Seasonal Vehicle Collision Analysis	3-6
3.1.3	Collisions by Vehicle Type and Road Location	3-6
3.1.4	Contributing Factors in Vehicle Collisions	3-6
3.2	Collision Prediction Modelling.....	3-12
3.2.1	Methodology.....	3-12
3.2.2	Limitations of the Models	3-14
3.2.3	Project-specific Results	3-14
4.	Effects and Risk Assessment Methods.....	4-1
4.1	Introduction	4-1
4.2	Baseline Data Overview Methods	4-2
4.3	Issue Scoping Methods	4-2
4.3.1	Assessment Topic Scoping Methods	4-2
4.3.2	Valued Component Scoping Methods.....	4-2
4.3.3	Methods for Identification of Potential Traffic/Valued Component Interactions.....	4-5
4.4	Risk Analysis Methods.....	4-5
4.4.1	Risk Identification Methods.....	4-6
4.4.2	Risk Mitigation Methods	4-6
4.4.3	Risk Characterization	4-6
5.	Assessment of the Potential Risks of Project Traffic.....	5-1
5.1	Socio-economics and Land Use.....	5-1
5.1.1	Baseline Data Overview	5-1
5.1.1.1	Economic Development	5-2
5.1.1.2	Communities	5-2
5.1.2	Issue Scoping	5-22
5.1.2.1	Socio-economic and Land Use Scoping	5-22
5.1.2.2	Valued Component Scoping	5-22
5.1.2.3	Potential Traffic/Valued Component Interactions.....	5-24
5.1.3	Risk Analysis.....	5-24
5.1.3.1	Community Well-being.....	5-24
5.1.3.2	Hunting and Trapping	5-29
5.2	Fish and Aquatic Habitat	5-30
5.2.1	Baseline Data Overview	5-30
5.2.2	Issue Scoping	5-32
5.2.2.1	Fish and Aquatic Habitat Scoping	5-32

	5.2.2.2	Valued Component Scoping	5-34
	5.2.2.3	Identification of Potential Traffic/Valued Component Interactions	5-35
5.2.3		Risk Analysis	5-35
	5.2.3.1	Fuel or Lubricant Spill.....	5-36
	5.2.3.2	Concentrate Spills	5-36
	5.2.3.3	Lime and Reagents.....	5-39
	5.2.3.4	Explosives	5-40
5.3		Wildlife	5-41
	5.3.1	Baseline Data Overview	5-41
		5.3.1.1 Moose	5-41
		5.3.1.2 Bears	5-42
		5.3.1.3 Western Toads.....	5-42
		5.3.1.4 Avian Community	5-43
	5.3.2	Issue Scoping	5-43
		5.3.2.1 Wildlife Scoping	5-43
		5.3.2.2 Valued Component Scoping	5-43
		5.3.2.3 Identification of Potential Traffic/Valued Component Interactions	5-43
	5.3.3	Risk Analysis	5-43
		5.3.3.1 Disruption of Movement	5-48
		5.3.3.2 Direct Mortality	5-53
		5.3.3.3 Chemical Hazards	5-56
5.4		Terrestrial Ecosystems	5-57
	5.4.1	Baseline Data Overview	5-57
		5.4.1.1 Disturbance History.....	5-58
	5.4.2	Issue Scoping	5-58
		5.4.2.1 Terrestrial Ecosystems Scoping.....	5-58
		5.4.2.2 Valued Component Scoping	5-58
		5.4.2.3 Potential Traffic/Valued Component Interactions.....	5-58
	5.4.3	Risk Analysis	5-59
		5.4.3.1 Introduction and Spread of Invasive Species.....	5-60
		5.4.3.2 Incidence of Wildfire	5-63
		5.4.3.3 Chemical Contamination.....	5-63
5.5		Wetlands	5-64
	5.5.1	Baseline Data Overview	5-64
	5.5.2	Issue Scoping	5-65
		5.5.2.1 Wetlands Scoping	5-65
		5.5.2.2 Valued Component Scoping	5-65
		5.5.2.3 Potential Traffic/Valued Component Interactions.....	5-66
	5.5.3	Risk Analysis	5-67

	5.5.3.1	Vehicle Accident in Wetland	5-69
5.6		Noise	5-69
	5.6.1	Baseline Data Overview	5-69
	5.6.2	Issue Scoping	5-69
	5.6.2.1	Noise Scoping	5-69
	5.6.2.2	Valued Component Scoping	5-70
	5.6.2.3	Potential Traffic/Valued Component Interactions	5-71
	5.6.3	Risk Analysis	5-71
5.7		Climate and Air Quality	5-71
	5.7.1	Baseline Data Overview	5-71
	5.7.2	Issue Scoping	5-72
	5.7.2.1	Climate and Air Quality Scoping.....	5-72
	5.7.2.2	Valued Component Scoping	5-73
	5.7.2.3	Potential Traffic/Valued Component Interactions	5-74
	5.7.3	Risk Analysis	5-74
	5.7.3.1	Climate and Air Quality	5-74
5.8		Human Health	5-79
	5.8.1	Baseline Data Overview	5-79
	5.8.2	Issue Scoping	5-80
	5.8.2.1	Human Health Scoping	5-80
	5.8.2.2	Valued Component Scoping	5-81
	5.8.2.3	Potential Traffic/Valued Component Interactions	5-81
	5.8.3	Risk Analysis	5-83
	5.8.3.1	Country Foods	5-83
	5.8.3.2	Noise	5-89
	5.8.3.3	Air Quality.....	5-91
	5.8.3.4	Drinking Water Quality.....	5-92
	5.8.3.5	Human Safety.....	5-93
5.9		Heritage	5-93
	5.9.1	Baseline Data Overview	5-93
	5.9.2	Issue Scoping	5-94
	5.9.2.1	Heritage Scoping	5-94
	5.9.2.2	Valued Component Scoping	5-95
	5.9.2.3	Potential Traffic/Valued Component Interactions	5-95
	5.9.3	Risk Analysis	5-96
	5.9.3.1	Chemical Contamination.....	5-96
	5.9.3.2	Incidence of Wildfire	5-98
6.		Summary of the Potential Risks of Project Traffic Accidents	6-1
	6.1	Introduction	6-1
	6.2	Scope and Objective	6-1
	6.3	Potential Traffic Accident Scenarios.....	6-1

6.3.1	Discharge of Hazardous Materials into the Environment	6-1
6.3.2	Detonation of Explosives	6-2
6.3.3	Fires.....	6-2
6.3.4	Injury or Mortality	6-2
6.4	Risks by Accident Scenario.....	6-2
6.4.1	On-road, Non-hazardous Cargo	6-2
6.4.2	On-road, Hazardous Cargo	6-3
6.4.3	Off-road, Non-hazardous Cargo	6-4
6.4.4	Off-road, Hazardous Cargo	6-5
7.	Summary of Mitigation and Environmental Management	7-1
7.1	Introduction	7-1
7.2	Mitigation and Management Objectives	7-1
7.3	Highway Traffic Management	7-1
7.3.1	Action to Avoid or Mitigate	7-1
7.3.1.1	Traffic and Access Management Plan Risk Mitigation Measures	7-1
7.3.1.2	Wildlife and Terrestrial Ecosystems Specific Risk Mitigation Measures.....	7-3
7.3.1.3	Climate and Air Quality Specific Risk Mitigation Measures	7-3
7.3.1.4	Dangerous Goods and Hazardous Materials Management Plan Risk Mitigation Measures.....	7-3
7.4	Traffic Accidents Management.....	7-4
7.4.1	Action to Avoid or Mitigate	7-4
7.4.1.1	Emergency Response Plan Risk Mitigation Measures	7-4
7.4.1.2	Spill Prevention and Emergency Response Plan Risk Mitigation Measures.....	7-4
7.5	Monitoring and Reporting	7-5
8.	Cumulative Risk Assessment.....	8-1
8.1	Traffic Considered.....	8-1
8.2	Potential Cumulative Increases in Traffic.....	8-2
8.3	Cumulative Vehicle Collision Prediction Modelling.....	8-7
8.4	Cumulative Risk Assessment Methodology	8-7
8.4.1	Cumulative Issue Scoping (Step 2).....	8-12
8.4.2	Cumulative Risk Analysis (Step 3)	8-12
8.4.2.1	Cumulative Risk Identification.....	8-12
8.4.2.2	Cumulative Risk Mitigation	8-12
8.4.2.3	Cumulative Risk Characterization.....	8-13
8.5	Cumulative Risk of Traffic on Socio-economics and Land Use.....	8-13
8.5.1	Cumulative Issue Scoping for Socio-economics and Land Use	8-13
8.5.2	Cumulative Risk to Community Well-being	8-14
8.5.2.1	Cumulative Risk Identification.....	8-14
8.5.2.2	Cumulative Risk Mitigation	8-15

- 8.5.2.3 Cumulative Risk Characterization..... 8-15
- 8.5.3 Cumulative Risk to Hunting and Trapping..... 8-17
 - 8.5.3.1 Cumulative Risk Identification..... 8-17
 - 8.5.3.2 Cumulative Risk Mitigation 8-17
 - 8.5.3.3 Cumulative Risk Characterization..... 8-18
- 8.6 Cumulative Risk of Traffic on Fish and Aquatic Habitat 8-18
 - 8.6.1 Cumulative Issue Scoping for Fish and Aquatic Habitat 8-18
 - 8.6.2 Cumulative Risk to Fish and Aquatic Habitat 8-18
 - 8.6.2.1 Cumulative Risk Identification..... 8-18
 - 8.6.2.2 Cumulative Risk Mitigation 8-18
 - 8.6.2.3 Cumulative Risk Characterization..... 8-19
- 8.7 Cumulative Risk of Traffic on Wildlife 8-19
 - 8.7.1 Cumulative Issue Scoping for Wildlife 8-19
 - 8.7.2 Cumulative Risk Analysis for Moose 8-19
 - 8.7.2.1 Cumulative Risk Identification..... 8-19
 - 8.7.2.2 Cumulative Risk Mitigation 8-22
 - 8.7.2.3 Cumulative Risk Characterization..... 8-22
 - 8.7.3 Cumulative Risk Analysis for Bears 8-25
 - 8.7.3.1 Cumulative Risk Identification..... 8-25
 - 8.7.3.2 Cumulative Risk Mitigation 8-26
 - 8.7.3.3 Cumulative Risk Characterization..... 8-26
 - 8.7.4 Cumulative Risk Analysis for Western Toads 8-27
 - 8.7.4.1 Cumulative Risk Identification..... 8-27
 - 8.7.4.2 Cumulative Risk Mitigation 8-27
 - 8.7.4.3 Cumulative Risk Characterization..... 8-28
 - 8.7.5 Cumulative Risk Analysis for Birds..... 8-28
 - 8.7.5.1 Cumulative Risk Identification..... 8-28
 - 8.7.5.2 Cumulative Risk Mitigation 8-28
 - 8.7.5.3 Cumulative Risk Characterization..... 8-28
- 8.8 Cumulative Risk of Traffic on Terrestrial Ecosystems 8-28
 - 8.8.1 Cumulative Issues Scoping for Terrestrial Ecosystems 8-28
 - 8.8.2 Cumulative Risk Analysis for Terrestrial Ecosystems..... 8-29
 - 8.8.2.1 Cumulative Risk Identification..... 8-29
 - 8.8.2.2 Cumulative Risk Mitigation 8-29
 - 8.8.2.3 Cumulative Risk Characterization..... 8-30
- 8.9 Cumulative Risk of Traffic on Wetlands 8-30
 - 8.9.1 Cumulative Issues Scoping for Wetlands 8-30
 - 8.9.2 Cumulative Risk Analysis for Wetland Function 8-30
 - 8.9.2.1 Cumulative Risk Identification..... 8-30
 - 8.9.2.2 Cumulative Risk Mitigation 8-33
 - 8.9.2.3 Cumulative Risk Characterization..... 8-33

8.10	Cumulative Risk of Traffic on Noise.....	8-33
8.10.1	Cumulative Issues Scoping for Noise	8-34
8.10.2	Cumulative Risk Analysis for Noise	8-34
8.10.2.1	Cumulative Noise Modelling.....	8-34
8.11	Cumulative Risk of Traffic on Climate and Air Quality	8-35
8.11.1	Cumulative Issues Scoping for Climate and Air Quality.....	8-35
8.11.2	Cumulative Risks Analysis for Air Quality	8-35
8.11.2.1	Cumulative Risk Identification.....	8-35
8.11.2.2	Cumulative Risk Mitigation	8-36
8.11.2.3	Cumulative Risk Characterization.....	8-36
8.12	Cumulative Risk of Traffic on Human Health.....	8-36
8.12.1	Cumulative Issues Scoping for Human Health	8-36
8.12.2	Cumulative Risk Analysis for Country Foods	8-36
8.12.2.1	Cumulative Risk Identification.....	8-36
8.12.2.2	Cumulative Risk Mitigation	8-38
8.12.2.3	Cumulative Risk Characterization.....	8-38
8.12.3	Cumulative Risk Analysis for Noise	8-38
8.12.3.1	Cumulative Risk Identification.....	8-38
8.12.3.2	Cumulative Risk Mitigation	8-38
8.12.3.3	Cumulative Risk Characterization.....	8-40
8.12.4	Cumulative Risk Analysis for Air Quality	8-40
8.12.4.1	Cumulative Risk Identification.....	8-40
8.12.4.2	Cumulative Risk Mitigation	8-40
8.12.4.3	Cumulative Risk Characterization.....	8-40
8.12.5	Cumulative Risk Analysis for Drinking Water Quality	8-41
8.12.5.1	Cumulative Risk Identification.....	8-41
8.12.5.2	Cumulative Risk Mitigation	8-41
8.12.5.3	Cumulative Risk Characterization.....	8-41
8.12.6	Cumulative Risk Analysis for Human Safety	8-41
8.12.6.1	Cumulative Risk Identification.....	8-41
8.12.6.2	Cumulative Risk Mitigation	8-41
8.12.6.3	Cumulative Risk Characterization.....	8-42
8.13	Cumulative Risk of Traffic on Heritage	8-42
8.13.1	Cumulative Issues Scoping for Heritage	8-42
8.13.2	Cumulative Risks Analysis for Archaeological and Heritage Sites.....	8-42
8.13.2.1	Cumulative Risk Identification.....	8-42
8.13.2.2	Cumulative Risk Mitigation	8-42
8.13.2.3	Cumulative Risk Characterization.....	8-43
9.	Summary	9-1
	References.....	R-1

List of Figures

FIGURE	PAGE
Figure 1. Assessment of Potential Risks Associated with Project-related Traffic (by Topic)	iii
Figure 1.2-1. KSM Project Traffic Study Area.....	1-3
Figure 2.1-1. Highway Bridge Sites Requiring Upgrading	2-5
Figure 2.1-2. Summer Average Daily Traffic on Highway 37, 1980 to 1989	2-7
Figure 2.1-3a. Summer Average Daily Traffic on Highway 37, 1990 to 1999.....	2-9
Figure 2.1-3b. Annual Average Daily Traffic on Highway 37, 1994 to 1999	2-9
Figure 2.1-4a. Summer Average Daily Traffic on Highway 37, 2000 to 2011.....	2-10
Figure 2.1-4b. Annual Average Daily Traffic on Highway 37, 2000 to 2011	2-10
Figure 2.1-5. Combined Annual Daily Traffic from Eskay Creek and Huckleberry Mines on Highways 37 and 37A	2-13
Figure 2.1-6. Minimum Forestry Haul Traffic from Brown Bear Forest Service Road to Stewart between 1995 and 2009	2-14
Figure 2.3-1. KSM Project Traffic Study Cargo Routes	2-19
Figure 2.4-1. One-way Trips per Day during Each Project Phase	2-23
Figure 2.4-2. KSM Project Traffic Study One-way Trips per Day during Each Project Phase.....	2-24
Figure 3.1-1. Vehicle Collisions on Highway 37 between Bob Quinn Camp and Kitwanga.....	3-2
Figure 3.1-2. Locations of Vehicle Collisions on Highways 37 and 37A, 1996 to 2011.....	3-4
Figure 3.1-3. Locations of Vehicle Collisions on Highway 37 between Kitwanga and Gitanyow, 1996 to 2011.....	3-5
Figure 3.1-4. Seasonal Vehicle Collisions on Highway 37 between Kitwanga and Bob Quinn Lake	3-7
Figure 3.1-5. Seasonal Vehicle Collisions on Highway 37A	3-8
Figure 3.1-6. Collisions by Vehicle Type on Highway 37 between Kitwanga and Bob Quinn Lake	3-9
Figure 3.1-7. Collisions by Vehicle Type on Highway 37A On- and Off-highway.....	3-10
Figure 3.2-1. Predicted Number of Collisions per Year on Highway 37 North – Baseline AADT vs. Project Phases	3-15
Figure 3.2-2. Predicted Number of Collisions per Year on Highway 37 South – Baseline AADT vs. Project Phases	3-16
Figure 3.2-3. Predicted Number of Collisions per Year on Highway 37A – Baseline AADT vs. Project Phases	3-17
Figure 4.1-1. Risk Assessment Flow Chart.....	4-3
Figure 5.1-1a. Traffic Study Area Baseline Map.....	5-3
Figure 5.1-1b. Traffic Study Area Baseline Map.....	5-5

Figure 5.1-1c. Traffic Study Area Baseline Map5-7

Figure 5.1-1d. Traffic Study Area Baseline Map.....5-9

Figure 5.1-1e. Traffic Study Area Baseline Map..... 5-11

Figure 5.1-1f. Traffic Study Area Baseline Map 5-13

Figure 5.1-1g. Traffic Study Area Baseline Map 5-15

Figure 5.1-1h. Traffic Study Area Baseline Map..... 5-17

Figure 5.1-1i. Traffic Study Area Baseline Map 5-19

Figure 5.2-1. Important Salmon Bearing Streams..... 5-33

Figure 8.1-1. Present and Future Project Traffic Routes.....8-3

Figure 8.2-1. Potential Cumulative One-way Trips per Day as a Result of KSM and Other Projects8-5

Figure 8.2-2. Potential Cumulative One-way Trips per Day.....8-6

Figure 8.3-1. Predicted Number of Collisions per Year on Highway 37 North - Baseline Average Annual Daily Trips vs. Cumulative Traffic.....8-8

Figure 8.3-2. Predicted Number of Collisions per Year on Highway 37 South - Baseline Average Annual Daily Trips vs. Cumulative Traffic.....8-9

Figure 8.3-3. Predicted Number of Collisions per Year on Highway 37A - Baseline Average Annual Daily Trips vs Cumulative Traffic 8-10

Figure 8.4-1. Cumulative Risk Assessment Flow Chart..... 8-11

Figure 9-1. Assessment of Potential Risks Associated with Traffic from KSM and Other Projects (by Topic)9-3

List of Tables

TABLE	PAGE
Table 2.1-1. Highway 37 Services.....	2-6
Table 2.1-2. Highway 37 Annual Average Daily Traffic and Summer Average Daily Traffic by Year.....	2-8
Table 2.1-3. Mining Average Annual Daily Traffic by Route.....	2-11
Table 2.1-4. Combined Annual Average Daily Traffic from Eskay Creek and Huckleberry Mines on Highway 37.....	2-12
Table 2.1-5. Combined Annual Average Daily Traffic from Eskay Creek and Huckleberry Mines on Highway 37A	2-15
Table 2.1-6. Forestry Haul Traffic as a Percentage of Overall Summer Average Daily Traffic on Highways 37 and 37A	2-16
Table 2.4-1. Total Average Annual One-way Trips by Route for Construction	2-20
Table 2.4-2. Total Average Annual One-way Trips by Route for Operation.....	2-21

Table 2.4-3. Total Average Annual One-way Trips by Route for Closure 2-21

Table 2.4-4. Total Average Annual One-way Trips by Route for Post-closure 2-22

Table 2.4-5. Copper Concentrate Toxicity Characterization Leaching Results Compared to Canadian Drinking Water Guidelines 2-27

Table 2.4-6. Projected Traffic Volumes for Process Plant Lime and Reagents 2-29

Table 2.5-1. Estimated Traffic Volume Increases on Highways 37 and 37A Resulting from the KSM Project 2-31

Table 3.1-1. Vehicle Collisions on Highway 37 between Bob Quinn Camp and Kitwanga 3-1

Table 3.1-2. Vehicle Collisions on Highway 37A between Stewart and Meziadin Junction 3-3

Table 3.1-3. Annual Collisions per 100,000 Vehicles on Highway 37 between Kitwanga and Bob Quinn Lake 3-11

Table 3.1-4. Annual Collisions per 100,000 Vehicles on Highway 37A 3-11

Table 3.2-1. Collision Prediction Model Variables for Rural Arterial Undivided Two-lane Roads 3-13

Table 3.2-2. Project-related Annual Increases to Traffic Volumes 3-13

Table 3.2-3. Predicted Number of Collisions per Year – Baseline vs. Project Operation Phase 3-14

Table 4.3-1. Assessment Topic Scoping Matrix (Example) 4-4

Table 4.3-2. Identification and Rationale for Valued Component Selection/Exclusion Matrix (Example) 4-4

Table 4.3-3. Potential Traffic/Valued Component Interaction Matrix (Example) 4-5

Table 4.4-1. Risk Assessment Matrix for Project Traffic (Example) 4-7

Table 4.4-2. Risk Assessment Matrix for Traffic Accidents (Example) 4-7

Table 5.1-1. Population and Demographics – Regional District of Kitimat-Stikine 5-1

Table 5.1-2. Socio-economic and Land Use Scoping Matrix 5-22

Table 5.1-3. Identification and Rationale for Socio-economic and Land Use Valued Component Selection/Exclusion 5-22

Table 5.1-4. Potential Traffic / Socio-economic and Land Use Valued Component Interaction Matrix 5-24

Table 5.1-5. Social-economic and Land Use Risk Assessment Severity Scale Descriptors 5-25

Table 5.1-6. Social Risk Assessment Matrix for Project Traffic 5-26

Table 5.1-7. Social Risk Assessment Matrix for Traffic Accidents 5-26

Table 5.2-1. Watercourses with Sensitive Fish and Aquatic Habitat Values along Highways 37 and 37A .. 5-30

Table 5.2-2. Fish and Aquatic Habitat Scoping Matrix 5-34

Table 5.2-3. Identification and Rationale for Fish and Aquatic Habitat Valued Component Selection/Exclusion 5-34

Table 5.2-4. Potential Traffic / Fish and Aquatic Habitat Valued Component Interaction Matrix..... 5-35

Table 5.2-5. Fish and Aquatic Habitat Risk Assessment Severity Scale Descriptors 5-35

Table 5.2-6. Fish and Aquatic Habitat Risk Assessment Matrix for Project Traffic 5-37

Table 5.2-7. Fish and Aquatic Habitat Risk Assessment Matrix for Traffic Accidents 5-37

Table 5.3-1. Wildlife Scoping Matrix 5-43

Table 5.3-2. Identification and Rationale for Wildlife Valued Component Selection/Exclusion 5-44

Table 5.3-3. Potential Traffic / Wildlife Valued Component Interaction Matrix..... 5-47

Table 5.3-4. Wildlife Risk Assessment Severity Scale Descriptors 5-48

Table 5.3-5. Wildlife Risk Assessment Matrix for Project Traffic 5-49

Table 5.3-6. Wildlife Risk Assessment Matrix for Traffic Accidents 5-49

Table 5.3-7. Average Annual Daily Traffic along Highway 37 (Eskay Creek Mine Access Road to Meziadin Junction) 5-51

Table 5.3-8. Average Annual Daily Traffic along Highway 37 (Meziadin Junction to Kitwanga)..... 5-51

Table 5.3-9. Average Annual Daily Traffic along Highway 37A 5-51

Table 5.4-1. Terrestrial Ecosystems Scoping Matrix..... 5-58

Table 5.4-2. Identification and Rationale for Terrestrial Ecosystems Valued Component Selection/Exclusion 5-59

Table 5.4-3. Potential Traffic / Terrestrial Ecosystems Valued Component Interaction Matrix 5-59

Table 5.4-4. Terrestrial Ecosystems Risk Assessment Severity Scale Descriptors 5-60

Table 5.4-5. Terrestrial Ecosystems Risk Assessment Matrix for Project Traffic Activities 5-61

Table 5.4-6. Terrestrial Ecosystems Risk Assessment Matrix for Traffic Accidents..... 5-61

Table 5.5-1. Areas of TRIM Wetlands along Highways 37 and 37A within the Study Area 5-64

Table 5.5-2. Wetlands Scoping Matrix 5-65

Table 5.5-3. Identification and Rationale for Wetlands Valued Component Selection/Exclusion..... 5-66

Table 5.5-4. Potential Traffic / Wetlands Valued Component Interaction Matrix 5-66

Table 5.5-5. Wetlands Risk Assessment Severity Scale Descriptors 5-67

Table 5.5-6. Wetlands Risk Assessment Matrix for Traffic Accidents 5-68

Table 5.6-1. Estimated Baseline Traffic Noise Levels Averaged Over 24 Hours 5-70

Table 5.6-2. Noise Scoping Matrix 5-70

Table 5.6-3. Identification and Rationale for Noise Valued Component Selection/Exclusion 5-70

Table 5.6-4. Potential Traffic / Valued Component Interaction Matrix – Noise 5-71

Table 5.6-5. Estimated Traffic Noise Levels Averaged Over 24 Hours – Baseline and Predicted during Operation Phase 5-71

Table 5.7-1. Background Air Contaminant Measurements – Diavik Diamond Mine 5-72

Table 5.7-2. Background Air Contaminant Measurements – Galore Creek Project..... 5-72

Table 5.7-3. Climate and Air Quality Scoping Matrix..... 5-73

Table 5.7-4. Identification and Rationale for Climate and Air Quality Valued Component Selection/Exclusion 5-73

Table 5.7-5. Potential Traffic / Climate and Air Quality Valued Component Interaction Matrix 5-74

Table 5.7-6. Climate and Air Quality Risk Assessment Severity Scale Descriptors..... 5-74

Table 5.7-7. Climate and Air Quality Risk Assessment Matrix for Project Activities 5-77

Table 5.7-8. Climate and Air Quality Risk Assessment Matrix for Traffic Accidents..... 5-77

Table 5.8-1. Human Health Scoping Matrix 5-80

Table 5.8-2. Identification and Rationale for Human Health Valued Component Selection/Exclusion 5-82

Table 5.8-3. Potential Traffic / Valued Component Interaction Matrix – Human Health 5-82

Table 5.8-4. Human Health Risk Assessment Severity Scale Descriptors 5-83

Table 5.8-5. Human Health Risk Assessment Matrix for Project Traffic 5-85

Table 5.8-6. Human Health Risk Assessment Matrix for Traffic Accidents 5-85

Table 5.8-7. Predicted and Adjusted Sound Levels for Baseline and Project Traffic Noise and Calculated Impact from Project Traffic on Percentage Change in High Annoyance..... 5-90

Table 5.9-1. Archaeological Sites within 200 Metres of Highway 37 5-94

Table 5.9-2. Heritage Scoping Matrix 5-95

Table 5.9-3. Identification and Rationale for Heritage Valued Component Selection/Exclusion 5-95

Table 5.9-4. Potential Traffic/Heritage Valued Component Interaction Matrix 5-95

Table 5.9-5. Heritage Risk Assessment Severity Scale Descriptors 5-96

Table 5.9-6. Heritage Risk Assessment Matrix for Traffic Accidents 5-97

Table 6.4-1. Potential Risks and Severity of On-road Traffic Accidents (Non-hazardous Cargo).....6-3

Table 6.4-2. Potential Risks and Severity of On-road Traffic Accidents (Hazardous Cargo)6-3

Table 6.4-3. Potential Risks and Severity of Off-road Traffic Accidents (Non-hazardous Cargo)6-4

Table 6.4-4. Potential Risks and Severity of Off-road Traffic Accidents (Hazardous Cargo).....6-5

Table 6.4-5. Potential Risks and Severity of Traffic Accidents involving Process Plant Reagent Spills6-7

Table 7.4-1. Spill Response Measures for Specific Reagents.....7-7

Table 8.2-1. Potential Cumulative One-way Trips per Day as a Result of KSM and Other Projects during Operation8-4

Table 8.3-1. Predicted Number of Collisions per Year – Baseline vs. Cumulative Traffic.....8-7

Table 8.4-1. Potential Cumulative Interaction Matrix (Example)..... 8-12

Table 8.4-2. Assessment Matrix for Cumulative Risks (Example) 8-13

Table 8.5-1. Potential Cumulative Interaction Matrix: Socio-economics and Land Use 8-14

Table 8.5-2. Assessment Matrix for Cumulative Risks: Socio-economics and Land Use 8-16

Table 8.6-1. Potential Cumulative Interaction Matrix: Fish and Aquatic Habitat..... 8-18

Table 8.6-2. Assessment Matrix for Cumulative Risks: Fish and Aquatic Habitat 8-20

Table 8.7-1. Potential Cumulative Interaction Matrix: Wildlife..... 8-21

Table 8.7-2. Estimated Traffic Rates (Vehicles per Hour) of all Cumulative Risk Assessment Projects
Based on Projected Traffic Estimates (all Projects) and Existing Background Traffic Levels 8-21

Table 8.7-3. Assessment Matrix for Cumulative Risks: Wildlife 8-23

Table 8.8-1. Potential Cumulative Interaction Matrix: Terrestrial Ecosystems 8-29

Table 8.8-2. Assessment Matrix for Cumulative Risks: Terrestrial Ecosystems..... 8-31

Table 8.9-1. Potential Cumulative Interaction Matrix: Wetlands..... 8-33

Table 8.9-2. Assessment Matrix for Cumulative Risks: Wetland Function..... 8-33

Table 8.10-1. Potential Cumulative Interaction Matrix: Noise 8-34

Table 8.10-2. Cumulative Traffic Estimates for Noise at the Closest Receiver 8-34

Table 8.11-1. Potential Cumulative Interaction Matrix: Climate and Air Quality..... 8-35

Table 8.11-2. Assessment Matrix for Cumulative Risks: Climate and Air Quality 8-37

Table 8.12-1. Potential Cumulative Interaction Matrix: Human Health 8-37

Table 8.12-2. Assessment Matrix for Cumulative Risks: Human Health..... 8-39

Table 8.13-1. Potential Cumulative Interaction Matrix: Heritage 8-42

Table 8.13-2. Assessment Matrix for Cumulative Risks: Heritage..... 8-44

List of Plates

PLATE	PAGE
Plate 2.3-1. Bulk B-train truck example.....	2-18
Plate 2.3-2. Fuel tanker truck example.	2-18

List of Appendices

- Appendix A. KSM Project Section 13 Order (BCEAO 2011)
- Appendix B. Review of Historical Traffic Patterns and Capacity on Highway 37 in Proximity to the Proposed KSM Project (McElhanney 2011)
- Appendix C. KSM Project Traffic Volume Study (Wardrop 2012)
- Appendix D. Moose and Highway 37/37A Traffic; a Population Viability Approach
- Appendix E. Updated KSM Project Highway Traffic Noise Predictions Including Cumulative Effects (BKL 2013)
- Appendix F. Working Group Comment Tracking Table

Glossary and Abbreviations

Abbreviations used in this document are defined where they are first used. The following list will assist readers who may choose to review only portions of the document.

% HA	Percent Highly Annoyed
µg/m³	Micrograms per cubic metre
AADT	Annual Average Daily Traffic
AANDC	Aboriginal Affairs and Northern Development Canada
AMS	Arrow Mining Services Inc.
BC	British Columbia
BCEAA	British Columbia <i>Environmental Assessment Act</i>
BCEAO	British Columbia Environmental Assessment Office
BC MFML	British Columbia Ministry of Forests, Mines and Land
BC MOTI	British Columbia Ministry of Transportation and Infrastructure
Bioaccumulate	To build up within the tissues of living organisms
BMP	Best Management Practice
CAC	criteria air contaminant
CAPMoN	Canadian Air and Precipitation Monitoring Network
CCME	Canadian Council of Ministers of the Environment
CEAA	<i>Canadian Environmental Assessment Act</i>
CMHC	Canada Mortgage and Housing Corporation
CPM	Collision prediction model
CPPI	Canadian Petroleum Products Institute
CRA	Cumulative Risk Assessment
CWB	Community Well-being
dB	Decibels
EA	environmental assessment
EB	Empirical Bayes
FSR	Forestry Service Road
GHG	greenhouse gas
HA	High Annoyance
IARC	International Agency for Research on Cancer
ICBC	Insurance Corporation of British Columbia

HIGHWAYS 37 AND 37A TRAFFIC EFFECTS ASSESSMENT

ICMI	International Cyanide Management Institute
IUCN	International Union for the Conservation of Nature
LKI	Landmark Kilometre Inventory
LRMP	Land and Resource Management Plan
LOS	Level of Service
MAWTP	Mine Area Water Treatment Plant
MSDS	Materials Safety Datasheet
NWA	Nass Wildlife Area
pc/h	Passenger cars per hour
PDO	Property Damage Only
PVA	Population Viability Analysis
RAAD	Remote Access to Archaeological Data
RAU2	Rural Arterial Undivided Two-Lane
SADT	Summer Average Daily Traffic
SARA	<i>Species at Risk Act, 2002</i>
Seabridge	Seabridge Gold Inc.
SRMP	Sustainable Resource Management Plan
TDG	Transportation of Dangerous Goods
the Project	the KSM Project
the Study Area	The Highways 37 and 37A Traffic Effects Assessment Study Area
TMF	Tailing Management Facility
TRIM	Terrain Resource Information Management
UWR	Ungulate Winter Range
VC	Valued Component
VHF	Very High Frequency
WARS	Wildlife Accident Reporting System
WHA	Wildlife Habitat Area
WHMIS	Workplace Hazardous Materials Information System

1. Introduction

1.1 OVERVIEW

Seabridge Gold Inc. (Seabridge) is proposing to develop the KSM Project (the Project), a gold, copper, silver and molybdenum mine located in the mountainous terrain of northwestern British Columbia (BC), approximately 950 km northwest of Vancouver, and approximately 65 km northwest of Stewart, BC. The Project is subject to the British Columbia *Environmental Assessment Act* (BCEAA) and the *Canadian Environmental Assessment Act* (CEAA).

The KSM Highways 37 and 37A Traffic Effects Assessment meets the requirements of the Section 13 order issued by the BC Environmental Assessment Office (BCEAO) on September 29, 2011, which amended the Section 11 order issued on November 6, 2009. The Section 13 order requires Seabridge to assess the potential effects arising from the transport of people, goods and materials, including, but limited to fuel, hazardous cargo and explosives along access roads and Highway 37 between the proposed Project site and its junction with Highway 16 at Kitwanga. This report focuses on the potential effects of Project-related traffic travelling on highways 37 and 37A and addresses the Section 13 order (Appendix A) requirement to assess the potential effects on the Nisga'a Nation, and the Tahltan, Gitanyow, and Gitksan Nation (including the Skii km Lax Ha) First Nations within the Project transportation corridor. The results will also be relevant to non-Aboriginal people who may be affected by Project traffic along highways 37 and 37A. The use of existing and proposed access roads off of these two main transportation corridors (highways 37 and 37A) to the Project site will be assessed in Seabridge's Application for an Environmental Assessment Certificate.

Traffic-related issues and concerns have been a part of Project discussions since initiation of the environmental assessment (EA) process and through the pre-Application stage. Issues raised by Nisga'a Nation, First Nations, local governments, and federal and provincial agency representatives include:

- concern about the potential increase in wildlife mortality levels on Highway 37 as a result of increased traffic;
- concern about potential effects on traditional medicine along the haul route;
- concern about emissions generated from trucking ore to Stewart, and accidents and malfunctions;
- inclusion of transportation routes in the spatial boundary for the Project;
- request to report Project-related traffic estimates; and
- concern about Project traffic cargo such as acid solvents, explosives and other dangerous materials/hazardous cargo.

This report has considered the input from government, Nisga'a Nation, and First Nations as a result of Traffic Working Group meeting was held on July 9, 2012 in Terrace, BC and in subsequent correspondence. Appendix F details the comments provided, Seabridge's responses, and where applicable provides a reference to relevant sections in the report.


This document is organized into the following sections:

- **Project Description:** A description of highways 37 and 37A, summary of historical traffic on these highways, an overview of the proposed Project and transportation requirements during construction, operation, closure and post-closure, and projected traffic volumes from the Project.
- **Vehicle Accidents on highways 37 and 37A:** A description of vehicle accident statistics and an analysis predicting the potential for traffic-related accidents.
- **Effects and Risk Assessment Methods:** A step-by step explanation of the risk assessment methods, including definitions for transportation-specific risk ratings, used to assess potential effects of traffic on environmental and socio-economic Valued Components (VCs).
- **Assessment of the Potential Risks of Project Traffic:** An assessment of potential risks related to Project traffic following the methods described in the Effects and Risk Assessment Methods section, grouped by assessment topic (i.e., Socio-economics, Fish and Aquatic Habitat, Wildlife, Terrestrial Ecosystems, Wetlands, Noise, Climate and Air Quality, Human Health, and Heritage). “Project Traffic” is used to describe planned Project traffic activities.
- **Summary of the Potential Risks of Traffic Accidents:** A risk assessment approach that evaluates the probability and severity of potential effects of accidents and malfunctions for each assessment topic. Traffic Accidents are divided into “off-road” and “on-road” accidents. “On-road” refers to a traffic accident where vehicles remain on the travelled part of the road, while “off-road” refers to accidents that result in a vehicle leaving the travelled part of the road.
- **Summary of Mitigation and Environmental Management:** A description of mitigation objectives and actions that apply specifically to the proposed highway haul route.
- **Cumulative Risk Assessment:** An assessment of risk from the proposed Project from highway traffic and accidents combined with highway traffic effects from other present and reasonably foreseeable future projects.
- **Summary of Highway Traffic Effects Assessment:** A summary of the findings and conclusions of this study and the risk ratings for Project-related traffic by assessment topic.

1.2 SCOPE

The Highways 37 and 37A Traffic Effects Assessment Study Area (the “Study Area”) encompasses approximately 300 km of Highway 37 from the Eskay Creek Mine Access Road junction, southeast to its junction with Highway 16 in Kitwanga; and approximately 65 km of Highway 37A from Meziadin Junction to the District of Stewart. The Study Area includes a 500 metre buffer on either side of the highways (Figure 1.2-1). This assessment considers the potential effects of Project-related traffic within the Study Area for the phases of the Project:

- construction (5 years);
- operation (51.5 years);
- closure (3 years); and
- post-closure (250 years).



Legend

- KSM Highway Traffic Study Area
- KSM Project Footprint
- Highway

1:1,500,000

0 25 50

Kilometres

GIS #: KSM-15-169
Date: January 29, 2013
Projection: NAD 1983 UTM Zone 9N

Figure 1.2-1

2. Project Description

2.1 HIGHWAYS 37 AND 37A DESCRIPTION

Highway 37, a provincial highway, runs 725 km through northwestern British Columbia, travelling north from the Kitwanga Junction to Junction 37, where it meets the Alaska Highway in the Yukon Territory. Along the way, it passes through Meziadin Junction, Bell II, Bob Quinn Lake, Iskut, Dease Lake, and Good Hope Lake.

Highway 37 is one of only two overland routes to Alaska and it connects a number of small settlements in the region. The highway was first developed as a logging and mining road, and paved in the 1970s. Improvements including road straightening and widening to the Highway have been made in recent years.

Highway 37A, also a provincial highway, branches westward from Highway 37 at Meziadin Junction and terminates at Stewart, BC, near Hyder, Alaska.

As described in Section 1.2, the Study Area includes Highway 37 from the Eskay Creek Mine Access Road junction, southeast to junction with Highway 16; and Highway 37A from Meziadin Junction to the District of Stewart (Figure 1.2-1).


2.1.1 Highway Condition

Highway 37 is suitable for a range of vehicle types. Most of the road is hard-surfaced (either paved or seal-coated), although there are some gravelled sections north of Iskut. The speed limit ranges from 80 to 100 km/h, and is 90 km/h from Meziadin Junction to the Yukon border (S. Applegate, pers. comm., 2012). Most of the Highway is double-lane, although lane markings may not be present and single-lane bridges are common.

Road conditions depend on the season and the weather; potholes and broken seal coat are common year-round. The British Columbia Ministry of Transportation and Infrastructure (BC MOTI) is responsible for repairs and improvements to Highway 37. Construction and maintenance occurs throughout the year, and is mainly focused on the southern half of the Highway. The Highway is sanded and cleared of snow in the winter, and gravelled sections are graded in the summer (BC MOTI 2011c).

It is anticipated that some bridge crossings along highways 37 and 37A will require upgrading in order to accommodate vehicle equipment loads for the Project (Wardrop 2011). A study conducted by McElhanney (2008) identified potential issues with the following bridge sites which fall within the Study Area (see Figure 2.1-1):

- Clements Creek Bridge (#3255);
- Entrance Creek Bridge (#7922);
- Bell Irving River Bridge # 2 (#2195);
- Hanna Creek North Bridge (#7775);
- Hanna Creek South Bridge (#7628);
- Nass River Bridge (# 7773);
- Cranberry River Bridge #2 (#2681);
- Tintina River Bridge (#7774).



Highway Bridge Sites Requiring Upgrading

Figure 2.1-1

While some of these bridge sites in the McElhanney report were identified as being scheduled for upgrading in 2009, or requiring further field investigation, no upgrades to these bridges have been completed, and only one upgrade (Nass River Bridge #7773) is currently being undertaken, scheduled to be completed at the end of March, 2013 (S. Applegate, pers. comm., 2012). Additionally, recent extreme weather events (notably in September of 2011) are known to have washed out bridge and crossing structures along Highway 37. These events may have resulted in additional work being required to bridge crossings along Highway 37.

2.1.2 Highway Services

There are limited services along Highway 37 (Table 2.1-1). There are no services along Highway 37A.

Table 2.1-1. Highway 37 Services

Location	Distance (South to North)	Facilities
Kitwanga	0 km	Gas, diesel, minor repairs, restaurant
Gitanyow	24 km	Gas, diesel, groceries
Bell II	249 km	Gas, diesel, minor repairs, restaurant
Tatogga	392 km	Gas, diesel, restaurant (summer only)
Iskut	405 km	Gas, diesel, groceries
Dease Lake	480 km	Gas, diesel, repairs, groceries, propane
Jade City	595 km	Gas and diesel
Good Hope Lake	629 km	Gas, diesel, store
Junction 37 and Alaska Highway	727 km	Gas, diesel, minor repairs and restaurant

Source: BC MOTI (2011c).


Fuel, basic supplies, and restaurant facilities are available at the Kitwanga Junction. Meziadin Junction used to offer fuel, food, and a campground; however, these facilities have been closed for the past few years. Bell II has accommodation, a restaurant, and a gas bar. Heading north, the next services are in Iskut, Tatogga and Dease Lake.

2.1.3 Historical Traffic

Traffic data collected between 1985 and 2001 for four segments of Highway 37 (Kitwanga to Meziadin Junction, Meziadin Junction to Stikine River Bridge, Stikine River Bridge to Dease Lake and Dease Lake to Alaska Highway) are available through the BC MOTI database (BC MOTI 2011e). The data set between 1980 and 1985 is limited because the data was not collected for the entire highway or throughout the year. After 2001, most non-permanent traffic counters along Highway 37 were not used, except for a counter near Meziadin Junction in 2005, 2008 and 2010.

1980 to 1989

Traffic counts indicate that the highest traffic levels occurred in the southern section of Highway 37 during the 1980s. However, these data were not collected along the entire highway, nor were they collected every year (Figure 2.1-2). During this period, traffic counts were conducted in July and August to create a Summer Average Daily Traffic (SADT) count, measured in one-way trips. The SADT count likely represents the highest annual traffic volume along the highway, since peak traffic levels are typically in the summer. Traffic counts include recreational, resource, and commercial traffic; however, the data does not distinguish between the three. Data were either not available or not collected on some sections of the highway during this period. Due to a lack of available traffic data, 1981 to 1984 and 1988 counts are not considered here (BC MOTI 2011e).



Note: Where gaps are present, data is unavailable for those years.
 Source: BC MOTI 2011d.

SADT counts on the Highway 37 between Kitwanga and Meziadin Junction increased every year from 1985 to 1989. In 1989, the peak daily traffic count reached approximately 1,500. Between Meziadin Junction and the Stikine River Bridge, north of Iskut, SADT counts ranged from 840 to 1,100 (BC MOTI 2011e).

Traffic north of the Stikine River Bridge was on average 22% less than traffic on the southern portions of the highway (BC MOTI 2011e).

1990 to 1999

Between 1990 and 1999, traffic volume along Highway 37 remained high, continuing the steady increase that began in the 1980s (Figures 2.1-3a and 2.1-3b). Summertime traffic patterns fluctuated from year to year, but overall Annual Average Daily Traffic (AADT) counts, starting in 1994, remained relatively consistent and slightly lower than SADT counts. Generally, the highest counts occurred at the south end of the route between Kitwanga and Meziadin Junction. Traffic along the northern sections steadily increased from 1990 to 1995. Traffic volume along the entire stretch of the highway rose in the mid-1990s, and then dropped from 1996 to 1999 (BC MOTI 2011e).

In 1992, 1994, and 1995, a significant increase in traffic was noted between the Stikine River Bridge and Dease Lake. An average 944 SADT was measured over 1994 and 1995, 47% higher than the average along that section in the 1990s (BC MOTI 2011e). Forestry traffic may have been a contributor to these increases (see Section 2.1.3.2).

2000 to 2011



After 2001, non-permanent traffic counters were not used along Highway 37. The only permanent counter along the route, found along the southern segment at the junction of highways 16 and 37, does not provide an accurate count for Highway 37 traffic. However, periodic traffic counts for the northern section of the highway taken in 2005 and 2008 north of Meziadin Junction, and in 2006 north of Dease Lake (Table 2.1-2 and Figures 2.1-4a and 2.1-4b), serve as approximate indicators of traffic trends along the route (BC MOTI 2011e).

Table 2.1-2. Highway 37 Annual Average Daily Traffic and Summer Average Daily Traffic by Year

Year	Southern Segment		Northern Segment	
	AADT Count	SADT Count	AADT Count	SADT Count
2000	698	851	469	593
2001	707	854	405	510
2002	-	-	-	-
2003	-	-	-	-
2004	918	1,182	-	-
2005	816	1,111	238	356
2006	795	1,171	-	-
2007	838	-	-	-
2008	740	1,011	224	378
2009	760	-	-	-
2010	709	977	210	-
2011	828	1,104	-	-



- : No data

Source: BC MOTI (2011e)



Note: Where gaps are present, data is unavailable for those years.
 Source: BC MOTI 2011d.

Figure 2.1-3



Note: Where gaps are present, data is unavailable for those years.
 Source: BC MOTI 2011d.

Figure 2.1-4

Overall, traffic levels were lower in the 2000s than in the previous decades. Traffic patterns were very similar, with more vehicles recorded between Kitwanga and Meziadin Junction than elsewhere (Table 2.1-2). Traffic volume increased during the summer between the Stikine River Bridge and Dease Lake.

2.1.3.1 Mining Haul Traffic

Recently, mining haul traffic along highways 37 and 37A has occurred from the Eskay Creek Mine (north of Meziadin Junction) and the Huckleberry Mine (south of Meziadin). Both mines hauled product to the port of Stewart. Until the spring of 2008, four or five haul trucks from the Eskay Creek Mine and about ten trucks from the Huckleberry Mine travelled the highway each day (AMS, pers. comm., 2010). The Eskay Creek Mine ceased production in the spring of 2008.

Highway 37

Arrow Mining Services Inc. (AMS) has provided haul services for mine projects in the region over the past several decades and it is expected to provide similar services for the KSM Project. AMS uses “B-Train” type side dump trailers that have a total payload of approximately 40 tonnes (AMS, pers. comm., 2010).

Data were collected in 2010 from AMS, who provided haul services for Barrick Gold’s Eskay Creek and Imperial Metal’s Huckleberry mine in the region during their operation between 2000 and 2009. Table 2.1-3 summarizes AMS data for the Eskay Creek and Huckleberry mines based on three haul routes. These two mines generally operated year round.

Table 2.1-3. Mining Average Annual Daily Traffic by Route

Destination	Eskay Creek Mine		Huckleberry Mine
	Stewart	Highway 16	Stewart
Highway 37 Section	Bob Quinn Lake Area/Meziadin Junction	Bob Quinn Lake Area/Kitwanga	Kitwanga/Meziadin Junction
2000	6	9	15
2001	6	13	20
2002	6	13	19
2003	9	12	19
2004	9	14	16
2005	4	11	18
2006	3	5	17
2007	2	4	14
2008	0	1	9
2009	0	0	10

Note: Bob Quinn Lake Area refers to the Eskay Creek Mine road/Highway 37 junction.
Source: AMS (pers. comm., 2010).

The Eskay Creek Mine used two haul routes along Highway 37: from the Highway 37 junction with Eskay Creek Mine road to Meziadin Junction, and from the Highway 37 junction with the Eskay Creek Mine road to Kitwanga. The Huckleberry Mine used one haul route from between Kitwanga and Meziadin Junction to Stewart. Based on AMS’s total haul traffic figures for these routes an AADT was calculated for each route (Table 2.1-4). Figure 2.1-5 is a synthesis of these routes, calculating cumulative traffic for each section of Highway 37.

Table 2.1-4. Combined Annual Average Daily Traffic from Eskay Creek and Huckleberry Mines on Highway 37

Year	Bob Quinn Lake /Meziadin		Kitwanga/Meziadin Junction	
	Mining Haul AADT	% of total AADT	Mining Haul AADT	% of total AADT
2000	15	3%	24	3%
2001	19	5%	32	5%
2002	19	-	32	-
2003	21	-	31	-
2004	23	-	30	4%
2005	15	6%	30	4%
2006	8	-	23	3%
2007	5	-	18	2%
2008	1	1%	11	1%
2009	0	-	10	1%

Note: Bob Quinn Lake Area refers to the Eskay Creek Mine road/Highway 37 junction.

Source: AMS (pers. comm., 2010).

- : Data not available, only periodic traffic counts were taken in 2005 and 2008 north of Meziadin Junction.

Mining haul traffic between 2000 and 2009 was concentrated along the Kitwanga to Meziadin Junction segment of Highway 37. Mining traffic generally peaked between 2001 and 2005 while both Eskay Creek and Huckleberry mines were in full operation. By 2006 Eskay Creek Mine had slowed production, and the mine closed in 2008 (BC MEMPR 2012). During these periods, mine haul traffic accounted for between 1 and 5% of total traffic along the Kitwanga to Meziadin Junction segment of Highway 37, and between 1 and 6% of the overall traffic AADT from Bob Quinn Lake area to Meziadin Junction (Table 2.1-3). Huckleberry Mine traffic is expected to continue as the life of the mine is being extended from 2014 to 2021 (Imperial Metals Corp. 2012). Additional mining-related traffic in 2010 included Yukon Zinc's Wolverine Mine in the Yukon, which began hauling to the port of Stewart along highways 37 and 37A at an estimated rate of 18 one-way trips per day (Tobin 2009).


Highway 37A

Combined traffic from the Eskay Creek and Huckleberry mines along Highway 37A is presented in Figure 2.1-6. Based on the cumulative AADT of AMS's haul trucks along Highway 37A, an average of 24 one-way trips were made between 2000 and 2006 (AMS, pers. comm., 2010). Haul traffic began declining in 2007 when the last haul by AMS was recorded from the Eskay Creek Mine. In 2009, a total of 10 one-way trips per day were made from the Huckleberry Mine along Highway 37A. Between 2000 and 2008, haul traffic along Highway 37A accounted for between 4 and 7% of overall AADT along the route (Table 2.1-5).

2.1.3.2 Forestry Traffic


Forestry hauling information was collected from the BC Ministry of Forests, Mines and Lands (BC MFML 2010a, 2010b). There are no available historical data regarding the number of forestry haul trucks on Highway 37. To determine the contribution of forestry haul traffic to historical SADT, estimates were derived from the total volume (in cubic metres) of wood scaled within the Kalum Forest District between 1995 and 2009. This only includes forestry trucks from the Skeena Stikine Forest District, and the former Kispiox Forest District (G. Olsen, pers. comm., 2011). The forestry trucks included in these data would have travelled along highways 37 and 37A to various sites, travelling from the Brown Bear Forestry Service Road (FSR), north of Meziadin Junction into Stewart.

a) Combined Mining Traffic for Arrow Mining Services (2000-2009)



Source: AMS (Pers. Comm., 2010).


b) Combined Mining Traffic for Arrow Mining Services (2000-2009)



Source: AMS (Pers. Comm., 2010).

Combined Annual Daily Traffic from Eskay Creek and Huckleberry Mines on Highways 37 and 37A

Figure 2.1-5



Note: SADT represents forestry harvest season in the Stewart area, which occurs between late-November and mid-March, and late-June and mid-October.
 Source: BC MFML 2010.

Table 2.1-5. Combined Annual Average Daily Traffic from Eskay Creek and Huckleberry Mines on Highway 37A

Year	Highway 37A	
	Mining Haul AADT	% of Total AADT
2000	21	4%
2001	26	6%
2002	25	-
2003	28	-
2004	25	-
2005	22	7%
2006	20	-
2007	16	-
2008	9	4%
2009	10	-

Source: AMS (pers. comm., 2010).

- : Data not available as permanent traffic counters along Highway 37A were removed in 2001.

Since traffic figures are estimates based on overall volume of wood scaled, they may be considered the approximate minimum number of forestry haul trips for each year along this route. Other logging traffic not accounted for in these data may include logging trucks that were scaled elsewhere that may have driven on highways 37 and 37A, and logging traffic travelling between the Yukon border and Smithers, which has accounted for up to approximately 30 to 40 truckloads of processed timber per year (Rescan 2010a).

Through the 1990s, raw log transport between the Brown Bear FSR and Stewart was a significant contributor to highway traffic. Harvesting in the region typically occurs from late November through to mid-March, and from late June to mid-October. Freezing and thawing periods were not included as forestry roads are unusable during these periods. Peak periods for forestry haul traffic occurred in the late 1990s. During this time, between 10,000 and 16,000 loads were transported each year (Figure 2.1-6). By 2001, a downturn in the regional forestry industry resulted in a significantly lower volume of haul traffic. This trend continued through the 2000s, with an average 8,600 one-way trips annually between 2001 and 2009. The slowest year to date is 2009, with 1,020 one-way trips, and an AADT of 3 (Figure 2.1-6). Forestry traffic was approximately 16 and 38% of overall AADT during peak years, but less than 10% during slow forestry years (Table 2.1-6). A decline in the Japanese timber export market in 1996 and 1997 resulted in a significantly lower volume of traffic (G. Olsen, pers. comm., 2011).

2.1.3.3 Commercial Traffic

Highway 37

A number of commercial carriers have operated in northwestern BC over the past 30 years, including Lindsay's Cartage and Storage, Canadian Freightways and Bandstra Transportation Systems. Commercial haul traffic includes goods, heavy equipment, container shipping and mining services; however, Bandstra has not hauled industrial mining shipments since the 1990s (Van Essen, pers. comm.). Currently, Canadian Freightways and Bandstra are the most active carriers along the Highway 37 corridor. Over the past ten years Bandstra has provided an average of two regularly scheduled trips to Stewart and two to Dease Lake per week. Peak years during this period were 2007 and 2008, which averaged one round trip per day along Highway 37, with a maximum of six round trips per day. Increased traffic during these two years was primarily associated with development related to the Galore Creek mining project (Van Essen, pers. comm.).

Table 2.1-6. Forestry Haul Traffic as a Percentage of Overall Summer Average Daily Traffic on Highways 37 and 37A

Year	Forestry Haul SADT	Percent of Total SADT ¹ Highway 37, Meziadin to Stikine	Percent of Total SADT ¹ Highway 37A
1995	132	18%	16%
1996	37	9%	6%
1997	43	12%	6%
1998	83	26%	34%
1999	109	32%	38%
2000	106	23%	19%
2001	55	14%	10%
2002	37	-	-
2003	50	-	-
2004	47	-	-
2005	18	8%	-
2006	25	-	-
2007	40	-	-
2008	16	7%	-
2009	4	-	-

¹SADT represents forestry harvest season in the Stewart area, which occurs between late-November and mid-March, and late-June and mid-October.

- Data not available, only periodic traffic counts were taken in 2005, and 2008 north of Meziadin Junction.

Highway 37A

Through the 2000s, Bandstra Transportation Systems averaged two scheduled shipments per week to Stewart (Van Essen, pers. comm.). Other commercial carriers in the region include Canadian Freightways.

2.1.3.4 Average Commercial Truck Speed

BC MOTI conducted a study on the speeds of heavy long-distance commercial trucks on provincial highways between 2004 and 2005 (BC MOTI 2006). Satellite tracking data revealed that average speeds were approximately 80 km/h in uncongested rural areas of the province, and typically lower (as low as 25 km/h) in urban areas. Commercial truck traffic was found to travel at approximately 80% of the posted speed limit. The average posted speed along Highway 37 between Kitwanga and the Yukon border was just above 80 km/h, while observed average truck speeds were approximately 70 km/h in 2004 and 65 km/h in 2005. Just recently, the speed limit on Highway 37 from Meziadin Junction to the Yukon border has been increased to 90 km/h (S. Applegate, pers. comm., 2012)

2.1.4 Highway Capacity

The capacity of a highway is reached when the Level of Service (LOS) reaches a rating of “E”¹ A report conducted by McElhanney for the Project (2011, Appendix B), based on traffic volume data collected in 2008, and using methodologies outlined in the Highway Capacity Manual (TRB 2000), estimated that the capacity of Highway 37 for a representative segment of highway (rolling terrain and 40% of length

¹ LOS for a highway is rated, in descending quality, as “A” (highest), “B”, “C”, “D” and “E”(lowest), based on criteria such as the percentage of time a driver is immediately behind another vehicle, the two-way hourly volume (measured in vehicles per hour), and the two-way flow rate (pc/h). See Table 2 in Appendix B for further details.

no-passing) is a two-way volume of 1,260 passenger cars per hour (pc/h), or 630 pc/h in each direction². Commercial trucks are equivalent to 2.5 passenger cars, modifying the capacity to 504 commercial vehicles per hour two-way or 252 commercial vehicles per hour one-way. Highway 37 operated at LOS “A” based on data collected in both 1992 and 2008. It was predicted that peak hour traffic volumes would have to increase by 300% over 2008 volumes (73 pc/h) for the highway to be downgraded to LOS “B”. In other words, Highway 37 has significant excess capacity available.

2.2 KSM PROJECT OVERVIEW

The Project intends to mine four mineral deposits: Kerr, Sulphurets, Mitchell and Iron Cap, which contain significant amounts of gold, copper, silver and molybdenum. The Project footprint will consist of two distinct and geographically separate areas: the Mine Site, and the Process Plant and Tailing Management Area (PTMA).

The Mine Site is located in the drainage basin of Sulphurets Creek, a tributary of the Unuk River. It will be accessed via the existing Eskay Creek Mine road and the new, 34-kilometre Coulter Creek access road. Mining operations will include open pit mining of the Kerr, Sulphurets and Mitchell pits, and underground mining of the Mitchell and Iron Cap deposits later in operation. Ore from the Mine Site will be conveyed through 23 km twin tunnels to the Process Plant. Waste rock will be stored near the open pits. Surface water that contacts disturbed areas will be collected via a Water Storage Pond and treated at a Water Treatment Plant, as appropriate.

The PTMA will be located in the upper Teigen Creek/Treaty Creek valley; both of these creeks flow into the Bell-Irving River. A new road along Treaty Creek and North Treaty Creek will connect the Process Plant to Highway 37. The Process Plant will process up to 130,000 tonnes of ore per day to produce approximately 1,200 tonnes of concentrate daily, which will be trucked to the Port of Stewart. The tailing will be pumped to the TMF. The TMF has capacity to hold all of the estimated 2.3 billion tonnes of tailing that will be produced over the estimated 51.5-year mine life.

2.3 TRANSPORTATION REQUIREMENTS

The Project will transport personnel, supplies, equipment and hazardous cargo including diesel fuel and lubricants, lime and reagents, explosives and concentrates, to and from the mine during the construction, operation, closure and post-closure phases. Examples of vehicles that will be used include bulk B-train trucks, and fuel tanker trucks (see Plates 2.3-1 and 2.3-2; Udovicic 2012).

The Project will use a marshalling/staging area in Smithers, BC or other nearby communities to receive and deliver equipment and supplies to the site during the construction and operation phases. Heavy equipment may be transported by transport truck, port or rail to the closest viable rail siding at Smithers, and then loaded onto transport trucks and taken to the Project site along Highway 16 or Highway 37 north to the junction of the Project access roads (Wardrop 2011).

The proposed transportation route for copper concentrate from the Project site is via highways 37 and 37A. Copper concentrate will be transported about 185 km by contract trucking firms to a storage and concentrate loading facility site near Stewart, where it will be loaded and shipped to overseas smelters in Asia (Wardrop 2011).

² For reference purposes, the base level capacity of a two-lane highway assuming ideal conditions is 1,700 pc/h one-way or 3,200 pc/h for two-way scenarios.



Plate 2.3-1. Bulk B-train truck example.



Plate 2.3-2. Fuel tanker truck example.

Molybdenum concentrate will be transported in bags from the Project site via trucks along Highway 37 south and then Highway 16 west to the port of Prince Rupert. The bags will be transferred from the trucks to containers and then delivered to Fairview Terminal for loading onto an oceangoing vessel (Wardrop 2011).

Figure 2.3-1 illustrates the proposed cargo routes by Project phase, and identifies the cargo that will be transported during each phase, within the Study Area for this assessment.




Figure 2.3-1

2.4 PROJECTED TRAFFIC VOLUMES

Traffic volumes from the Project along highways 37 and 37A (measured in average annual one-way trips) were estimated by Wardrop in 2012 (Appendix C) based on the 2012 Pre-Feasibility Study (PFS) design and capital cost estimates for the Project.

Estimates were projected for the construction, operation, closure, and post-closure phases respectively, and are considered accurate at the time the report was prepared. Traffic volume estimates for the different highway segments within the Study Area were also identified (see Tables 2.4-1 through 2.4-4). For example, 48' Flat-Deck vehicles carrying infrastructure (shown in the first line of Table 2.4-1), there would be 613 one-way trips along Highway 37 from Kitwanga to Meziadin Junction. At Meziadin Junction, 218 vehicles turn and travel west along Highway 37A (to the temporary Frank Mackie Glacier access route), while 395 vehicles continue north along Highway 37 to the Treaty Creek access road junction. Of the 395 vehicles, 111 continue to the Eskay Creek Mine Road junction.

Table 2.4-1. Total Average Annual One-way Trips by Route for Construction

Vehicle Type	Cargo	Route			
		Highway 37 (Eskay-Treaty Treaty-Eskay)	Highway 37 (Treaty-Meziadin Meziadin-Treaty)	Highway 37A	Highway 37 (Meziadin-Kitwanga Kitwanga-Meziadin)
48' Flat-Deck	Infrastructure	111	395	218	613
Vans (Enclosed Trailers)	Infrastructure	36	132	72	204
48' Flat-Deck	Camps & Support Facilities	292	777	-	777
Vans (Enclosed Trailers)	Camps & Support Facilities	98	259	-	259
48' Flat-Deck	Mine Site	774	786	376	1,162
Vans (Enclosed Trailers)	Mine Site	258	261	126	387
48' Flat-Deck	Plant Site	-	2,380	-	2,380
Vans (Enclosed Trailers)	Plant Site	-	794	-	794
Bus & Passenger Vehicles	Crew Transport	427	861	10	871
48' Flat-Deck	Equipment	158	253	28	281
Vans (Enclosed Trailers)	Equipment	53	84	10	94
48' Flat-Deck	Materials	132	394	-	394
Vans (Enclosed Trailers)	Materials	44	132	-	132
48' Flat-Deck	Flocculant*	18	18	-	18
Bulk Tanker	Lime*	279	279	-	279
Tanker (45,000 L)	Fuel*	198	215	30	445
Vans (Enclosed Trailers)	Explosives*	5	21	10	31
Grand Total (Average Annual)		2,883	8,041	880	9,121
Total** Average Annual Trips per Day		8	22	3	25
Hazardous Materials Annual Trips per Day		1	1	0	1

Source: Wardrop 2012(Appendix C)

- is not applicable

0 is where numbers were rounded to 0

* counted in calculations for hazardous materials annual trips per day

** includes both hazardous and non-hazardous cargo

Table 2.4-2. Total Average Annual One-way Trips by Route for Operation

Vehicle Type	Cargo	Route			
		Highway 37 (Eskay-Treaty Treaty-Eskay)	Highway 37 (Treaty-Meziadin Meziadin-Treaty)	Highway 37A	Highway 37 (Meziadin-Kitwanga Kitwanga-Meziadin)
Bulk B-Train	Copper concentrates*	-	13, 200	13, 200	-
Super-B Train	Molybdenum concentrates*	-	86	-	86
Vans (Enclosed Trailers)	Lime & All other reagents*	-	8,440	-	8,440
48' Flat-Deck	Grinding Media	-	2,810	-	2,810
Tanker (45,000 L)	Fuel & Lubricants*	-	2,296	-	2,296
Bus & Passenger Vehicles	Personnel, Visitors & Maintenance	-	408	-	408
Vans (Enclosed Trailers)	Camp Supplies	-	480	-	480
Super-B Trucks	Explosives*	925	925	-	925
Bulk Tanker	Lime - Water Treatment*	-	1,278	-	1,278
48' Flat-Deck	Flocculant - Water Treatment*	-	20	-	20
48' Flat-Deck	Parts & Machinery	-	1,136	-	1,136
48' Flat-Deck	Major Mine Equipment	79	79	-	79
Grand Total (Average Annual)		1,004	31,158	13,200	17,958
Total** Average Annual Trips per Day		3	85	36	49
Hazardous Materials Average Trips per Day		3	36	18	18

Source: Wardrop 2012(Appendix C)

- is not applicable

0 is where numbers were rounded to 0

* counted in calculations for hazardous materials annual trips per day

** includes both hazardous and non-hazardous cargo

Table 2.4-3. Total Average Annual One-way Trips by Route for Closure

Vehicle Type	Cargo	Route			
		Highway 37 (Eskay-Treaty Treaty-Eskay)	Highway 37 (Treaty-Meziadin Meziadin-Treaty)	Highway 37A	Highway 37 (Meziadin-Kitwanga Kitwanga-Meziadin)
48' Flat-Deck	Infrastructure	-	221	-	221
48' Flat-Deck	Camps & Support Facilities	-	250	-	250
48' Flat-Deck	Mine Site	-	662	-	662
48' Flat-Deck	Plant Site	-	1,511	-	1,511
48' Flat-Deck	Materials	-	143	-	143
Bus & Passenger Vehicle	Personnel	-	210	-	210
Super-B Trucks	Infrastructure	-	74	-	74
Super-B Trucks	Camps & Support Facilities	-	84	-	84
Super-B Trucks	Mine Site	-	221	-	221
Super-B Trucks	Plant Site	-	504	-	504
Super-B Trucks	Materials	-	48	-	48
Super-B Trains	Lime - Water Treatment*	-	1,000	-	1,000

(continued)

Table 2.4-3. Total Average Annual One-way Trips by Route for Closure (completed)

Vehicle Type	Cargo	Route			
		Highway 37 (Eskay-Treaty Treaty-Eskay)	Highway 37 (Treaty-Meziadin Meziadin-Treaty)	Highway 37A	Highway 37 (Meziadin-Kitwanga Kitwanga-Meziadin)
48' Flat-Deck	Flocculant - Water Treatment*	-	18	-	18
Tanker (45,000 L)	Fuel*	-	888	-	888
Grand Total (Average Annual)		-	5,834	-	5,834
Total** Average Annual Trips per Day		-	16	-	16
Hazardous Materials Average Trips per Day		-	3	-	3

Source: Wardrop 2012(Appendix C)

- is not applicable

* counted in calculations for hazardous materials annual trips per day

** includes both hazardous and non-hazardous cargo

Table 2.4-4. Total Average Annual One-way Trips by Route for Post-closure

Vehicle Type	Cargo	Route			
		Highway 37 (Eskay-Treaty Treaty-Eskay)	Highway 37 (Treaty-Meziadin Meziadin-Treaty)	Highway 37A	Highway 37 (Meziadin-Kitwanga Kitwanga-Meziadin)
Bulk Truck	Lime - Water Treatment*	-	2,190	-	2,190
Lowboy Flat Deck	Sludge Haul & Maintenance Equipment	-	20	-	20
48' Flat-Deck	Flocculant - Water Treatment*	-	18	-	18
Bus & Passenger Vehicles	Personnel	-	24	-	24
Vans	Food & Misc Supplies	-	12	-	12
Tanker (45,000 L)	Fuel*	-	16	-	16
Passenger Vehicles	Visitors & Maintenance	-	8	-	8
Grand Total (Average Annual)		-	2,288	-	2,288
Total** Average Annual Trips per Day		-	6	-	6
Hazardous Average Trips per Day		-	3	-	3

Source: Wardrop 2012(Appendix C)

- is not applicable


* counted in calculations for hazardous annual trips per day

** includes both hazardous and non-hazardous cargo

Estimates for all cargo types were added to obtain the total average annual traffic estimates for each Project phase. The total average annual trips per year are then divided by 365 to provide an estimate of expected trips per day along each highway segment. Figures 2.4-1 and 2.4-2 show trips per day along each segment of the two highways.


2.4.1 Construction Phase Activities

During the construction phase, equipment, materials, and supplies to build camps roads and infrastructure will be shipped to the Project site (Table 2.4-1). During the first three years of construction, the Temporary Frank Mackie Glacier access route will be used to transport equipment and materials. Traffic accessing this route will originate in Stewart, with half of the cargo being delivered to Stewart by barge, and the other half being delivered by truck (via highways 37 and 37A). During the remaining years of construction, all traffic will use the Eskay Creek Mine /Coulter Creek and Treaty Creek access roads.



**One-way Trips per Day during
Each KSM Project Phase**

Figure 2.4-1



KSM Project Traffic Study - One-way Trips per Day during each Project Phase

Figure 2.4-2

2.4.2 Operation Phase Activities

During operation, diesel fuel and lubricants, personnel, camp supplies, lime and reagents, and parts/machinery will be transported to the Project site via Highway 37 and along the Treaty Creek access road and, when necessary, through the Mitchell-Treaty Tunnel to supply the Mine Site. Explosives and major mine equipment required at the Mine Site will be transported via Highway 37 to the Eskay Creek Mine/Coulter Creek access roads.

Copper concentrate will be trucked in bulk form super-B trucks with a capacity of 50 tonnes to Stewart Bulk Terminals in Stewart. The heavier payload assumes the allowance of heavier loads under the provincial Bulk Haul Program (BC MOTI 2010). Molybdenum concentrate will be loaded in 2 tonne bags and transported on super-B flat deck trucks south along Highway 37 and then on to Prince Rupert. Gold and silver doré will be shipped from site via air transport for security purposes.

2.4.3 Closure Phase Activities

During closure, the Project will be decommissioned, all equipment and material except foundations will be removed, and reclamation activities will be completed. Traffic volumes for the closure phase are estimated to be approximately 70% of the traffic required to transport material/equipment during the construction phase. All traffic is expected to be via Highway 37, the Treaty Creek access road, and through the Mitchell Treaty Tunnel when access to the Mine Site is required. The Coulter Creek access road will be decommissioned and reclaimed.

2.4.4 Post-closure Phase Activities

During post-closure, traffic will move via Highway 37, the Treaty Creek access road, and through the Mitchell Treaty Tunnel when access to the Mine Site is required. Equipment, supplies and personnel will be required to continue operation of the Water Treatment Plant and the hydro facilities, as well as for monitoring and maintenance. It is assumed that activities and traffic volumes will be consistent throughout the entire post-closure phase.

2.4.5 Hazardous Cargo

In Tables 2.4-1 through 2.4-4, the average annual number of trips was further broken down to show the proportion of the traffic expected to transport hazardous cargo. The total number of trips in cargo categories considered to be hazardous (marked with a single asterisk in the aforementioned tables) were added together for each Project phase, divided by two so that empty vehicles are not counted as hazardous cargo, and then divided by 365 to show the average number of trips per day expected to be carrying hazardous cargo.

Hazardous materials to be transported throughout the life of the Project include:

- fuel and lubricants;
- concentrate (copper and molybdenum);
- lime and reagents for the Process Plant and water treatment (including flocculant); and
- explosives.

2.4.5.1 Fuel and Lubricants

Fuel will be required during construction for power generation, and throughout the life of the Project for activities like building heating, equipment operation and maintenance. Diesel fuel is assumed to be sourced from Terrace, BC, and delivered in super-B tanker trucks with a capacity of 45,000 litres per truck.

During the construction phase, fuel will be transported along Highway 37 and then via the Treaty Creek and Eskay Creek Mine/Coulter Creek access roads, as well as along Highway 37A to the Temporary Frank Mackie Glacier access road.

During the operation phase, annual traffic volumes for diesel fuel will vary from year to year, generally coinciding with mine production rates. Both diesel fuel and lubricants will be transported along Highway 37, along the Treaty Creek access road to the Plant Site, and through the Mitchell Treaty Tunnel if required at the Mine Site.

2.4.5.2 Concentrate

Copper Concentrate

During operation, hauling of copper concentrate will comprise the majority of the expected traffic volumes on the highways within the Study Area. Copper concentrate will be transported during operation from the Plant Site via the Treaty Creek access road, and along Highway 37 to Meziadin Junction, and then along Highway 37A to the Port of Stewart.

A Toxicity Characterization Leaching Procedure - EPA 1311 test was performed to determine if KSM copper concentrates are hazardous under BC MOE's Hazardous Waste Regulation (BC Reg. 63/2009). Briefly, during the EPA 1311 test, the copper concentrate was agitated in acidic extraction fluid and metal concentrations were subsequently analyzed in the extract. G&T Metallurgical Services provided a composite concentrate sample (PP3 Composite Bench Test Concentrate) obtained from two pilot test runs (PP2 and PP3); the analytical lab processed this sample as KM#2670 Bulk Concentrate to the analysis laboratory. The metal concentrations in the resulting extract were compared to Canadian Council of Ministers of the Environment (CCME) and BC water quality guidelines for the protection of aquatic life (BC MOE 2006; CCME n.d.) to detect exceedances. Leachable antimony, arsenic, cadmium, chromium, copper, iron, lead, mercury, nickel, selenium, silver, thallium, vanadium, and zinc concentrations exceeded either the CCME or the BC water quality guidelines, or both. However, environmental conditions are far less acidic than the leach test conditions and the concentrate itself is alkaline, and the EPA1311 test does not take dilution into account.

Table 2.4-5 shows the results of toxicity testing on KSM copper concentrate.

Molybdenum Concentrate

Molybdenum concentrate is assumed to be transported south from the PTMA along Highway 37 to Highway 16, and then west along Highway 16 to the port of Prince Rupert. While it is acknowledged that molybdenum concentrate is also potentially toxic, only 43 shipments of concentrate (i.e., 86 one-way trips) are anticipated per year during the operation phase. This is an anticipated average of 0.23 trips per day of molybdenum concentrate, or one trip every four or five days. In contrast, 6,600 shipments of copper concentrate per year (i.e., 36 one-way trips per day) are anticipated during operation. Due to the infrequency of transport of molybdenum concentrate, the biophysical and social risks from the transport of molybdenum concentrate are considered negligible, and are not considered further in this assessment.

2.4.5.3 Lime and Reagents

Water treatment is assumed to begin in the construction phase using temporary treatment facilities. Later during construction, the permanent Water Treatment Plant (WTP) will become operational and will continue treatment through post-closure.

Table 2.4-5. Copper Concentrate Toxicity Characterization Leaching Results Compared to Canadian Drinking Water Guidelines

TCLP Metals	Detection Limits mg/L (except pH)	Results of Analysis mg/L (except pH)	CCME Water Quality Guidelines ¹ mg/L	BC Working Water Quality Guidelines (Aquatic Life) mg/L	Canadian Drinking Water Guidelines (MAC) ⁴ mg/L
1st Preliminary PH	0.10	5.94	N.A.	N.A.	N.A.
2nd Preliminary PH	0.10	1.42	N.A.	N.A.	N.A.
Final pH	0.10	4.95	N.A.	N.A.	N.A.
Extraction Solution Initial pH	0.10	4.93	N.A.	N.A.	N.A.
Antimony (Sb)-Leachable	1.0	< 1.0	N.G.	0.02	*0.006
Arsenic (As)-Leachable	1.0	< 1.0	0.005	0.005	0.01
Barium (Ba)-Leachable	2.5	< 2.5	N.G.	N.G.	1.00
Beryllium (Be)-Leachable	0.025	0.01	N.G.	N.G.	N.G.
Boron (B)-Leachable	0.50	0.25	1.50	1.20	*5
Cadmium (Cd)-Leachable	0.050	0.10	0.000,00457 ²	0.000,00457 ²	0.005
Calcium (Ca)-Leachable	2.0	132.00	N.G.	N.G.	N.G.
Chromium (Cr)-Leachable	0.25	< 0.125	0.001 ³	0.001 ³	0.05
Cobalt (Co)-Leachable	0.050	0.07	N.G.	0.11 (maximum), 0.004 (30-day average)	N.G.
Copper (Cu)-Leachable	0.050	25.50	0.002 ²	0.0029 ² (maximum), 0.002 (30-day average)	≤ 1
Iron (Fe)-Leachable	0.15	0.57	0.30	0.35 ⁵ , 1.0 ⁶	≤ 0.3
Lead (Pb)-Leachable	0.25	9.19	0.001 ²	0.004 ² (maximum and 30-day average)	0.01
Magnesium (Mg)-Leachable	0.50	8.83	N.G.	N.G.	N.G.
Mercury (Hg)-Leachable	0.0010	< 0.0010	0.000,026	0.00002 (30-day average when MeHg = 0.5% of THg)	0.001
Nickel (Ni)-Leachable	0.25	0.13	0.025 ²	0.025 ²	N.G.
Selenium (Se)-Leachable	1.0	< 1.0	0.001	0.002	0.01
Silver (Ag)-Leachable	0.25	0.13	0.0001	0.0001 (maximum), 0.00005 (30-day average) ²	N.G.
Thallium (Tl)-Leachable	1.0	< 1.0	0.0008	0.0003	N.G.
Vanadium (V)-Leachable	0.15	0.08	N.G.	0.006	N.G.
Zinc (Zn)-Leachable	0.50	4.42	0.03	0.033 (maximum), 0.0075 (30-day average) ²	≤ 5

¹ CCME Water Quality Guidelines for the Protection of Aquatic Life (Freshwater)

² based on a hardness of 10 mg/L CaCO₃

³ Guidelines presented for hexavalent chromium Cr(VI)

⁴ Maximum acceptable concentration

⁵ Guidelines presented short-term maximum guideline for dissolved iron concentrations

⁶ Guidelines presented short-term maximum guideline for total iron concentrations

* Interim MAC (discontinued by the Federal-Provincial-Territorial Committee on Drinking Water in 2003)

N.A. = Not Applicable; N.G. = No Guideline

Grey shading indicates known exceedance of at least one guideline

The water treatment process will require lime and flocculant, which will be transported along Highway 37 and along the Eskay Creek Mine/Coulter Creek access roads to the WTP during construction. During operation, closure and post-closure, lime and flocculant will be transported to the WTP along the Treaty Creek access road and through the Mitchell-Treaty Tunnel.

Process Plant operation will use a number of reagents, detailed in Table 2.4-6, for copper, gold and molybdenum flotation, carbon-in-leach gold recovery, and cyanide recovery and destruction. These reagents will be transported along Highway 37 during the operation phase between Kitwanga and the Treaty Creek access road to the PTMA. More detailed information on lime and reagents expected to be transported to the Process Plant, including their Transportation of Dangerous Goods (TDG) rating, and the estimated number of trucks per day for each reagent, is shown in Table 2.4-6. One of the reagents, sodium cyanide, is classified as posing great danger under TDG regulations (Transport Canada n.d.). Most reagents, however, are not listed in the TDG regulations or pose only a minor danger.

2.4.5.4 Explosives

During construction, explosives will be required for bedrock excavation associated with the road alignment, borrow source development and tunnel construction. During operation, explosives will be used to break apart the rock in the open pits and the underground mines for recovery of the ore. Due to the large volumes of explosives required and the remote location of the Project, explosives will be manufactured on site. The annual volumes of explosives required for the Project varies according to production rates from year to year.

Potentially hazardous materials used to manufacture industrial explosives are Ammonium Nitrate (AN) prill, diesel fuel, initiation systems, ANFO (a combination of ammonium nitrate and fuel oil), and emulsion. During construction and operation, explosives will be transported by super-B trucks with a capacity of 40 tonnes along Highway 37 and the Eskay Creek Mine/Coulter Creek access roads to the Mine Site.

2.5 SUMMARY OF PREDICTED TRAFFIC VOLUMES

In general, historical traffic data within the Study Area is limited due to the inconsistent use of traffic counters along highways 37 and 37A (see Section 2.1.3). In many cases, data were not collected along the entire highway, nor were they collected every year. Although data availability is low, it is the best available information and it is used in this report to provide approximate indicators of traffic trends along the highways, and to estimate existing baseline traffic (Table 2.5-1).

Anticipated traffic volumes for the Project are compared to the estimated baseline traffic levels presented in Table 2.1-2. The highest percentage increase in traffic as a result of the Project is expected during Operation. A 38% increase is expected along Highway 37 between the Treaty Creek access road and Meziadin Junction, and a 15% increase is expected along Highway 37A. This is representative of the Project's copper concentrate haul route. Percentage increases along other highway segments and during the other phases of the Project range between one and ten percent. Despite the modest increases in traffic due to the Project on Highway 37 between Meziadin and Kitwanga (maximum 6% during operation), traffic baseline volumes alone are already 87% of the historical maximum. The remainder of the segments, however, will not see traffic exceeding 30% of historical maximums even with the addition of Project traffic. Traffic increases from the Project along both north and south segments of Highway 37 are well within the design capacity of the Highway.

This information is used throughout this report to assess the potential environmental and social effects of Project traffic along highways 37 and 37A.

Table 2.4-6. Projected Traffic Volumes for Process Plant Lime and Reagents

Process Plant Reagent ¹	TDG Danger Rating ⁴	Description ²	Consumption (t/year)	Trucks ³ per Year	Trucks ³ per Day	Liquid/Solid	Purity/ Concentration (to be transported)	Delivery Packaging
Sodium Hydrosulphide (NaHS)	II	Corrosive; spontaneously combustible	2,000	100	0.27	S	>70%, Solid, Flakes	1 t Bulk Bag
Sodium Cyanide (NaCN)	I	Poisonous (toxic) and infectious substance; toxic and/or corrosive (non-combustible/ water sensitive)	7,800	390	1.07	S	~98%, Solid, Briquettes	1 t tote; Boxed; 2 Plastic Layers Bag (woven polypropylene bags with a heat sealed polyethylene liner)
Sodium Silicate (Na ₂ SiO ₃) (Sodium Metasilicate)	-	High pH (Basic); non-combustible	40	2	0.01	S	>98%, Solid, Powder	25 kg Bag; Pallet
Activated Carbon	III	Flammable and combustible; on contact with water emits flammable gases	100	5	0.01	S	> 95%, Solid, Granulars	500 kg Bulk Bag
Hydrochloric Acid (HCl)	II/III	Toxic and/or corrosive (non-combustible/water sensitive)	720	36	0.10	L	33%- 35% HCl, Liquid	1 t Tote
Sodium Hydroxide (NaOH) (Caustic soda)	II	Toxic and/or corrosive (non-combustible)	5,900	295	0.81	S	> 98%, Solid, Flakes	1 t Bulk Bag
Sodium Metabisulfite (MBS)	-	Low pH (Acidic); moisture and air sensitive; non-corrosive in the presence of glass	6,000	300	0.82	S	~96%, Solid, Powder	1 t Bulk Bag
Copper Sulphate Pentahydrate (CuSO ₄ ·5H ₂ O)	-	Air sensitive; corrosive to finely powdered metals; non-flammable	480	24	0.07	S	>96%, Dry, Powder	1 t Bulk Bag
Sulphuric Acid (H ₂ SO ₄)	II	Corrosive; water-reactive; not combustible	22,000	1100	3.01	L	~ 96% H ₂ SO ₄ , Liquid	1 t Tote or Bulk Truck
PAX (potassium amyl xanthate)	II/III	Corrosive; spontaneously combustible	1,900	95	0.26	S	> 90%, Granular	1 t Bulk Bag
A208 (Diethyl Dithiophosphate)	-	Proprietary reagent	2,300	115	0.32	L	~45% Dithiophosphate	1 t Tote or Bulk Truck
3418A (Dialkyl Dithiophosphinate)	-	Proprietary reagent	380	19	0.05	L	~50% Dialkyl Dithiophosphinate	1 t Tote or Bulk Truck

(continued)

Table 2.4-6. Projected Traffic Volumes for Process Plant Lime and Reagents (completed)

Process Plant Reagent ¹	TDG Danger Rating ⁴	Description ²	Consumption (t/year)	Trucks ³ per Year	Trucks ³ per Day	Liquid/Solid	Purity/ Concentration (to be transported)	Delivery Packaging
3418A (Dialkyl Dithiophosphinate)	-	Proprietary reagent	380	19	0.05	L	~50% Dialkyl Dithiophosphinate	1 t Tote or Bulk Truck
MIBC (Methyl Isobutyl Carbinol)	III	Flammable and combustible liquids (polar/water-miscible/ noxious)	1,500	75	0.21	L	>98%	1 t Tote or Bulk Truck
Flocculant (Magnafloc 336)	-	Proprietary reagent; Slippery; low corrosivity	850	43	0.12	S	>95%	25 kg Bag; Pallet
Anti-scalant	-	Proprietary reagent; interferes with precipitation reactions	380	19	0.05	L	Liquid	1 t Tote
Fuel Oil	III	Flammable and combustible liquids (non-polar/water-immiscible)	950	23	0.06	L	Liquid	Bulk Truck
Lime (Calcium Oxide)	III	Toxic and/or corrosive (non-combustible/water sensitive)	60,000	1500	4.11	S	>90%, Solid, Granulars	Tanker Truck
Ferric Chloride (FeCl ₃)	III	Toxic and/or corrosive (non-combustible)	70	4	0.01	S	>96%, Solid, Flakes	25 kg Bag; Pallet; or 50 kg Drums
Calcium Chloride (CaCl ₂)	-	Normally stable; very soluble in water; not combustible; not corrosive	200	10	0.03	S	~94%, Solid, Powder	25 kg Bag; Pallet
Copper Chloride (CuCl ₂ ·2H ₂ O)	III	Toxic and/or corrosive (non-combustible)	340	17	0.05	S	~98%, Solid, Powder	25 kg Bag; Pallet
Antifoam	-	Proprietary reagent	100	5	0.01	L	Liquid	1 t Tote
Liquid Chlorine (Sodium Hypochlorite)	II/III	Toxic and/or corrosive (non-combustible)	850	43	0.12	L	~99%, Liquid	500 L or 1,000 L Cylinder
TOTAL				4,220	11.57			

Source: Wardrop 2012 (Appendix C)

¹ Table does not include lime and flocculant to be used at the Water Treatment Plant

² As defined by the federal Transportation of Dangerous Goods Regulation class and/or Emergency Response Guide substance classification, or product Materials Safety Datasheet

³ "Trucks" represents loaded trips only, rather than both loaded and empty.

⁴ TDG Danger Rating: I = Great Danger; II = Medium Danger; III = Minor Danger; - = Not Listed.

Table 2.5-1. Estimated Traffic Volume Increases on Highways 37 and 37A Resulting from the KSM Project

	Route/Phase															
	Highway 37 (Eskay to Treaty) North Segment				Highway 37 (Treaty to Meziadin) North Segment				Highway 37A				Highway 37 (Meziadin to Kitwanga) South Segment			
	Construction	Operation	Closure	Post-closure	Construction	Operation	Closure	Post-closure	Construction	Operation	Closure	Post-closure	Construction	Operation	Closure	Post-closure
Estimated Existing Baseline Traffic*	224	224	224	224	224	224	224	224	244	244	244	244	799	799	799	799
KSM Project Traffic	8	3	0	0	22	85	16	6	3	36	0	0	25	49	16	6
Total (Baseline + KSM)	232	227	224	224	246	309	240	230	247	280	244	244	824	848	815	805
Projected Percentage Increase	4%	1%	0%	0%	10%	38%	7%	3%	1%	15%	0%	0%	3%	6%	2%	1%
Historical Maximum Traffic	1014	1014	1014	1014	1014	1014	1014	1014	917	917	917	917	917	917	917	917
Percentage of Historical Maximum	23%	22%	22%	22%	24%	30%	24%	23%	27%	31%	27%	27%	90%	92%	89%	88%
Percentage of Highway 37 Capacity ¹	3.8%	3.7%	3.7%	3.7%	4.0%	5.1%	3.9%	3.8%	n/a	n/a	n/a	n/a	13.6%	14.0%	13.4%	13.3%

¹ Based on Highway 37 modified capacity of 252 commercial vehicles per hour one-way (equivalent to 252 one-way trips per hour) or 6,048 one-way trips per day.

Note: Given that traffic volumes in the 1990s were substantially high, existing baseline traffic was calculated as the average AADT from 2004 to 2011.

3. Vehicle Accidents on Highways 37 and 37A

3.1 HISTORICAL VEHICLE ACCIDENT STATISTICS

Police data for vehicle collisions along Project-relevant segments of highways 37 and 37A are available from 1996 to 2011. Both traffic volumes and accidents have been generally decreasing since 1996. Traffic accidents for this time period are summarized in Figure 3.1-1, and Tables 3.1-1 and 3.1-2.


Table 3.1-1. Vehicle Collisions on Highway 37 between Bob Quinn Camp and Kitwanga

Crash Counts Year	Severity		Total
	Injury or Fatality	Property Damage Only	
1996	15	10	25
1997	12	4	16
1998	5	5	10
1999	17	4	21
2000	10	3	13
2001	7	8	15
2002	7	9	16
2003	10	2	12
2004	8	5	13
2005	5	5	10
2006	2	3	5
2007	7	1	8
2008	6	2	8
2009	2	2	4
2010	4	1	5
2011	1	1	2
Grand Total	118	65	183

Source: ICBC (2011a)

Data are derived from police reports and do not include collisions where police were not notified.³ Collisions are recorded on provincial highways using the Landmark Kilometre Inventory (LKI). The LKI are highway segments defined by the BC MOTI. A segment may consist of one or both sides (directions) of a highway.

³ ICBC generally has more comprehensive collision data than the police, as the insurance company is typically contacted even when police are not notified about a traffic accident. However, the quality of ICBC data is dependent on the insured individual's report. Many submitted reports lack accurate information about the exact location of the collision. In most instances ICBC does not know the exact location of collisions on highways outside of cities, and the collision is classified as being located at the nearest major town. As such, available ICBC data are very limited and only report a fraction of the collisions reported by the police for the same period. Cross-referencing individual collision incidents reported in ICBC and police data is not possible. The use of both data sets may therefore result in double counting. Consequently, only historical police data (provided by ICBC) is considered and analyzed in this report.



Note: R^2 = % trend line.
 Source: ICBC (2011).

Vehicle Collisions on Highway 37 between Bob Quinn Camp and Kitwanga

Figure 3.1-1

Table 3.1-2. Vehicle Collisions on Highway 37A between Stewart and Meziadin Junction

Crash Counts	Severity		Grand Total
	Injury or Fatality	Property Damage Only	
Year			
1996	0	0	0
1997	3	3	6
1998	2	1	3
1999	0	0	0
2000	1	1	2
2001	1	2	3
2002	1	3	4
2003	1	0	1
2004	1	0	1
2005	0	0	0
2006	0	0	0
2007	0	0	0
2008	0	0	0
2009	0	0	0
2010	0	0	0
2011	0	0	0
Grand Total	10	10	20

Source: ICBC (2011b)


Note: Accidents occurring inside the town of Stewart are outside the scope of this study and are not included in these data. There were no police-reported accidents between 2004 and 2011 (ICBC 2011b).

Of the 183 accidents that occurred along the relevant section of Highway 37, 34 (19%) involved a commercial vehicle. Of the 20 reported accidents along Highway 37A, four (20%) involved a commercial vehicle (ICBC 2011a, 2011b).

3.1.1 Vehicle Collision Location Analysis


Historical traffic accidents (1996-2011) along both highway segments are mapped in Figure 3.1-2. Recorded LKI segments in the police data were geocoded and plotted within contiguous 10 km sections of the highways. Over the past 15 years, police reported vehicle collisions have occurred across the entire length of the two highway segments (37 and 37A); however, accidents are concentrated around settlements and near highway junctions and turn-offs. This is unsurprising as traffic accident risks tend to be higher at intersections and in areas of higher use.

The highest proportion of vehicle collisions occurred between Kitwanga and Gitanyow on Highway 37, as depicted in Figure 3.1-3. The southern segment of Highway 37 (Kitwanga to Meziadin Junction) experienced higher daily traffic counts than the northern segment (Meziadin Junction to Stikine River Bridge) between 1996 and 2011. This higher volume of traffic combined with the locations of Kitwanga and Gitanyow on the highway likely contributed to the higher number of vehicle collisions.



Locations of Vehicle Collisions on Highways 37 and 37A, 1996 to 2011

Figure 3.1-2



Locations of Vehicle Collisions on Highway 37 between Kitwanga and Gitanyow, 1996 to 2011

Figure 3.1-3

3.1.2 Seasonal Vehicle Collision Analysis

Annual vehicle collisions by season are depicted in Figure 3.1-4 (Highway 37) and Figure 3.1-5 (Highway 37A). Most traffic accidents along both highway segments have typically been concentrated during the summer months (June-August; ICBC 2011a, 2011b). This corresponds with higher average daily traffic counts on the highways. Consistent average daily traffic counts are available between 1996 and 2001 for both highway segments, and then intermittently for segments of Highway 37 following this period (Figure 3.1-4 and Figure 3.1-5).

3.1.3 Collisions by Vehicle Type and Road Location

Vehicle collisions by type (commercial and non-commercial) and road position (on- or off-highway) are depicted in Figures 3.1-6 and 3.1-7, along with the available daily traffic counts. The majority of vehicle collisions involve non-commercial vehicles, and a small fraction of commercial vehicle collisions involved an “off-road incident”, where the vehicle left the travelled part of the road.

Between 1996 and 2011, the average accident rate for commercial vehicles was 0.0016% for Highway 37, and 0.0002% for Highway 37A.⁴ The average accident rate for non-commercial vehicles, on the other hand, was 0.007% on Highway 37 and 0.0011% on Highway 37A. In other words, there were 77% fewer traffic accidents involving commercial vehicles than non-commercial vehicles on Highway 37, and 81% fewer commercial vehicle traffic accidents on Highway 37A compared to non-commercial vehicles. Historical accident rates per 100,000 vehicles (both commercial and non-commercial) for Highways 37 and 37A are provided in Tables 3.1-3 and 3.1-4, respectively.


3.1.4 Contributing Factors in Vehicle Collisions

The BC Motor Vehicle Branch (2007) describes the following top contributing factors in commercial (heavy and light) vehicle accidents (as a percentage of total commercial vehicle collisions), in order of magnitude:

- driver inattentiveness;
- speed;
- road conditions;
- driver error/confusion;
- failing to yield right of way; and
- following too closely.

In other words, unsafe driving practices and road conditions are largely to blame for the majority of accidents in British Columbia. Neither the amount of traffic, nor the type of vehicle, nor even the working condition of the vehicle plays any significant role in contributing to accidents in the province.

⁴ Accident rates (collisions per 100,000 vehicles) were calculated by dividing the number of vehicle accidents in a year by that year's annualized average AADT (an average of the southern and northern segment was used if both counts were available, if not just the southern segment count was used) and multiplying by 100,000. An average of the accident rates for the period 1996-2011 for each highway was then calculated. After 2001, the AADT count on Highway 37A was terminated and only intermittently recorded along some segments of Highway 37. Where there were gaps in historical data, AADT was extrapolated from available data using excel, where viable.



Available data for AADT and SADT is intermittent after 2001.

Source: BC MOTI 2010, 2012 and ICBC 2011

Definitions:

Summer: June, July, August

Fall: September, October, November

Winter: December, January, February


Spring: March, April, May

AADT: Annual Average Daily Traffic

SADT: Summer Average Daily Traffic

Southern (S) Segment: Kitwanga to Meziadin Junction

Northern (N) Segment: Meziadin Junction to Stikine River Bridge



Available data for AADT and SADT is intermittent after 2001.

Source: BC MOTI 2010, 2012 and ICBC 2011

Definitions:

Summer: June, July, August

Fall: September, October, November

Winter: December, January, February


Spring: March, April, May

AADT: Annual Average Daily Traffic

SADT: Summer Average Daily Traffic

Seasonal Vehicle Collisions on Highway 37A

Figure 3.1-5



Available data for AADT and SADT is intermittent after 2001.

Source: BC MOTI 2010, 2012 and ICBC 2011

Definitions:

AADT: Annual Average Daily Traffic


SADT: Summer Average Daily Traffic

Southern (S) Segment: Kitwanga to Meziadin Junction

Northern (N) Segment: Meziadin Junction to Stikine River Bridge

**Collisions by Vehicle Type on Highway 37
between Kitwanga and Bob Quinn Lake**

Figure 3.1-6



Available data for AADT and SADT is intermittent after 2001.

Source: BC MOTI 2010, 2012 and ICBC 2011

Definitions:

AADT: Annual Average Daily Traffic
 SADT: Summer Average Daily Traffic

Table 3.1-3. Annual Collisions per 100,000 Vehicles on Highway 37 between Kitwanga and Bob Quinn Lake

Year	AADT (S Segment)	AADT (N Segment)	Annualized Average AADT	Total Collisions		Collisions/100,000 Vehicles	
				Commercial Vehicles	Non- commercial Vehicles	Commercial Vehicles	Non- commercial Vehicles
1996	736	419	210,788	2	23	0.9	10.9
1997	750	364	203,305	3	13	1.5	6.4
1998	656	314	177,025	1	9	0.6	5.1
1999	686	346	188,340	6	15	3.2	8.0
2000	698	469	212,978	5	8	2.3	3.8
2001	707	405	202,940	2	13	1.0	6.4
2002	n/a	n/a	n/a	2	14	n/a	n/a
2003	n/a	n/a	n/a	5	7	n/a	n/a
2004	918	237*	210,766	2	11	0.9	5.2
2005	816	238	192,355	2	8	1.0	4.2
2006	795	226*	186,300	0	5	0.0	2.7
2007	838	220*	193,138	0	8	0.0	4.1
2008	740	224	175,930	2	6	1.1	3.4
2009	760	209*	176,884	1	3	0.6	1.7
2010	709	210	167,718	1	4	0.6	2.4
2011	828	198*	187,276	0	2	0.0	1.1
Average collisions per 100,000 vehicles						1.0	4.7
Average Rate of Collision						0.0016%	0.0068%

Notes:

n/a - not available

AADT - Annual Average Daily Total traffic count

* Extrapolated from available data.

Table 3.1-4. Annual Collisions per 100,000 Vehicles on Highway 37A

Year	AADT	Annualized AADT	Total Collisions		Collisions/100,000 Vehicles	
			Commercial Vehicles	Non-commercial Vehicles	Commercial Vehicles	Non-commercial Vehicles
1996	608	221,920	0	0	0.0	0.0
1997	775	282,875	1	5	0.4	1.8
1998	242	88,330	0	3	0.0	3.4
1999	288	105,120	0	0	0.0	0.0
2000	551	201,115	1	1	0.5	0.5
2001	548	200,020	1	2	0.5	1.0
2002	n/a	n/a	0	4	n/a	n/a
2003	n/a	n/a	1	0	n/a	n/a

(continued)

Table 3.1-4. Annual Collisions per 100,000 Vehicles on Highway 37A (completed)

Year	AADT	Annualized AADT	Total Collisions		Collisions/100,000 Vehicles	
			Commercial Vehicles	Non-commercial Vehicles	Commercial Vehicles	Non-commercial Vehicles
2004	318*	116,070	0	1	0.0	0.9
2005	295	107,675	0	0	0.0	0.0
2006	277*	101,105	0	0	0.0	0.0
2007	256*	93,440	0	0	0.0	0.0
2008	248	90,520	0	0	0.0	0.0
2009	215*	78,475	0	0	0.0	0.0
2010	190	69,350	0	0	0.0	0.0
2011	174*	63,510	0	0	0.0	0.0
Average collisions per 100,000 vehicles					0.1	0.5
Average Rate of Collision					0.0002%	0.0011%

Notes:*n/a - not available**AADT - Annual Average Daily Total traffic count*** Extrapolated from available data.***3.2 COLLISION PREDICTION MODELLING**

Collision prediction models (CPMs) were used to predict the annual number of collisions on highways 37 and 37A with increased traffic volume expected during all Project phases. CPMs like the one used for this assessment, are used because the relationship between collision frequency and exposure is frequently non-linear (Sayed and de Leur 2008). CPMs are regression models that estimate collision frequency by capturing systematic relationships between collisions, traffic volumes, and road geometry (Sayed and de Leur 2008).

3.2.1 Methodology

The CPM methodology used for this study was developed specifically for British Columbia highways by Sayed and de Leur (2008), and was adopted by BC MOTI (2009).

Three data elements were required for CPM development. The first was a classification of the highway segments; based on the BC MOTI Classification System, both Highway 37 and Highway 37A were classified as Rural Arterial Undivided Two-lane (RAU2) highways (BC MOTI 2009). The second step was to collect AADT volumes for each highway segment. Traffic volumes for highways 37 and 37A were obtained from BC MOTI (2011e). As discussed in Section 2.1, data for these routes have been collected intermittently since 2001, so historical traffic volumes from 1996 to the present were used in the analysis. The third step was to obtain historical collision data for both roads, which were provided by the Insurance Corporation of British Columbia (ICBC 2011a; 2011b; Section 3.1).

Two different sets of model variables were used to predict: (1) collisions resulting in property damage only (PDO); and (2) severe collisions resulting in human injury or casualty. The variables developed for RAU2 roads are presented in Table 3.2-1.

Table 3.2-1. Collision Prediction Model Variables for Rural Arterial Undivided Two-lane Roads

Collision Type	Model Variables			
	α_0	α_1	α_2	k
PDO	0.005706	0.7523	0.9222	2.138
Severe	0.005242	0.7279	0.9403	2.167

Source: Sayed and de Leur (2008).

A preliminary CPM was developed using the following segment model form (Sayed and de Leur 2008):

$$E(\Lambda) = a_0 V_1^{a_1} L_1^{a_2}$$

- where
- $E(\Lambda)$ = collision frequency
 - L = highway segment length
 - V = segment AADT
 - a_0, a_1, a_2 = model parameters (as shown in Table 2.5-1)

The historical collision data delineated the specific LKI segment where each collision occurred. The relevant historical AADT data separated traffic on Highway 37 into two segments, the northern segment comprising Meziadin Junction to the Stikine River Bridge (LKI 3730 and 3740), and the southern segment comprising Kitwanga to Meziadin Junction (LKI 3710 and 3720). For this reason, separate CPMs were developed for the northern and southern segment of Highway 37. Highway 37A (LKI 3725) was modeled as a single segment (BC MOTI 2011b).

The preliminary CPMs were then calibrated for the specific roadways using an Empirical Bayes (EB) refinement to consider the historical collision data, yielding more accurate, location-specific predictions. The EB refinements were calculated using the following equation (Sayed and de Leur 2008):

$$EB_{safety\ estimate} = \alpha \times prediction + (1 - \alpha) \times observed$$

- where
- $\alpha = \frac{k}{k + prediction}$
 - $observed$ = observed number of collisions
 - $prediction$ = predicted number of collisions from preliminary CPM
 - k = model dispersion parameter (as shown in Table 2.5-1)

The CPMs and their location-specific EB refinements were then applied to the increases to current traffic volumes expected on highways 37 and 37A as a result of the Project during each phase. These traffic estimates are summarized in Table 3.2-2.

Table 3.2-2. Project-related Annual Increases to Traffic Volumes

Project Phase	Average Annual Trips per Day for Project Traffic per Highway Segment		
	Highway 37 North Segment	Highway 37 South Segment	Highway 37A
Construction	22	25	3
Operation	85	49	36
Closure	16	16	0
Post-closure	6	6	0

The CPMs were also applied to the cumulative increases to current traffic volumes expected on highways 37 and 37A as a result of other human actions during the KSM operation phase (the period of highest Project-related traffic volumes). These traffic estimates are summarized in Section 8.3.2.

3.2.2 Limitations of the Models

The effectiveness of the CPMs was limited by the historical data available for the highway segments in question. As is discussed in Section 2.1.3, data for these routes have only been collected intermittently since 2001.

Moreover, it is important to acknowledge the limitations inherent in the models themselves. Many factors that affect collision frequency—such as driver error and weather conditions (and others, as listed in Section 3.1.4)—cannot be accounted for in a CPM. The CPMs can reliably predict the probable mean number of collisions on the highway segments *over time*; however, collisions in any specific year may be higher or lower than the model predictions due to the aforementioned variables. Therefore, the modelling results are used cautiously as broad indicators of probable collision frequency during the Project phases.

3.2.3 Project-specific Results


The results of the Project-specific CPM analysis are presented in Figures 3.2-1 to 3.2-3. The difference in predicted collisions between baseline conditions and the Operation phase (the Project phase with the highest traffic volumes) is summarized in Table 3.2-3.

Table 3.2-3. Predicted Number of Collisions per Year – Baseline vs. Project Operation Phase

Collision Type	Highway 37 North Segment			Highway 37 South Segment			Highway 37 A		
	Baseline	Operation	Change	Baseline	Operation	Change	Baseline	Operation	Change
PDO	1.036	1.133	+0.097	3.693	3.714	+0.021	0.973	1.012	+0.039
Severe	1.525	1.620	+0.095	5.889	5.915	+0.026	1.016	1.061	+0.045
Total	2.561	2.753	+0.192	9.582	9.629	+0.047	1.989	2.073	+0.084


The predicted number of annual collisions is not substantially higher in any Project phase than predictions based on current road traffic. The highest number of Project-related collisions predicted by the model occurs during the Operation phase. On the northern segment of Highway 37 during the Operation phase, a total increase of 0.192 collisions (0.097 PDO collisions and 0.095 severe collisions) per year is predicted. The southern segment of Highway 37 is predicted to experience a total increase of 0.047 collisions (0.021 PDO collisions and 0.026 severe collisions) per year during the Operation phase. The greatest predicted change to Highway 37A also occurs during the Operation phase: a total increase of 0.084 collisions (0.039 PDO collisions and 0.045 severe collisions) per year.

For all road segments in all other Project phases, an increase of less than 0.02 collisions per year is predicted.




Predicted Number of Collisions per Year on Highway 37 North - Baseline Annual Average Daily Traffic vs. Project Phases

Figure 3.2-1



Predicted Number of Collisions per Year on Highway 37 South - Baseline Annual Average Daily Traffic vs. Project Phases

Figure 3.2-2



Predicted Number of Collisions per Year on Highway 37A - Baseline Annual Average Daily Traffic vs. Project Phases

Figure 3.2-3

4. Effects and Risk Assessment Methods

4.1 INTRODUCTION

This chapter describes the methods used to assess potential risks and effects associated with Project traffic on highways 37 and 37A. A risk assessment methodology is used to estimate the likelihood or probability of potentially adverse environmental effects resulting from increased Project-traffic within the Study Area, and is complementary to methods used in Application/EIS where significance determinations are made. The risk assessment approach does not make significance determinations, but is systematic, and can be applied to a variety of situations, both quantitative and qualitative. Risk assessment methods are commonly used in land use and resource management planning, and when assessing risks associated hazards, accidents and malfunctions.

The results of the risk assessment are presented in Chapter 5, grouped by major assessment topic (i.e., socio-economic, fish and aquatic habitat, wildlife, terrestrial ecosystems, wetlands, noise, climate and air quality, human health, and heritage). Each topic-specific assessment considers two scenarios:

1. **Risks of “Project traffic”;** risks associated with normal, intended Project operation activities. Project traffic may include “all traffic”, or be further broken down into “hazardous” and “non-hazardous” cargo or by specific cargo types (e.g., concentrates, lime and reagents, etc.), as appropriate for the topic being discussed.
2. **Risks of “traffic accidents”;** risks associated with unintended events, may be divided into “off-road” and “on-road” accidents. “On-road” refers to a traffic accident where vehicles remain on the travelled part of the road, while “off-road” refers to accidents that result in a vehicle leaving the travelled part of the road. Traffic accidents may include “all traffic”, or be further broken down into “hazardous” and “non-hazardous” cargo or by specific cargo types (e.g., concentrates, lime and reagents, etc.), as appropriate for the topic being discussed. The results of the potential risk of traffic accidents are then summarized in Chapter 6.

The risk assessment of potential effects for each topic comprises the following three steps:

1. **Baseline Data Overview:** Summarize environmental and socio-economic baseline information for the Study Area (Figure 1.2-1);
2. **Issue scoping:** Define the scope of the assessment using the following approach in sequence:
 - a) **Assessment topic scoping:** Project traffic and traffic accident scenarios are considered in relation to assessment topics. Scenarios with potential for traffic-related risks to the environmental topic are carried forward into the risk assessment (“scoped-in”), while those topics that are not expected to be affected are excluded from further consideration (“scoped-out”). A clear rationale for either choice is provided.
 - b) **Valued Component scoping:** Within each scoped-in assessment topic from the previous exercise, specific VCs are identified for further analysis.
 - c) **Identify potential traffic/Valued Component interactions:** If the scoped-in traffic types and VCs from the preceding two exercises have potential to interact, the VCs are carried forward into the risk analysis.

3. **Risk analysis:** Potential risks to the VCs identified during issue scoping are characterized, as follows:
 - a) **Risk identification:** for each VC, potential risks are identified and described
 - b) **Risk mitigation:** for each potential risk, the mitigation measures proposed by the proponent are described; and
 - c) **Risk characterization:** taking mitigation measures into consideration, the likelihood and severity of any realized risks are characterized.

These three steps are described in more detail in Sections 4.2 to 4.4 and depicted in Figure 4.1-1.

4.2 BASELINE DATA OVERVIEW METHODS

The risk assessment described in this document considers the potential effects of Project-related traffic within the Study Area. As a first step in the risk assessment for each of the assessment topics, relevant information about existing biophysical and socio-economic conditions in the Study Area is briefly summarized.

4.3 ISSUE SCOPING METHODS

The risk assessment uses a scoping process to focus on Project traffic with real or perceived potential to pose an environmental or human risk. The scoping process for this risk assessment is informed by land use interviews, information provided by Nisga'a Nation, and First Nations, issues identified during stakeholder consultations, and professional judgement.

Three steps are used to define the scope of the assessment: (1) assessment topic scoping, (2) VC scoping, and (3) identification of potential traffic/VC interactions.

4.3.1 Assessment Topic Scoping Methods

For each assessment topic, scoping begins with broadly identifying the risk potential associated with each traffic type under two scenarios: (1) in the context of Project traffic and (2) in the context of traffic accidents. An identical list of traffic types is used to populate a matrix for each scenario, an example of which is shown in Example Table 4.3-1, where the example of wetlands is used. If a potential risk associated with a particular traffic type was identified, that cell in the matrix is marked and the potential risk was considered further in the next scoping stage. Scoping-in at this stage does not necessarily indicate that there is a confirmed risk associated with that traffic type, but that further analysis is necessary to assess the potential risk in the context of expected Project traffic. A clear rationale is identified for scoping-in some traffic types and excluding others.

4.3.2 Valued Component Scoping Methods

VCs are those parts of the biophysical or human environment deemed important based on social values or scientific concerns. For assessment topics where potential risks associated with traffic are selected for further analysis, as described in Section 4.3.1, relevant potentially affected VCs are identified. For both scenarios (i.e., Project traffic and traffic accidents), a list of potential VCs is generated, drawing from stakeholder consultations and the professional judgement of topic specialists. This list is then used to populate another matrix table, an example of which is shown in Table 4.3-2 using wetlands. The VCs are then selected for (or excluded from) the risk assessment, with a clear rationale provided for either decision. Scoping-in at this stage of the scoping exercise means that a VC is carried forward for further analysis.




Figure 4.1-1

Table 4.3-1. Assessment Topic Scoping Matrix (Example)

Traffic Type	Potential Risk?	Rationale for Selection/Exclusion
<i>Project traffic</i>		
<u>Personnel and non-hazardous cargo</u>		
Personnel	No	<i>This assessment is for the use of existing roads; alterations, upgrades, or maintenance to the road are not considered. Thus, no Project traffic/wetland interactions are expected given that wetlands will not be altered.</i>
Materials, equipment, and supplies	No	
<u>Hazardous cargo</u>		
Diesel fuel and lubricants	No	
Concentrates	No	
Lime and reagents	No	
Explosives	No	
<i>Traffic accidents</i>		
<u>Personnel and non-hazardous cargo</u>		
Personnel	Yes	<i>Traffic accidents have the potential to affect wetlands if accidents occur in or near wetlands, as hydrocarbon contamination may result.</i>
Materials, equipment, and supplies	Yes	
<u>Hazardous cargo</u>		
Diesel fuel and lubricants	Yes	
Concentrates	Yes	
Lime and reagents	Yes	
Explosives	Yes	

Table 4.3-2. Identification and Rationale for Valued Component Selection/Exclusion Matrix (Example)

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	Normal Project Traffic?	Traffic Accidents?	
<i>Wetland Extent</i>	X	X		X	No	No	<i>Extent is affected by direct footprint interactions. As this assessment is based on use of existing highways, potential effects to extent are not expected.</i>
<i>Wetland Function</i>	X	X		X	No	Yes	<i>The use of existing highways will not affect wetlands ability to continue to perform the functions they currently provide; this VC was therefore scoped out. Traffic accidents have the potential to affect wetland function if vehicle crashes or spills occur in wetlands.</i>

¹ "X" indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; "-" indicates that the group did not identify the VC as an issue.

² "Yes" indicates that the VC is selected for further analysis; "No" indicates that the VC is excluded from further analysis.

VCs included in the assessments must meet the following criteria:

- There is spatial overlap between the study area and the VC.
- There is temporal overlap between the Project life span and the VC.
- There is a real or perceived likelihood—as identified by stakeholders or topic specialists—that Project traffic could pose a risk to the VC.

4.3.3 Methods for Identification of Potential Traffic/Valued Component Interactions

The traffic types and VCs identified in the preceding two steps are then used to populate two axes of a potential interactions matrix, an example of which is shown in Table 4.3-3. In light of the baseline data and the assessor’s professional judgement, each traffic type is re-considered. In the case of traffic accidents, on-road and off-road events are considered separately.

Table 4.3-3. Potential Traffic/Valued Component Interaction Matrix (Example)

Traffic Type	VCs	
	<i>Wetland Function</i>	<i><Name of VC 2></i>
<i>Project traffic</i>		
Concentrates	-	
Lime and reagents	-	
<i>Traffic accidents: on-road</i>		
Personnel	-	
Materials, equipment, and supplies	-	
Diesel fuel and lubricants	X	
Concentrates	X	
Lime and reagents	X	
Explosives	X	
<i>Traffic accidents: off-road</i>		
Personnel	X	
Materials, equipment, and supplies	X	
Diesel fuel and lubricants	X	
Concentrates	X	
Lime and reagents	X	
Explosives	X	

“X” indicates that a potential interaction has been identified.

“-” indicates that no potential interaction was identified.

If a traffic type does not have the potential to interact with an identified VC, that cell in the matrix is left blank. If there is a potential interaction, then that cell is marked and the interaction was examined in more detail in the risk analysis (described in Section 4.4). Proponent mitigation measures are not taken into consideration until after the scoping stage of the assessment was complete.

4.4 RISK ANALYSIS METHODS

For each assessment topic, risk analyses under the two scenarios were carried out separately. Risk analysis included three steps: (1) risk identification, (2) risk mitigation, and (3) risk characterization.

4.4.1 Risk Identification Methods

For each of the potential interactions identified at the end of issue scoping (as described in Section 4.3), potential traffic risks to VCs are identified and described. Each risk is documented as being associated with a discrete Project phase (i.e., construction, operation, closure, or post-closure) or with all phases over the Project life. Risks are also described as being associated with a particular traffic type or with all traffic types. Project phases and traffic types are grouped whenever possible. This information is used to populate the first four columns of a risk assessment matrix. A separate risk assessment matrix is filled out for each scenario (i.e., Project traffic and traffic accidents), as shown in Tables 4.4-1 and 4.4-2 using wetlands as an example.

4.4.2 Risk Mitigation Methods

Proposed measures to mitigate and manage each of the potential risks to VCs identified in the preceding step are briefly described in the fifth column of the risk assessment matrices, examples of which are shown in Tables 4.4-1 and 4.4-2. These measures are more thoroughly described in the accompanying text, if necessary.

4.4.3 Risk Characterization

Potential risks to VCs are then considered in the context of the proposed mitigation and management measures. Post-mitigation consequences of realized risks are briefly described in the final column of the risk assessment matrix, as shown in Tables 4.4-1 and 4.4-2. Two aspects of risks are characterized in the sixth and seventh columns of the risk assessment matrix: (1) the likelihood of the risk, and (2) the severity of any risks expected to persist post-mitigation. If a particular risk is judged to be fully mitigated, this is indicated in the final column and the sixth and seventh columns are left empty. In the example of wetlands, Table 4.4-1 is not required as no interaction between wetlands and Project traffic was identified in the preceding steps. Table 4.4-2 would be completed as shown in the example.

The **likelihood** of risk occurrence is evaluated and characterized using the following rating scale:

- Rare: Highly unlikely, but may occur in exceptional circumstances (i.e., there is a greater than 0% change of occurrence). This risk is not expected to be realized.
- Unlikely: Not expected, but there is a small probability that this risk will be realized.
- Possible: This risk may be realized.
- Likely: This risk will probably be realized.
- Certain: This risk is highly likely to be realized.

The **severity** of the consequence, should the risk be realized, was then evaluated and characterized using the following scale:

- negligible;
- minor;
- moderate;
- major; or
- catastrophic.

The descriptors for the severity scale are defined separately for each topic.

Table 4.4-1. Risk Assessment Matrix for Project Traffic (Example)

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
<Name of VC>	<traffic type>	<description of risk>	<phase>	<description of mitigation>	<likelihood rating>	<severity rating>	<description of post-mitigation risk>

Table 4.4-2. Risk Assessment Matrix for Traffic Accidents (Example)

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Wetland Function	All traffic types	deposition of deleterious substances in wetlands from:	All phases	Limit the extent of contamination; Limit the time a contaminant may be in contact with a wetland, and follow spill prevention and emergency response plans	Unlikely	Major	A loss of wetland function within a specific wetland or wetland complex.

5. Assessment of the Potential Risks of Project Traffic

This chapter summarizes baseline information for a variety of disciplines, identifies potential issues and assesses potential risks associated with Project traffic on highways 37 and 37A. The assessment follows the methodology described in Chapter 4.

5.1 SOCIO-ECONOMICS AND LAND USE

5.1.1 Baseline Data Overview

The socio-economic study area falls within the Regional District of Kitimat-Stikine (RDKS) and includes the settlements of Bob Quinn Lake (north of the Eskay Creek Mine access road), Bell II, Meziadin Junction, and the villages of Gitanyow and Kitwanga (Figure 5.1-1).

Communities in this area of northwestern BC are dispersed and isolated from one another, as well as major populations and governance centres. Distances between settlements are long and it is common to travel two or more hours between communities. Isolation can also be exacerbated by the weather, as road closures can restrict access to and from communities. These factors play a large role in determining the frequency and the manner in which residents access, use and relate to much of the social, economic, and heritage environment in the region.

The Nisga'a Nation and First Nations have a physical, cultural, and historical presence within the Study Area. Approximately 32% of the RDKS's population is Aboriginal (Table 5.1-1) and most of the smaller communities along the north-south corridor of Highway 37 are predominantly Aboriginal.

Table 5.1-1. Population and Demographics – Regional District of Kitimat-Stikine

Region	Total Population (2011)	Males (2011)	Females (2011)	Median Age (2011)	Aboriginal Identity (2006)
RDKS	37,361	19,035 (51%)	18,320(49%)	40.3	12,275 (32%)
British Columbia	4,400,055	2,156,600(49%)	2,243,455 (51%)	41.9	196,070 (4.8%)

Source: Statistics Canada (2007, 2012)

The population of the RDKS has generally declined over the past decade or more, largely due to the loss of jobs (e.g., mine closures), particularly among non-Aboriginal communities. This decline is most evident in Stewart (Statistics Canada 2007). The number of males and females remains relatively balanced, and the median age is slightly below the provincial figure of 41.9.

Services vary considerably based on the size of the community. Limited services and accommodations are typical of the smaller communities. The number of recreation, health, social and educational services within the communities has declined in conjunction with a decrease in population. Primary and secondary education facilities exist in many communities, while educational facilities within certain Aboriginal communities do not extend beyond elementary school.

In addition to the highways 37 and 37A transportation corridors, the communities of Stewart and Bob Quinn are each equipped with an airstrip. Small emergency landing strips exist in the area, two of which are located south of Meziadin Junction. A helicopter landing pad is located at Bell II. Mobile cellular phone coverage is unavailable north of Kitwanga.

5.1.1.1 *Economic Development*

The RDKS is considered one of the least economically diversified regions of the province (Horne 2009). Economic development has largely been driven by the area's abundant natural resources. The value of mining and mineral activities has been a strong contributor, and sustainable mineral development is supported by regional land use management plans (BC ILMB 2000a, 2004). However, lack of infrastructure, isolated communities, small populations, long winters and long travel distances have constrained the level of economic development. The Northwest Transmission Line is expected to facilitate the growth of the mining industry in the area, which will bring new economic opportunities to the northwest region.

In 2006, unemployment within the RDKS was approximately 14% (Statistics Canada 2007). Unemployment in the region has usually been above the provincial average, which was 6% in 2006. The recent global economic downturn has also led to a slowing of economic activity within the region.

Employment in logging and mining led to the development of most non-Aboriginal communities in the RDKS, with most forestry activity occurring south of Bell II (BC MOFR 2010b). There are a number of past and current mine operations in the region, as well as mines currently under development or in the planning phase. Past mine operations include Golden Bear gold mine, Snip gold-silver mine, Premier gold-silver mine, Granduc copper mine, Eskay Creek gold-silver mine, and Kitsault molybdenum mine. Current mine and/or exploration developments include the Galore Creek copper-gold mine, Red Chris copper-gold mine, as well as a number of smaller-scale jade mines. Proposed mine projects include the Kutcho copper-zinc mine, Schaft Creek copper-gold-molybdenum-silver mine, and Arctos Anthracite coal mine, as well as the re-opening of the Kitsault molybdenum mine.

Tourism in the region draws tourists from around the world and has grown in recent years. Tourism activities include guide outfitting, hunting, fishing, heli-skiing, and backcountry recreation opportunities. Residents in the four Nisga'a villages and the Tahltan, Gitanyow, and Gitksan (including Skii km Lax Ha) First Nations communities are also involved in resource activities (including mining and mineral exploration), as well as construction and tourism (Rescan 2012b).⁵ Public administration is typically a major employer within these communities. Nisga'a Nation and First Nations also pursue a wide range of sustenance activities (including hunting and fishing), which contribute economically, socially and culturally to their households and communities (BC ILMB 2004).

5.1.1.2 *Communities*

Kitwanga

Kitwanga (Gitwangak) is a small reserve located near the junction of Highway 37 and Highway 16, where the Kitwanga River runs into the Skeena River. The registered population of Kitwanga was approximately 1,216 in 2012 (AANDC 2012b). Approximately one third of the registered on-reserve Gitksan population (33.1% or 402 people) live in Kitwanga (AANDC 2012b).

In 2006, only 50% of the population aged 15 years and over had received a high school certificate. The high school incompleteness rate (50%) was more than twice the provincial rate (20%). A similar proportion of the Kitwanga population obtained trades certificates (11.8%) compared to 11% province-wide.

⁵ For example, out of 22 recently surveyed Nisga'a commercial ventures, four businesses (about 20% of respondents) had worked in the mining, quarrying, oil and gas sector. Six businesses (27.3%) had worked in the construction sector, five in the forestry sector (22.7%), and another five (22.7%) in the transportation sector. Most respondents (14 or 63.6%) indicated that their businesses had worked in the tourism/accommodation/food services sector (Rescan 2012).





Figure 5.1-1a







Figure 5.1-1c



Gitanyow First Nation Territory
Source: BC MFLNRO 2012

Gitksan Territory
Source: GeoBC 2005, Gitksan Treaty Society 2011

Skii km Lax Ha (Wilp) (Territory)
Source: GeoBC 2005, Gitksan Treaty Society 2011

Skii km Lax Ha Traditional Territory
Source: ILMB and Skii km Lax Ha 2008

Tahltan Nation Traditional Territory
Source: TCC 2011

Nass Area as per Nisga'a Final Agreement

Accident Type¹

- Casualty - Commercial Vehicle
- Casualty - Non-commercial Vehicle
- Property Damage - Commercial Vehicle
- Property Damage - Non-commercial Vehicle
- Archaeological Site


Other Features:

- Highway
- Secondary Road
- Stream²
- Wetlands²
- Open Water²
- Traffic Study Area
- Mountain Goat Winter Ungulate Range
- Moose Winter Ungulate Range

Source:
1) Accident Statistics: Province of BC, ICBC Periodicals, Motor-Vehicle Branch.
2) Freshwater atlas: Province of BC, ILMB Crown Registry and Geographic Base Branch (CRGB)
GIS #: KSM-15-144d
Projection: NAD 1983 UTM Zone 9N

1:100,000

0 2 4
Kilometres







Figure 5.1-1f







Figure 5.1-1h



Gitanyow First Nation Territory
Source: BC MFLNRO 2012

Gitksan Territory
Source: GeoBC 2005, Gitksan Treaty Society 2011

Skii km Lax Ha (Wlup) (Territory)
Source: GeoBC 2005, Gitksan Treaty Society 2011

Skii km Lax Ha Traditional Territory
Source: ILMB and Skii km Lax Ha 2008

Tahltan Nation Traditional Territory
Source: TCC 2011

Nass Area as per Nisga'a Final Agreement

1 Indicates total accidents within 10 km section (1996 - 2011)

Accident Type¹

- Casualty - Commercial Vehicle
- Casualty - Non-commercial Vehicle
- Property Damage - Commercial Vehicle
- Property Damage - Non-commercial Vehicle
- Archaeological Site

Highway
 Secondary Road
 Stream²
 Wetlands²
 Open Water²
 Traffic Study Area
 Mountain Goat Winter Ungulate Range
 Moose Winter Ungulate Range

Source:
 1) Accident Statistics: Province of BC, ICBC Periodicals, Motor-Vehicle Branch.
 2) Freshwater atlas: Province of BC, ILMB Crown Registry and Geographic Base Branch (CRGB)

GIS #: KSM-15-144i
 Projection: NAD 1983 UTM Zone 9N

1:100,000

0 2 4
 Kilometres

Kitwanga's economy relies on primary and secondary industries, including natural resources, and manufacturing (Statistics Canada 2007). Forestry has been the main resource industry; however, the closure of the local sawmill in October 2011 (after its reopening in June 2011) has resulted in fewer forestry opportunities in the area.

Kitwanga's total labour force population was approximately 340 people in 2006. Of these, 33.8% were employed and 25% were unemployed. Labour force participation (being either employed or unemployed and seeking work) in the community was 57.4% in 2006. Median earnings in 2005 were reported at \$11,392 (Statistics Canada 2007). The full-time earnings were markedly lower (estimated at \$30,592) than the provincial median level (\$42,230) in 2005. Government transfers were a major source of income, representing 29% of total income.

Kitwanga relies primarily on Hazelton, and to a lesser extent Terrace, for health care and policing. Fire services are provided by the Gitsegukla Fire Hall in Kitwanga. BC Ambulance provides ambulance from Kitwanga. Residents in need of medical attention are transported to the Wrinch Memorial Hospital in Hazelton. The Community Well-Being (CWB) Index score for Kitwanga was 55 in 2006, lower than both the non-First Nations CWB average of 82 and the First Nations CWB average of 57 (AANDC 2011).

Gitanyow

Gitanyow (Gitanyow Indian Reserve 1) is located on the Kitwanga River, 8 km south of Kitwancool Lake, at the confluence of Kitwancool Creek. The Gitanyow First Nation is politically independent, although culturally affiliated with the Gitksan. Gitanyow is located approximately 400 m west of Highway 37 and approximately 140 km northeast of Terrace.

The registered population of the Gitanyow First Nation was approximately 802 in 2012 (AANDC 2012a). Just under half of the population (48% or 382 people) live on the Gitanyow reserve.

In 2006, only 20% of the Gitanyow population aged 15 years and over had completed a high school certificate. (Statistics Canada 2007). The Gitanyow high school incompleteness rate (54%) was more than twice the provincial rate (20%). A higher proportion of the Gitanyow population obtained trades certificates (14%) compared to 11% province-wide.

The unemployment rate for the community of Gitanyow was 51.7% in 2006, up substantially from 34.8% in 2001 (Statistics Canada 2007). Annual full-time median earnings, representing income received as wage or salary, for Gitanyow was \$27,200 in 2005, much lower than the full-time median earnings for BC as a whole (\$42,230).

The economy within the Gitanyow community is rooted in primary and secondary industries, including natural resources, construction and manufacturing (Statistics Canada 2007). Forestry has been the main resource industry; however, the closure of the Kitwanga sawmill in October 2011 has affected the Gitanyow community along with other communities in the area (Gitanyow Hereditary Chiefs 2006).

The total labour force population on Gitanyow Indian Reserve 1 was 275 people in 2006 (Statistics Canada 2007). Of these, 25.5% were employed and 51.7% were unemployed. Labour force participation (being either employed or unemployed and seeking work) in the Gitanyow community was 52.7% in 2006 and 46.9% in 2001. Government transfers were a major source of income, representing 29.5% of total income. This proportion is almost three times higher than the amount for British Columbia overall (10.7%- Statistics Canada 2007).

Gitanyow health services are managed by Gitanyow Human Services (GHS), an office that runs a number of health programs within the community. Health services are primarily procured in Terrace or Hazelton. Policing and ambulance services are provided through the Hazeltons. A local fire department

provides emergency fire protection. The 2006 CWB Index for Gitanyow was 54, lower than the average First Nations score of 57 (AANDC 2010, 2011).

Settlements

Bob Quinn Lake, Meziadin Junction, and Bell II are generally considered tourist destinations, and are significantly smaller than the communities previously discussed. Most businesses are seasonal, including businesses related to fishing, hiking, heli-skiing, snowmobiling, and hunting. Bell II and Bob Quinn Lake have helped support local mineral exploration activities, primarily through the provision of accommodations. Facilities at Meziadin Junction have been decommissioned.

5.1.2 Issue Scoping

5.1.2.1 Socio-economic and Land Use Scoping

Project activities are expected to result in additional traffic volumes on highways 37 and 37A, although not exceeding historical peaks. Potential risks related to traffic are presented in Table 5.1-2.

Table 5.1-2. Socio-economic and Land Use Scoping Matrix

Topic	Potential Risk?	Rationale for Selection/Exclusion
<i>Project traffic</i>	Yes	Project traffic has the potential to affect community well-being due to increased traffic volume on the highways (e.g., vehicle noise and emissions). Project traffic has the potential to affect availability of resources harvested by land users as a result of wildlife-vehicle interactions.
<i>Traffic accidents</i>	Yes	Traffic accidents have the potential to affect socio-economic VCs due to increased traffic volumes. This could pose a safety risk to local residents and tourists travelling along the highways. Traffic accidents may require local emergency services and first responders in the area.

5.1.2.2 Valued Component Scoping

The selected socio-economic VCs and the rationale for their inclusion or exclusion are presented in Table 5.1-3. The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise).

Table 5.1-3. Identification and Rationale for Socio-economic and Land Use Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	...Project Traffic?	... Traffic Accidents?	
Community demographics and infrastructure	-	-	X	X	No	No	A change in traffic volume is not anticipated to affect community demographics or population numbers. No changes to infrastructure are anticipated as Project traffic will be along existing highways.
Education, skills development, and training	X	-	-	X	No	No	No change in education, skills or training is anticipated as a result of Project traffic. Any changes in these areas are anticipated to be directly linked to Project development.

(continued)

Table 5.1-3. Identification and Rationale for Socio-economic and Land Use Valued Component Selection/Exclusion (completed)

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	... Project Traffic?	... Traffic Accidents?	
Community Well-being (CWB)	X	-	-	-	Yes	Yes	Project traffic may result in an increase in vehicle noise and emissions over existing baseline conditions, as well as a decrease in public safety.
Employment and Income	X	-	X	-	No	No	No change in employment and income is anticipated as a result of Project traffic. Any changes in these areas are anticipated to be directly linked to Project development.
Business Opportunities and Economic Development	x		x	x	No	No	No change in business opportunities and economic development is anticipated as a result of Project traffic. Any changes in these areas are anticipated to be directly linked to Project development.
Access	X	X	X	X	No	No	No change in access anticipated as a result of Project traffic. Any changes in these areas are anticipated to be directly linked to Project development.
Hunting and Trapping	X	X	X	X	Yes	No	The proposed Project may affect availability of resources harvested by land users as a result of wildlife/vehicle interactions. Potential subsistence activities carried out by the Nisga'a Nation, Skii km Lax Ha, Tahltan Nation and Gitanyow First Nation could be altered as a result of changes in the availability of resources.

¹ "X" indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; "-" indicates that the group did not identify the VC as an issue.

² "Yes" indicates that the VC is selected for further analysis; "No" indicates that the VC is excluded from further analysis.

Community well-being is a multi-dimensional concept that refers to individual and collective levels of health, satisfaction, quality of life, and standard of living (Kusel 1996; Costa, Silvana, and Scoble 2006; Sirgy et al. 2009). Community Well-being dimensions include financial independence and access to goods and services; sense of individual and community worth; substance misuse; family stress; the quality of the natural environment; and traffic safety.

Community Well-Being (CWB) is the only socio-economic VC to be potentially affected by Project traffic. Potential impacts include nuisance effects from vehicle noise and emissions in the vicinity of the highways, particularly where the highways pass through communities and settlements. Public safety may also be impacted. There may also be perceived impacts on the quality of the natural environment, both due to Project traffic and the type of Project vehicles using the highways (i.e., haul trucks).

Accidents involving Project vehicles have the potential to affect aspects of CWB as they pose a safety risk to residents and tourists travelling along the highways. Traffic accidents could occur anywhere along the highway corridors and could involve one or multiple vehicles and vehicle types.

The Land Use VC, Hunting and Trapping was identified as having the potential to be indirectly affected by Project-related traffic along highways 37 and 37A. Wildlife/vehicle interactions from Project-traffic such as disruption of movement and direct mortality could potentially affect availability of wildlife resources harvested by land users for recreational, subsistence and traditional purposes. This is true mainly for moose and bears. Other harvest resources of interest to land users, including hoary marmots, American marten, and mountain goats, are also not predicted to be at increased risk from vehicle collisions. Subsistence harvest resources, such as fish and edible plants, are not anticipated to be at increased risk from change in traffic. These resources are not considered further in this assessment.

5.1.2.3 Potential Traffic/Valued Component Interactions

The potential traffic/socio-economic and land use interactions associated with Project traffic along highways 37 and 37A are related to the CWB and hunting and trapping VCs (Table 5.1-4). Vehicles will be transporting either non-hazardous or hazardous cargo and accidents could potentially affect public safety. Four broad categories of traffic accidents were considered in this assessment in order to be inclusive of all types of traffic accidents.

Table 5.1-4. Potential Traffic / Socio-economic and Land Use Valued Component Interaction Matrix

Traffic Type	VCs	
	Community Well-being	Hunting and Trapping
<i>Project traffic</i>		
All traffic types	X	X
<i>Traffic accidents: on-road</i>		
All non-hazardous cargo	X	-
All hazardous cargo	X	-
<i>Traffic accidents: off-road</i>		
All non-hazardous cargo	X	-
All hazardous cargo	X	-

“X” indicates that a potential interaction has been identified.

“-” indicates that no potential interaction was identified.

5.1.3 Risk Analysis

5.1.3.1 Community Well-being

This section analyzes the risks associated with Project traffic on the CWB VC. There are four potential effects related to the CWB VC: (1) nuisance effects from vehicle emissions (potential air quality impacts), (2) nuisance effects from vehicle noise, (3) perceived impacts on the quality of the natural environment due to the type and number of Project vehicles, and (4) reduced public safety due to Project traffic and related accidents.

The following sections describe each potential effect and how it relates to the CWB VC. Each of these potential effects, including mitigation, predicted likelihood and severity of effects are discussed in the following sections. Table 5.1-5 describes the scale used to qualitatively assess the risks. The potential risks, mitigation, and evaluation of severity are shown in Table 5.1-6 and Table 5.1-7.

Ambient Air Quality Effects

Risk Identification

The potential for effects on CWB from air quality associated with Project traffic along highways 37 and 37A will exist during all Project phases. However, air emission contributions from the Project will vary for each phase due to changes in traffic volumes. Further, it is anticipated that any potential effects to ambient air quality will be highly localised and experienced within 50 m of the highway corridor.

Project traffic activities will contribute to air quality effects along the highways because of engine combustion emissions. Table 5.1-6 shows the potential risk before and after mitigation. Since engine combustion is continuous for vehicles, the contribution to VCs will occur regularly during all phases of the Project.

Table 5.1-5. Social-economic and Land Use Risk Assessment Severity Scale Descriptors

Descriptor	Definition
Negligible	No measurable or detectable change from baseline conditions.
Minor	Safety conditions differ to a small degree (e.g., within the range of natural variation). Air and noise effects limited to a few individuals. Traffic accidents do not involve any injuries. Land use value differs from the average value for baseline conditions, but is within the range of natural variation and well below threshold values.
Moderate	Air, noise and safety effects limited to communities (Gitanyow, Kitwanga, Bob Quinn Lake, Bell 11, Meziadin Junction) adjacent to the highway. Traffic accidents involve minor injuries. Land use value differs from the average value for baseline conditions, and approaches the range of natural variation, but below threshold values.
Major	Air, noise and safety effects extend to the local community. Traffic accidents include significant injury. Land use value differs from baseline conditions and exceed threshold values so that there will be a detectable change beyond the range of natural variation
Catastrophic	Traffic accidents involve human death. Land use value differs from baseline conditions and exceed threshold values so that there will be a structural and functional changes in land use values beyond the range of natural variation

Risk Mitigation

Vehicle emissions will be minimized using the following mitigation measures:

- switching fuel to more efficient blends;
- optimizing vehicle load rates to minimize the number of trips;
- following procedures and schedules provided by vehicle manufacturers to increase fuel efficiency;
- minimizing idling; and
- ensuring diesel vehicles use low sulfur content fuel as required by law.

Risk Characterization

Project traffic is expected to result in ambient air quality concentrations of Criteria Air Contaminants (CACs) below BC air quality objectives and standards. The maximum potential extent of this effect is anticipated to occur during Operation. Project activities are expected to result in additional traffic volumes, not exceeding historical peaks (in most cases less than 30% of historic maximums), on highways 37 and 37A. Therefore, the risk to the CWB VC due to air quality effects is expected to be minimal. The Project's contribution to vehicle emissions is discussed in further detail in Section 5.7.3.

Noise Effects*Risk Identification*

Potential noise effects associated with Project traffic along highways 37 and 37A could occur through all phases of the Project. However, noise effects on CWB will differ for each phase due to varying traffic volumes.

Health Canada considers noise a human health concern and requires noise assessment to be undertaken as part of an environmental assessment.

Table 5.1-6. Social Risk Assessment Matrix for Project Traffic

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Community Well-being	All traffic types	Reduced ambient air quality from increased vehicle emissions	All phases	Using well maintained vehicles to optimize combustion, using low sulphur fuel, minimize trips on highway	Possible	Minor	Reduced local ambient air quality with minimal risk to community well-being
	All traffic types	Nuisance from increased vehicle noise	All phases	Using well maintained vehicles, minimize trips on highway	Likely	Minor	Minor increase in noise levels of a very localized nature
	All traffic types	Reduced quality of the natural environment	All phases	Using well maintained vehicles, minimize trips on highway	-	-	Fully mitigated
	All traffic types	Reduced public safety	All phases	Ensure appropriate signage along the highway corridor; Enforce speed limits and other traffic rules; Appropriate driver safety training; Company zero-tolerance policy on alcohol; Adhere to accident first aid, emergency response and other procedures; Highway maintenance	Possible	Major	Increase of vehicle accidents and decreased public safety

Table 5.1-7. Social Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Community Well-being	All traffic types	Accidents of varying severity leading to injury or death of drivers, passengers, and other highway users. Hazardous cargo spills from accidents may expose local residents or emergency responders to additional safety risks.	All phases	Ensure appropriate signage along the highway corridor; Enforce speed limits and other traffic rules; Appropriate driver safety training; Company zero-tolerance policy on alcohol; Adhere to accident first aid, emergency response and other procedures; Ensure emergency responders are appropriately equipped and trained; Highway maintenance	Possible	Catastrophic	Accidents are rare, but may affect human health and safety to a large degree, including death

Health Canada has developed a draft guideline for a noise human health assessment; however, there are no applicable guidelines or enforced standards. Health Canada advises proponents to consult with provincial or local government authorities for applicable or relevant standards. This study considers standards developed by the Canada Mortgage and Housing Corporation (CMHC 1986), which are similar to general noise level thresholds accepted by many authorities across Canada and internationally.

Risk Mitigation

Noise reduction is directly related to the operation and type of vehicles used for the Project as noise concerns are mainly attributable to engine type and size. Potential noise effects from the Project will be mitigated by:

- minimizing the number of trips required;
- following maintenance procedures and schedules provided by vehicle manufacturers;
- using vehicle noise suppression technologies where possible;
- avoiding the use of engine brakes near communities; and
- providing noise awareness training for Project transportation personnel.

Risk Characterization

Noise from Project traffic will occur throughout all phases of the Project; however, the level of potential effects will change according to the Project phase and also vary depending on the traffic schedule, vehicle types, ground cover, topography and number of human receptors in proximity to the highways. Moreover, sound intensity decreases in proportion with the square of the distance from the source; a drop-off rate of 4.5 dBA is generally used in traffic analyses for each doubling of distance. Traffic noise is not a serious problem for people who live more than 30 to 60 m from lightly traveled roads (FHWA 1995).

Potential noise effects from Project traffic will have the greatest impact during Operation. However, with the addition of Project traffic, the level of traffic on the highways will be below historical levels (in most cases less than 30% of historic maximums) so the overall impact on noise is not expected to adversely affect Community Well-Being (see Sections 5.6.3 and 5.8.3).

Quality of the Natural Environment

Risk Identification

The Project will occur in a sparsely populated area of northwestern BC. Residents and tourists value the quiet and wilderness aspects of this region of the Province. The increased visual presence of vehicles, as well as potential nuisance effects resulting from vehicle noise and emissions, may be perceived to have a negative effect on the quality of the natural environment. The increase in industrial traffic, in particular, may contribute to this perception.

Risk Mitigation

The perceived negative effects on the quality of the natural environment will be minimized by using the following mitigation measures:

- minimizing the number of trips required;
- following maintenance procedures and schedules provided by vehicle manufacturers;
- using vehicle noise suppression technologies where possible; and
- ensuring Project-related vehicles avoid local roads and remain on the highways.

Risk Characterization

Perceptions with respect to the quality of the natural environment are intangible and vary by individual and community. It is difficult to ascertain objectively the extent to which the northwestern region of the province is valued for its pristine qualities, and to what extent this may be altered as a result of Project industrial traffic. However, the highway was designed to accommodate industrial traffic, including mining and forestry vehicles. With the addition of Project traffic, the level of traffic will be below historical levels (in most cases less than 30% of historic maximums) so the perceived negative effect on the quality of the natural environment (visual, nuisance) is unlikely to occur and anticipated to be fully mitigated.

Reduced Public Safety/Increase in Accidents

Risk Identification

It is anticipated that any increase in vehicle traffic may result in reduced public safety, for both vehicles and pedestrians, due to the increased probability of vehicle accidents. Vehicle collisions may result in immediate safety and human health effects (i.e., injury or fatality), thereby affecting CWB. Traffic accidents in or near communities, particularly involving dangerous cargo, could further affect community safety.

Police accident reports were used to assess the risks of traffic accidents (Chapter 3). Between 1996 and 2011, 118 severe collisions⁶ were recorded on Highway 37 between Bob Quinn Camp and Kitwanga (an average of 7.4 severe collisions per year) and 10 severe collisions were recorded for Highway 37A between Stewart and Meziadin (average of 0.63 per year), including commercial and non-commercial vehicles. Severe collisions of commercial vehicle accidents was 34 (average 2.1 per year) on Highway 37 and 4 (average 0.25 per year) on Highway 37A. Collisions and effects to human health are discussed further in Section 5.8.3.

Risk Mitigation

The BC MOTI will be encouraged to post additional signage along appropriate places on the highways. Speed limits and other traffic rules will be enforced and adhered to by Project personnel. All contractors and workers will be required to adhere to BC Occupational Health and Safety Regulation (BC Reg 296/97), as well as a zero-tolerance policy on alcohol and drugs. Procedures for emergency response and occupational first aid will be developed and workers and contractors will undergo required training. Information on weather and highway conditions as well as communication devices, will be made available to all Project drivers before departure.

Risk Characterization

Historically (between 1996 and 2011), an average of 2.1 severe collisions (resulting in injury or casualty) per year on Highway 37 and an average of 0.25 severe collisions per year on Highway 37A involving a commercial vehicle occurred. Accident statistics show a downward trend between 1996 and 2011 in tandem with a reduction in traffic volume; however, increases and decreases in the rate of traffic accidents are not anticipated to be concurrent with any increase or decrease in traffic volume (see Section 3.2). As shown in the CPM (Section 3.2.3), a maximum incremental increase of 0.191 collisions per year is predicted due to an increase in traffic from the KSM Project. Residual effects to safety and direct human health risks from accidents cannot be eliminated. However, while the probability of accidents increases slightly, the severity of injury cannot be predicted.

⁶ Severe collisions are those resulting in human injury or fatality.

5.1.3.2 *Hunting and Trapping*

Risk Identification

Land users may be indirectly affected by changes in traffic volumes along highways 37 and 37A. Indirect effects relate to potential adverse traffic risks to the harvest of wildlife resources, through disruption of movement and direct mortality effects on wildlife. Many land users, particularly hunters and trappers, adapt their activities based on the presence and habits of wildlife resources. Species harvested in the Study Area which could be at risk from a change in traffic along highways 37 and 37A include bear and moose (see Wildlife, Section 5.3).

Disruption of Movement Risk to Quantity of Resources

Increased traffic volumes along highways 37 and 37A may have an indirect effect on the quantity of resources available to hunters and trappers by disrupting or acting as a barrier to wildlife movements. Vehicle traffic may disrupt wildlife movement by decreasing the highway crossings by certain hunted and trapped species, including moose, grizzly bears, and black bears. In turn, risks to these harvest species may indirectly affect hunting and trapping activities within the Study Area.

The Wildlife risk assessment (Section 5.3) identifies that moose and bear movements may be at risk along highways 37 and 37A as a result of traffic volumes.

Direct Mortality Risk to Quantity of Resources

The quantity of resources available to hunters and trappers may also be indirectly affected by vehicle-related wildlife mortalities. As described in Section 5.3, because of the current status of the moose population in the area (i.e., with a history of declining numbers), and the potential habitat along Highway 37, direct mortality from vehicle-moose collisions was identified as a risk and potential effects of vehicle-related direct mortality on moose are evaluated using a population viability assessment, and moose a vehicle collision model (see Section 5.3 and Appendix D). With respect to moose, hunting and trapping interest may be at risk.

Conversely, following the implementation of mitigation measures to minimize vehicle-related wildlife mortality (e.g., enforcing speed limits, yielding to observed wildlife, etc.), no risk was predicted for black or grizzly bears as a result of vehicle-wildlife collisions. Further, there is no risk of vehicles colliding with bears in winter, as bears are in their dens during winter months. With respect to bear, hunting and trapping interest are not anticipated to be at increased risk.

Risk Mitigation

A change in the quantity of moose as resources is dependent on multiple factors affecting both land users and wildlife within the Study Area. In addition to mitigation strategies introduced in Section 5.3 to reduce the disruption to wildlife movement and direct mortality of wildlife (e.g., wildlife right-of-way, speed limits, and adhering to signage in areas of wildlife crossing), along Highway 37 and 37A, the Traffic and Access Management Plan enable land users to plan their activities on the basis of information about Project activities, and will be implemented to mitigate changes in the quantity of resources and to facilitate the continued safe access of land use areas off of Highway 37.

Risk Characterization

Despite mitigation, it is possible that disruption of movement to moose may occur as a result of increased traffic on Highway 37. The population viability assessment and moose vehicle collision model include a sensitivity analysis (see Section 5.3 and Appendix D). The sensitivity analysis performed

considered population predictions, and vehicle traffic under a variety of possible future survival rates and hunting rates.

Model results of the historic reconstruction of the moose population indicate that hunting rates were the likely initial cause of the moose population decline from 1595 to 517 animals during 2001 - 2011 and indicate that the addition of traffic from the KSM project is projected to cause an additional <1% mortality to the moose population at the current population size, a mortality rate that does not predict a substantial decline from the base case scenario. Under a scenario of baseline traffic plus KSM traffic, if the modeled survival rate of moose is increased a small amount (2-3%) such as by altering hunting rates, the model predicts an increase in the Nass moose population by 2030 from current conditions.

While possible, hunting and trapping activities are not predicted to be at risk from a change in traffic volumes as a result of the Project. As such, the severity of the risk for hunting and trapping as a result of change in traffic is expected to be minor.

5.2 FISH AND AQUATIC HABITAT

5.2.1 Baseline Data Overview

Traffic from the Project will travel through three major watersheds: the Nass River, Skeena River, and North Coast rivers (coastal rivers near Stewart, e.g. Bear River) watersheds. All three watersheds support large stocks of commercial and non-commercial fish species. Chinook salmon (*Oncorhynchus tshawytscha*), sockeye salmon (*Oncorhynchus nerka*), coho salmon (*Oncorhynchus kisutch*), pink salmon (*Oncorhynchus gorbuscha*), chum salmon (*Oncorhynchus keta*) and steelhead (*Oncorhynchus mykiss*) are commercially and culturally important species found in watercourses along highways 37 and 37A. Other species, including Dolly Varden (*Salvelinus malma malma*), bull trout (*Salvelinus confluentus*), Pacific lamprey (*Lampetra tridentate*) and mountain whitefish (*Prosopium williamsoni*) are also present throughout watercourses along the Project traffic routes (Figure 5.1-1).

A list of the specific watercourses (i.e., streams, rivers, lakes, and wetlands) where there are sensitive fish and aquatic habitat values along the transportation route are provided in Table 5.2-1. Table 5.2-1 provides the watercourse name, fish species present, and sensitive time period (based upon species presence and life history).

Table 5.2-1. Watercourses with Sensitive Fish and Aquatic Habitat Values along Highways 37 and 37A

Waterbody	Species Present	Sensitive Life History Stage	Timing
Bell-Irving River	Chinook salmon	Spawning - Egg incubation	August - May
	Coho salmon	Spawning - Egg incubation	September - June
Bear River	Chum salmon	Spawning - Egg incubation	August - April
	Coho salmon	Spawning - Egg incubation	September - June
Brown Bear Creek	Steelhead	Spawning - Egg incubation	September - March
	Sockeye/Kokanee Salmon	Spawning - Egg incubation	September - March
	Steelhead	Spawning - Egg incubation	September - March
Cranberry River	Chinook salmon	Spawning - Egg incubation	August - May
	Coho salmon	Spawning - Egg incubation	September - June
	Pink salmon	Spawning - Egg incubation	August - March
	Steelhead	Spawning - Egg incubation	September - March
	Bull trout	All life stages	Year-round

(continued)

Table 5.2-1. Watercourses with Sensitive Fish and Aquatic Habitat Values along Highways 37 and 37A (completed)

Waterbody	Species Present	Sensitive Life History Stage	Timing
Hanna Creek	Chinook salmon	Spawning - Egg incubation	August - May
	Coho salmon	Spawning - Egg incubation	September - June
	Sockeye/Kokanee Salmon	Spawning - Egg incubation	September - March
	Steelhead	Spawning - Egg incubation	September - March
	Bull trout	All life stages	Year-round
Kitwancool Lake	Sockeye/Kokanee Salmon	Rearing	Year-round
Kitwanga River	Chinook salmon	Spawning - Egg incubation	August - May
	Chum salmon	Spawning - Egg incubation	August - April
	Coho salmon	Spawning - Egg incubation	September - June
	Pink salmon	Spawning - Egg incubation	August - March
	Sockeye/Kokanee Salmon	Spawning - Egg incubation	September - March
	Steelhead	Spawning - Egg incubation	September - March
	Bull trout	All life stages	Year-round
Meziadin Lake	Sockeye/Kokanee Salmon	Rearing	Year-round
	Bull trout	All life stages	Year-round
Meziadin River	Coho salmon	Spawning - Egg incubation	September - June
	Pink salmon	Spawning - Egg incubation	August - March
Nass River	Chinook salmon	Migration (to Kwinageese, Damdochax River)	July - August
Tintina Creek	Chinook salmon	Spawning - Egg incubation	August - May
	Coho salmon	Spawning - Egg incubation	September - June
	Sockeye/Kokanee Salmon	Spawning - Egg incubation	September - March
	Steelhead	Spawning - Egg incubation	September - March
	Bull trout	All life stages	Year-round

Note: This table presents the species that were identified as being important by Nisga'a and First Nations. It is not a comprehensive list of the species present in each waterbody.

The Nass River Watershed provides spawning and rearing habitat for salmon and steelhead populations.

Sockeye salmon are a large component of local fisheries and an important ecological keystone species. Between 1994 and 2009, the mean run size estimate of sockeye salmon reaching Gitwinksihlkw and entering the Upper Nass system was 278,000 (Nisga'a Fisheries 2010). Hanna and Tintina creeks in the Nass River system support significant populations of sockeye salmon, along with chinook salmon, coho salmon and steelhead. The largest Skeena River sockeye runs are not along the proposed Project traffic routes. Kitwancool Lake (also referred to as Gitanyow Lake) is within 1 km of the traffic route. The Kitwancool Lake/Kitwanga River sockeye stock has been identified as being at serious risk of extirpation (Gottesfeld, Rabnett, and Hall 2002). Kokanee salmon have also been identified in Kitwancool Lake (Gottesfeld, Rabnett, and Hall 2002).

Coho salmon spawn and rear within 1 km of the proposed travel route. The Bell-Irving, Meziadin, and Cranberry rivers provide many of the coho smolts in the Upper Nass region (Bocking and Peacock 2004). Kitwanga River coho are considered a significant coho stock within the Skeena watershed (M. Cleveland, pers. comm, 2012). Coho salmon are numerous within the Bear River system and spawn in the Bear River adjacent to the Project traffic route.

The Bell-Irving and Cranberry river systems provide spawning grounds for an estimated 45% of chinook salmon in the Upper Nass system (Koski, Link, and English 1996). An additional two of the major chinook spawning grounds in the Nass system, Kwinageese River and Damdochax River, are upstream of the proposed traffic routes. While the spawning and rearing grounds for fish upstream of the route are outside any influence from Project traffic, salmon travelling to and from the spawning grounds migrate by the proposed travel route. In the Skeena Watershed, the Kitwanga River is a major area for chinook spawning and rearing, and recent low escapement numbers have suggested that this stock is particularly vulnerable (Gottesfeld, Rabnett, and Hall 2002).

Pink salmon are found in both the Nass and Skeena watersheds. The Cranberry, Meziadin, and Kitwanga rivers are important spawning and rearing locations for pink salmon (Gottesfeld, Rabnett, and Hall 2002).

Chum are not particularly numerous in the Skeena Watershed. Therefore stocks spawning and rearing in the Kitwanga River and its tributaries are particularly important in this system. Recent population estimates indicate there are low spawner numbers (Gottesfeld, Rabnett, and Hall 2002). Chum salmon are also found in the Bear River (BC MOE 2009; Figure 5.2-1).

Meziadin Lake and its major tributaries, Hanna, Tintina and Surprise creeks, account for up to 80% of the total Nass sockeye assessment (DFO 2004). Meziadin Lake is also the main sportfishing lake in the area. It features a number of popular sport fishing species including salmon, whitefish, Dolly Varden, kokanee, rainbow trout, bull trout and steelhead (Pierce Lefebvre Consulting 2008).

Steelhead are dependent upon a limited number of spawning and rearing areas along the Project travel route. Critical steelhead wintering areas have been located in the Cranberry River alongside Highway 37 (Mitchell 2006). Brown Bear Creek in the Nass system, a mid-sized waterbody along the proposed travel route, provides much of the spawning grounds for trout in the area, including steelhead, as well as sockeye (BC MOE 2009). The Kitwanga River and its tributaries are particularly important for Skeena steelhead, especially in providing critical overwintering habitat for steelhead stocks in the area (Gottesfeld, Rabnett, and Hall 2002).

Bull trout, a species of provincial concern, are abundant in the Kitwanga River watershed (Gottesfeld, Rabnett, and Hall 2002), as well as in the Cranberry River, and Hanna and Tintina creeks (M. Cleveland, pers. comm., 2012). Dolly Varden, a yellow-listed species, is found all along the transportation corridor (M. Cleveland, pers. comm., 2012).

5.2.2 Issue Scoping

5.2.2.1 Fish and Aquatic Habitat Scoping

Project activities are expected to result in additional traffic volumes, although not exceeding historical peaks, on highways 37 and 37A. The effects assessment considers potential effects on fish and fish habitat and concerns associated with Project traffic; potential alterations or upgrades to highways 37 and 37A are not considered in this document (Table 5.2-2).

Traffic from the Project is expected to have little to no effect on fish and aquatic habitat. The traffic will travel on paved or seal-coated highways and it is not expected to generate dust in amounts sufficient to affect fish or aquatic habitats. The operation of Project traffic is not expected to cause any additional stress or damage to aquatic systems or species beyond the current operation of the highway.




Figure 5.2-1

Table 5.2-2. Fish and Aquatic Habitat Scoping Matrix

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
<i>Project traffic</i>		
<u>Personnel and non-hazardous cargo</u>		
All non-hazardous	No	Project traffic will use existing highways; therefore no Project/aquatic habitat interactions are expected as aquatic habitat will not be altered.
<u>Hazardous cargo</u>		
Diesel fuel and lubricants	No	Project traffic will use existing highways; therefore no Project/aquatic habitat interactions are expected as aquatic habitat will not be altered.
Concentrates	No	
Lime and reagents	No	
Explosives	No	
<i>Traffic accidents</i>		
<u>Personnel and non-hazardous cargo</u>		
All non-hazardous	No	Non -hazardous cargo does not pose a risk to fish or aquatic habitats.
<u>Hazardous cargo</u>		
All hazardous	Yes	In the event of an accident, hazardous cargo may spill and enter nearby waterbodies. Hazardous substances could affect water quality, aquatic vegetation, aquatic invertebrates, and fish at any stage of their life cycle.

There are potential risks associated with traffic accidents. For traffic accidents to affect fish or aquatic habitat, the accident must occur at a watercourse crossing or where the highway runs in close proximity to a watercourse (Figure 5.1-1).

5.2.2.2 Valued Component Scoping

The selected fish and aquatic habitat VCs and the rationales for their inclusion or exclusion in the assessment are presented in Table 5.2-3. The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise). The VCs for the Project include Pacific salmon, steelhead/rainbow trout, bull trout, and Dolly Varden. For the purposes of this study, all fish species have been grouped together, as potential effects and mitigation measures will be similar for all fish species.

Table 5.2-3. Identification and Rationale for Fish and Aquatic Habitat Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	... Project Traffic?	...Traffic Accidents?	
Fish species	X	X	X		No	Yes	Accidents involving Project traffic may affect fish species during all phases of the Project’s life span. All fish species have been grouped together as potential effects and mitigation measures will be the same for all species.
Aquatic habitat	X	X			No	Yes	Traffic accidents involving Project traffic may affect aquatic ecosystems during all phases of the Project.

¹ “X” indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; “-” indicates that the group did not identify the VC as an issue.

² “Yes” indicates that the VC is selected for further analysis; “No” indicates that the VC is excluded from further analysis.

5.2.2.3 Identification of Potential Traffic/Valued Component Interactions

The potential interactions between Project traffic and the identified VCs are identified in Table 5.2-4. Where there is potential for an interaction between a traffic type and a VC, the potential is identified with an “X”. Only traffic types that have been identified to potentially affect one or more VCs are included in the Risk Analysis (Section 5.2.3).

Table 5.2-4. Potential Traffic / Fish and Aquatic Habitat Valued Component Interaction Matrix

Traffic Type	VCs	
	Fish Species	Aquatic Habitat
<i>Project traffic</i>		
Lime and reagents	-	-
Explosives	-	-
<i>Traffic accidents: on-road</i>		
Diesel fuel and lubricants	X	X
Concentrates	-	-
Lime and reagents	-	X
Explosives	-	-
<i>Traffic accidents: off-road</i>		
Diesel fuel and lubricants	X	X
Concentrates	X	X
Lime and reagents	X	X
Explosives	X	X

“X” indicates that a potential interaction has been identified.

“-” indicates that no potential interaction was identified.

5.2.3 Risk Analysis

This section provides an analysis of the risks associated with Project traffic on fish and aquatic habitat. Interactions identified in Table 5.2-4 are analysed and assigned a risk severity according to the definitions in Table 5.2-5. Traffic types, their potential risks, mitigation measures and severity are shown in Table 5.2-6 and Table 5.2-7.

Table 5.2-5. Fish and Aquatic Habitat Risk Assessment Severity Scale Descriptors

Descriptor	Definition
Negligible	No detectable change to aquatic organism abundance or fish health, and Ministry of Environment water quality guidelines will not be exceeded.
Minor	Effects are localized, short in duration, and low in magnitude. Fish species harvest rates will not be affected.
Moderate	Effects are moderate or high in magnitude but very limited spatially and temporally. Fish species harvest rates will not be affected.
Major	Effects are moderate in magnitude but are spatially or temporally extensive. Fish species harvest rates will not be affected.
Catastrophic	Permanent or semi-permanent high level effects over a large area. Potential for negative effects on fish harvest rates.

5.2.3.1 *Fuel or Lubricant Spill*

Risk Identification

Project traffic creates a risk of diesel fuel or lubricant entering aquatic habitat. The introduction of these substances to aquatic habitat may occur if a traffic accident occurs at a watercourse crossing or where traffic routes are in close proximity to a watercourse.

The geographic scope of a petroleum product spill may be localized to far-ranging. Most petroleum products are toxic to fish and aquatic organisms. They may cause mortality at high concentrations and reduced health or altered behaviour at sublethal levels. The toxicity of these products occurs through their water-soluble constituents and emulsions, and toxicity increases when dissolved oxygen levels are low. Hydrocarbons in petroleum products can damage gill epithelia, nerves, the liver and result in general organ failure (Fryday et al. 1996; Omoregie and Ufodike 2000).

Fuel spills reduce secondary producers (e.g., phytoplankton and zooplankton) and the effects of major fuel spills on aquatic habitat may extend as far as 12 km downstream of the source of the spill and may persist for longer than a year after the initial spill and clean-up (Poulton, Finger, and Humphry 1997; Lytle and Peckarsky 2001).

Behavioural changes in fish after sublethal exposure to spilled petroleum products typically are responses to the physiological changes caused by the toxins. In the event of a diesel fuel or lubricant spill in a river, these effects may occur farther downstream than direct mortality and persist after initial clean-up. Acute and chronic stress responses, as indicated by disturbances in blood chemistry (Zbanyszek and Smith 1984; Alkindi et al. 1996), can lead to behavioural changes such as decreased feeding activity (Camargo, Alonso, and Salamanca 2005) and changes in swimming behaviour (Struhsaker 1977; Little and DeLonay 1996).

Risk Mitigation

Prevention is the best form of mitigating spills. Petroleum spills will be prevented, and in the event of a spill, mitigated by implementing best management practices (BMPs) with regard to the handling and transportation of petroleum products, spill prevention and response in the event of a spill. BMPs relating to petroleum spills will be described in detail the Spill Prevention and Emergency Response Plan. This plan will provide specifications for preventing and controlling the release of spills during traffic accidents. Prompt containment and clean-up of spills is essential to mitigating risks to aquatic habitat and organisms. The plan will minimize response time and maximize clean-up efficiency, preventing long-term or geographically extensive effects.

Risk Characterization

While moderate effects on fish and aquatic habitat may be expected at the spill site, the Spill Prevention and Emergency Response Plan will limit the temporal and spatial effects of a spill. Outside the spill site, effects should be minor with few residual effects.

5.2.3.2 *Concentrate Spills*

Risk Identification

There is a risk of copper or molybdenum concentrate entering aquatic habitat. The introduction of these substances to aquatic habitat may occur if a traffic accident occurs at a stream crossing or where traffic routes are in close proximity to a watercourse and the vehicle or its cargo enters the watercourse.

Table 5.2-6. Fish and Aquatic Habitat Risk Assessment Matrix for Project Traffic

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Fish species	All traffic types	-	All phases	-	Possible	-	No effects on fish species
Aquatic Habitat	All traffic types	-	All phases	-	Possible	-	No effects on aquatic habitat

Table 5.2-7. Fish and Aquatic Habitat Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Fish species	Diesel fuel and lubricants	Fuel or lubricant spill into waterbody may cause localized or far-reaching effects. Petroleum products are toxic to fish species. Exposure to low concentrations may change fish behaviour	All phases	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Moderate	Localized, short-term, moderate effects on fish species
Fish species	Concentrates	Metal concentrate spill into waterbody may be toxic at the point source and exceed water quality guidelines at a distance; smothering of eggs and fish	Operations	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup; Low moisture concentrate	Unlikely	Moderate	Moderate to high effects confined to local area and on a short-term basis, rapid clean-up of concentrates
Fish species	Lime and reagents	Should lime and reagents spill into a waterbody, the resulting change in pH and water chemistry may result in mortality or decreased fish health. Reagent spills into waterbodies range in effect from localized disturbance to significant mortality and population changes in fish stocks	All phases	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Moderate	Negligible to major effects on local area on a short term basis, dependent on spill type. Negligible to moderate effects outside of immediate area
Fish species	Explosives	Explosives are toxic to aquatic invertebrates and fish eggs and fry. Explosive compounds entering aquatic systems may result in death or serious sublethal effects to invertebrate food sources for fish and to incubating or rearing juvenile fish	Operations	Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan	Unlikely	Moderate	Spills minimized and contained due to Spill Prevention and Emergency Response Plan. Moderate effects in immediate area, minor effects outside of immediate area.
Fish species	Explosives	Explosives are toxic to aquatic invertebrates and fish eggs and fry. Explosive compounds entering aquatic systems may result in death or serious sublethal effects to invertebrate food sources for fish and to incubating or rearing juvenile fish	Construction	Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan	Unlikely	Moderate	Spills minimized and contained due to Spill Prevention and Emergency Response Plan. Moderate effects in immediate area, minor effects outside of immediate area.
Aquatic Habitat	Diesel fuel and lubricants	Fuel or lubricant spill into waterbody may cause localized or far-reaching effects. Petroleum products are toxic to invertebrates. Exposure to low concentrations may change fish behaviour	All phases	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Moderate	Moderate to major effects confined to local area and on a short-term basis, rapid clean-up of concentrates
Aquatic Habitat	Concentrates	Metal concentrate spill into waterbody may be toxic at the point source and exceed water quality guidelines at a distance; smothering of benthic organisms	Operations	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup; Concentrate dewatered to a low moisture content before transport	Unlikely	Moderate	Moderate effects on local area on a short term basis. Negligible effects outside of immediate area
Aquatic Habitat	Lime and reagents	Should lime spill into a waterbody, the resulting change in pH and water chemistry may result in mortality of periphyton, macrophytes, and aquatic invertebrates. Reagent spills into waterbodies range in effect from localized disturbance to significant mortality and population changes of periphyton, macrophytes, and aquatic invertebrates	All phases	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Moderate	Negligible to major effects on local area on a short term basis, dependent on spill type. Negligible to moderate effects outside of immediate area
Aquatic Habitat	Explosives	Explosives are toxic to aquatic invertebrates and fish eggs and fry. Explosive compounds entering aquatic systems may result in death or serious sublethal effects to invertebrate food sources for fish and to incubating or rearing juvenile fish	Operations	Enforced speed limits and traffic safety; Adhere to the Spill Containment and Emergency Response Plan	Unlikely	Negligible	Spills minimized and contained due to Spill Prevention and Emergency Response Plan. Moderate effects in immediate area, minor effects outside of immediate area.
Aquatic Habitat	Explosives	Explosives are toxic to aquatic invertebrates. Explosive compounds entering aquatic systems may result in death or serious sublethal effects to freshwater invertebrates	Construction	Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan	Unlikely	Negligible	Spills minimized and contained due to Spill Prevention and Emergency Response Plan. Moderate effects in immediate area, minor effects outside of immediate area.

The majority of the effects of a concentrate spill would be highly localized. Low-moisture concentrate would not quickly mobilize and could be cleaned up relatively easily. Direct mortality would result if the concentrate enters the watercourse and crushes or smothers fish or aquatic organisms. Mortality may also occur if metal concentrations in the water around the spill increase above toxicity levels. These levels vary by species, water chemistry, and water temperature; however, copper and molybdenum toxicity has been known to occur at concentrations as low as 35 ppm (Eisler 1989, 1998).

Sublethal effects occur when metal accumulation in the gills of fish cause a stress response that can lead to behavioural changes (Wendelaar Bonga 1997).

Physiological effects of metal exposure in fish include acid-base disturbance, changes in gill function, ionic fluxes, and metals toxicity (Evans 1987; Wood 1992). Chronic stress caused by exposure to metals at sublethal levels can lead to decreased growth in fish through an increase in metabolic demands (Todd et al. 2006). The stress response is caused by metal uptake and pH surges that in turn stimulate increased gas exchange (Wood 1992).

Risk Mitigation

Prevention is the best form of mitigating spills. In the event of an accident resulting spilled concentrate, mitigation measures will be similar to those identified for diesel fuel and lubricant spills. Clean-up of concentrate spills will be easier than fuel spills due to the low-moisture levels. Prompt clean-up according to the Spill Prevention and Emergency Response Plan will limit the potential impact to minor effects in the local area.

Risk Characterization

With mitigation measures in place, effects will be limited to crushing or smothering of fish or aquatic organisms at the spill site, plus any additional damage to substrate and benthic communities from removing contaminated soils during clean-up. Metal contamination outside of the spill site will be minimal and should not cause large-scale or long-term effects.

5.2.3.3 *Lime and Reagents*

Risk Identification

The Project requires the transportation of large amounts of lime and other reagents. An off-road accident near a watercourse could result in the truck and its cargo entering the watercourse.

The introduction of lime into a watercourse could cause severe damage in small or stagnant waterbodies as it would not be quickly diluted. At low concentrations, lime is used to treat acidified waterbodies as it provides a buffering effect against acidification (Hultbert and Andersson 1982). However, at higher concentrations it can be hazardous to aquatic habitat and organisms.

The primary way in which lime affects aquatic habitat is by raising water pH. Certain macrophyte and aquatic invertebrate species are highly sensitive to liming, and will die when exposed to lime (Ye and Randall 1991; Brandrud 2002). In general, a pH of 9 or more will cause mortality in most fish species (Ye and Randall 1991). When exposed to lower levels of alkalinity, fish experience impaired ammonia excretion and sodium influx that may result in changes to blood ammonia levels (Ye and Randall 1991). Behaviour changes resulting from the physical stress, such as impaired swimming performance, may affect fish growth and survival.

Several other reagents expected to be transported along this route, including sodium hydroxide, hydrochloric acid, and sulphuric acid could also affect aquatic habitats due by influencing pH.

Other reagents have additional toxicity concerns. Sodium cyanide is toxic to fish, aquatic invertebrates, vegetation, and amphibians, and cyanide spills have caused serious damage to aquatic ecosystems (Eisler et al. 1999). A cyanide spill in an aquatic habitat would have lethal effects for nearby aquatic life. However, cyanide rapidly oxidizes in aquatic environments and is unlikely to persist at toxic levels for more than 40 days, although population-level effects from associated mortality may affect fish stocks for much longer. Copper sulphate (Cu_2SO_4) and potassium amyl xanthate (PAX) are toxic to aquatic vegetation, invertebrates, and fish and may persist in the environment. Potential effects of chemical hazards on fish and aquatic habitat are described in greater detail in Section 6.4.4 and Table 6.4-5.

Risk Mitigation

Prevention is the primary way of mitigating risks off-road traffic accidents, and in the event of an accident resulting in a spill, ensuring prompt clean-up of lime and reagent spills. Adhering to speed limits and safe traffic practices will prevent off-road accidents. Cyanide transportation will follow guidelines established in the International Cyanide Management Code (ICMI n.d.). Should an accident occur, prompt action according to the Spill Prevention and Emergency Response Plan will limit the potential impact to the local area.

Risk Characterization

Lime spills from Project traffic are likely to cause minimal to negligible effects. Outside the area directly adjacent to the spill, the lime is unlikely to harm aquatic life, especially in larger running watercourses where it will be quickly diluted. The potential effects of reagent spills are highly dependent on the type and quantity of reagent spilled. While some reagent spills (e.g., activated carbon) would have negligible effects, others (e.g., copper sulphate or sodium cyanide) have the potential to cause more severe effects. Persistence of effects is dependent on the type and volume of reagent spilled and may range from very short term to long term.

5.2.3.4 *Explosives*

Risk Identification

The exact pathways, lethal concentrations, and effects of explosives on aquatic organisms vary by explosive type. Most explosives used at mine sites are nitrogen-based, and nitrogen content creates the greatest risk for aquatic environments in the event of an explosives spill (Levit 2010). The nitrogen in explosives is often in highly water-soluble formats, in particular, nitrate and ammonia (Forsyth, Cameron, and Miller 1995).

Nitrate primarily causes damage to freshwater organisms by damaging the oxygen-carrying pigments in the blood, such as haemoglobin (Camargo, Alonso, and Salamanca 2005). In freshwater invertebrates, nitrates can cause mortality or sublethal effects including muscle fragmentation or shrinkage. Fish are particularly vulnerable to nitrate toxicity in the egg, fry and larval stages. Juvenile fish exposed to nitrates exhibit damage to blood proteins and pigments as well as liver damage (Camargo, Alonso, and Salamanca 2005).

Unlike responses to nitrate, fish are more strongly affected by ammonia exposure than invertebrates (Arthur et al. 1987). Ammonia can harm fish by damaging gill epithelia and the immune system, reducing the oxygen-carrying capacity of blood, disrupting blood vessels and osmoregulation, and preventing adenosine triphosphate production (Camargo and Alonso 2006).

Risk Mitigation

Preventing off-road traffic accidents is the primary way of mitigating risk. Adhering to speed limits and safe traffic practices will prevent off-road accidents. Should an accident occur, prompt action according to the Spill Prevention and Emergency Response Plan, ensuring prompt containment and clean-up of lime, explosives and reagent spills will limit the potential impact to the local area.

Risk Characterization

While potential effects may be expected at the spill site, the Spill Prevention and Emergency Response Plan will limit the temporal and spatial effects of the spill. Outside the spill site, effects are expected to be moderate with few residual effects.

5.3 WILDLIFE

5.3.1 Baseline Data Overview

Baseline conditions along the highways for wildlife VCs selected for this assessment are described below.

5.3.1.1 *Moose*

Moose are common throughout BC's forested areas, with an estimated population size of 170,000 animals (Blood 2000). However, the moose population in the Nass Wildlife Area (NWA) near Highway 37 has been declining since 2001. Corrected for sightability, the population was estimated to be $1,595 \pm 19\%$ in 2001, and declined to $638 \pm 33\%$ in 2007, and to $517 \pm 28\%$ in 2011. Despite management actions taken in 2007 to reduce harvest, the population has continued to decline (M. W. Demarchi 2011).

The Nass South Sustainable Resource Management Plan (SRMP) and the Cranberry SRMP area have been identified as providing high value moose habitat, including important calving, rutting and winter habitat. Winter habitat is generally the limiting factor in the carrying capacity for moose in BC because of increased energy demands from moving through snow pack and reduced nutritional forage quality (Armleder, Dawson, and Thomson 1986; Nyberg and Janz 1990). Moose winter range along the highway consists primarily of low elevation wetland-timber complexes, floodplains of main rivers, and large tributary streams adjacent to coniferous stands.

The low elevation and gentle topography of much of the area along Highway 37 represents suitable moose winter habitat, and movement corridors are present along Highway 37. Demarchi (2000) identified core use areas in the NWA where moose are consistently observed during the winter. Moose winter range has also been identified in the area from Meziadin to the Ningunsaw summit (Pollard 2007) and near Cranberry Junction and Cranberry River (BC MFLNRO 2012a). One calving area was identified by the Skii km Lax Ha on the floodplains and associated wetlands on the Bell-Irving River below Bell II (Rescan 2010a).

Movement corridors connect habitats that are exploited during different times of the year. Corridors maintain animal movement between habitat patches, increase population size, increase gene flow, and maintain biodiversity (Haddad et al. 2003). Migratory movements of moose, for example, often follow traditional routes, using the same migration corridor every year (Bowyer, Ballenberghe, and Kie 2003). Moose are known to cross the Nass River when moving between their seasonal ranges, most commonly near Van Dyke Island (Rescan 2010a), near Cottonwood Island west of Cranberry Junction, and at the Bell-Irving/Spruce crossing (Demarchi 2003). The valley between Bell II and Bob Quinn, which contains Highway 37, has also been identified as a wildlife movement corridor for a variety of wildlife species (Rescan 2010a).

Ungulate Winter Ranges (UWRs) ensure environmental sustainability across a landscape through two objectives: (1) identify suitable habitat, and (2) integrate habitats that provide a variety of functions (including considerations for habitat interspersion). There are no approved UWR for moose along the highways 37 and 37A; however, moose winter range has been mapped along the Bell-Irving River and Snowbank Creek near Highway 37, near Cranberry Junction, Van Dyke Island, and Meziadin Junction (Mahon et al. 2005; McElhanney 2007; Rescan 2010b).

5.3.1.2 Bears

Grizzly bears are found throughout the majority of BC across a broad range of elevations, from sea level to high alpine regions; an estimated 13,800 grizzlies live in the province (Gyug, Hamilton, and Austin 2004). Distribution of grizzly bears is often related to food supply, with higher densities in areas with abundant food (Hamilton 1987), such as along streams during salmon runs, and on alpine and subalpine slopes when berries are abundant. A three-year study conducted from 1996 to 1999 (Demarchi 2000; Demarchi and Johnson 2000) estimated a density of 0.04 bears/km² in the NWA based on surveys conducted in 1996 (Demarchi and Johnson 2000).

Highly suitable grizzly bear spring habitat has been identified near the Ningunsaw Pass, Bowser River, Dragon Lake, the mouth of the Kitsumkalum River (Rescan 2010a), and throughout the South Nass Timber Supply Area. In addition, Demarchi and Johnson (2000) identified Hanna and Tintina creeks near Meziadin Junction as important areas where grizzly bears feed on salmon. Reaches of potential importance for salmon spawning include the Nass River around Cottonwood Island, the lower Bowser River to its confluence with the Bell-Irving River, and the large floodplain associated with the Bell-Irving River and Teigen Creek drainages near Bell II (Rescan 2010a). A potential movement corridor used by grizzly bear has also been identified leading from the Cedar River into the Kiteen River drainage (Rescan 2010a).

Wildlife Habitat Areas (WHAs) are areas of high quality grizzly bear habitat. Management objectives associated with WHAs are created to maintain habitat necessary to sustain the local grizzly bear population across one or more seasons. The aim of WHAs is to identify areas for future integrated resource management; thus, delineated WHAs consider features such as topography for security and linkages between areas of seasonal habitat use. There are no approved WHAs for grizzly bear along the highways; however, WHA candidates for grizzly bear have been mapped. Candidate WHA polygons for grizzly bear occur in the North Nass Timber Supply Area between Meziadin Lake and Ningunsaw Summit, the South Nass Timber Supply Area between Meziadin Lake and Cranberry Junction, and within the Cranberry SRMP along Highway 37 south of Cranberry Junction (BC MFLNRO 2012a). In many cases, WHAs are blocks of un-harvested forest between cut blocks that were part of the large-scale cedar forestry industry along Highway 37.

5.3.1.3 Western Toads

The western toad (*Anaxyrus boreas*) is a federally listed species of special concern that is protected under Schedule 1 of the *Species at Risk Act* (SARA, City of Terrace 2002; Government of Canada 2010). It is also internationally recognized as a near threatened species by the International Union for the Conservation of Nature (IUCN 2010). In British Columbia, it is considered secure but is afforded protection under the BC *Wildlife Act* (1996).

Western toads occupy predominantly terrestrial habitats, but move seasonally to breeding ponds in the spring. Toad populations can experience relatively high rates of mortality when these migration routes cross roads. Considering the conservation status of western toads and its potential sensitivity to development, a toad study was conducted within the Wildlife Study Area at the Project site to identify toad breeding ponds. No systematic baseline surveys were conducted for western toads along highways 37 or 37A. Therefore, it is assumed for the purposes of this analysis that western toads may occur within the Study Area.

5.3.1.4 Avian Community

Avian species that migrate between countries receive protection under the federal *Migratory Birds Convention Act* (1994). Bird species, especially raptors, are also afforded additional protection under the BC *Wildlife Act* (1996), while avian species at risk are protected under SARA (City of Terrace 2002). No systematic baseline surveys were conducted for birds along highways 37 or 37A; however, for the purposes of this analysis it is assumed that birds occur within the Study Area.

5.3.2 Issue Scoping

5.3.2.1 Wildlife Scoping

Project activities are expected to result in additional traffic volumes on highways 37 and 37A, although not exceeding historical peaks. This assessment addresses potential wildlife issues and concerns associated with Project traffic. The principal issues for wildlife are associated with Project traffic and traffic accidents (Table 5.3-1).

Table 5.3-1. Wildlife Scoping Matrix

Traffic Type	Potential Risk?	
	Yes/No	Rationale for Selection/Exclusion
<i>Project traffic</i>		
All traffic	Yes	All traffic types may affect wildlife due to increased traffic volume on the highways (e.g., increased risk of vehicle/wildlife interactions and disruption of movement).
<i>Traffic accidents</i>		
All traffic	Yes	Traffic accidents have the potential to affect wildlife VCs, as hydrocarbon or other environmental contamination may result. If chemicals spill, they may be hazardous to wildlife (i.e., passed up the food chain into plants, small mammals, etc.).

5.3.2.2 Valued Component Scoping

The selected wildlife VCs and the rationales for their inclusion or exclusion in the assessment are presented in Table 5.3-2. The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise).

5.3.2.3 Identification of Potential Traffic/Valued Component Interactions

The potential traffic/wildlife interactions associated with Project traffic along highways 37 and 37A are primarily associated with moose and bears. The potential traffic/wildlife interactions are shown in Table 5.3-3.

5.3.3 Risk Analysis

The effects assessment addresses potential wildlife issues and risks associated with Project traffic along highways 37 and 37A. It is based on an assessment of VCs focused on selected wildlife species or groups selected in Table 5.3-2.

Table 5.3-2. Identification and Rationale for Wildlife Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	Normal Project Traffic?	Traffic Accidents?	
Moose	X	X	X	X	Yes	Yes	Considered because moose are identified as a culturally important and hunted species for the Nisga'a Nation, Skii km Lax Ha, Tahltan, Gitxsan and Gitanyow. Under the Nisga'a Final Agreement, moose is also an initial designated species for which the Nisga'a have a wildlife allocation. Moose are an economically important species to local hunters and guide outfitters. Moose are a species requiring increased management consideration in land management plans including Nass South SRMP (BC MFLNRO 2012b), Cassiar Iskut-Stikine Land and Resource Management Plan (LRMP) (BC ILMB 2000b), Cranberry SRMP (BC MFLNRO 2012a), and the Nisga'a Land Use Plan (NLG 2002). Biologically and ecologically important species. Candidate moose UWRs have been identified along the highway, as well as movement corridors. Moose/vehicle interactions are commonly reported along the highway, with 855 collisions reported between 1983 and 2002 in the Bulkley-Stikine District (Sielecki 2004), and are therefore considered in the assessment.
Bears (grizzly bear and black bear)	X	X	X	X	Yes	Yes	Considered because grizzly bears are provincially blue-listed and federally listed Species of Special Concern. Species of ecological and cultural importance for the Nisga'a Nation, Tahltan, Gitxsan, Gitanyow and Skii km Lax Ha, for hunting subsistence and traditional reasons. Under the Nisga'a Final Agreement, grizzly bear is also an initial designated species for which the Nisga'a have a wildlife allocation. Biologically important as an umbrella species ⁷ . Economically important to local hunters and guide outfitters. Identified as an important species requiring increased management consideration by land management plans including Nass South SRMP (BC MFLNRO 2012b), Cassiar Iskut-Stikine LRMP (BC ILMB 2000b), Cranberry SRMP (BC MFLNRO 2012a), and the Nisga'a Land Use Plan (NLG 2002). High value grizzly bear foraging habitat and spawning salmon reaches have been identified near the highways. Black bears were identified as a culturally important and hunted species for the Nisga'a Nation, Tahltan, Skii km Lax Ha, Gitxsan, and Gitanyow. Vehicle strike data along highways in the Bulkley-Stikine District collected between 1983 and 2002 documented 181 collisions with bears (grizzly or black) in 19 years (Sielecki 2004), and are therefore considered in the assessment.
American Marten	X	-	X	X	No	No	Considered because American marten are identified as a culturally important and trapped species for the Nisga'a Nation, Skii km Lax Ha, Tahltan, Gitxsan, and Gitanyow. Economically important furbearer to local trappers. Identified as an important species requiring increased management consideration by land management plans including the Nass South SRMP (BC MFLNRO 2012b) and Cassiar Iskut-Stikine LRMP (BC ILMB 2000b). Marten are excluded as a VC as the exposure of American marten to vehicular collisions is anticipated to be relatively low along the road because marten tend to avoid roads and areas that lack overhead cover (Poole et al. 2004).

(continued)

⁷ An "umbrella species" is defined as one with large area requirements for which the protection of the species offers protection to other species that share the same habitat.

Table 5.3-2. Identification and Rationale for Wildlife Valued Component Selection/Exclusion (continued)

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	Normal Project Traffic?	Traffic Accidents?	
American Marten (continued)							This conclusion is supported by mortality rates of marten along low and high use highways. Vehicle strike data along highways in the Bulkley-Stikine District collected between 1983 and 2002 documented three collisions with American marten in 19 years (Sielecki 2004). Similarly, in Banff National Park, American marten made up 2% of small vertebrate roadkills (Clevenger, Chruszcz, and Gunson 2003). Therefore, marten mortality due to vehicle collisions is expected to be an infrequent event and is excluded.
Hoary Marmot	X	-	-	-	No	No	<p>Considered because marmots are a culturally important and trapped species for the Nisga'a Nation, Skii km Lax Ha, Tahltan, Gitksan, and Gitanyow. Economically important furbearer to local trappers. Hoary marmots occupy relatively small home ranges (approximately 13.8 ha) (Holmes 1984), and foraging usually takes place within a few hundred metres of a burrow entrance (Banfield 1981).</p> <p>Given the small home range and relatively sedentary nature of marmots, it is unlikely that these animals will cross the highway, thereby reducing the risk of vehicle interactions. In addition, two vehicle collisions with marmots were recorded along highways in the Bulkley-Stikine District (Sielecki 2004) over 19 years. Based on these results additional traffic volumes, albeit not exceeding historical peaks along the highway in association with the Project is not expected to increase vehicle incidents with marmot and is therefore excluded from the assessment.</p>
Birds (waterfowl, forest birds, and raptors)	X	X	-	X	Yes	No	Considered because many birds are protected under the <i>Migratory Birds Convention Act</i> . Some bird species (e.g., crossbills, pine siskins) are vulnerable to vehicles strikes and are therefore considered in the assessment.
Amphibians (including Western Toad)	-	X	-	X	Yes	Yes	Considered because western toads are a Species of Special Concern under Schedule 1 of SARA (City of Terrace 2002). Biological importance as indicator species. High traffic roads can cause considerable mortality, particularly during breeding migrations (Lesbarrères, Lodé, and Merilä 2004). There is potential for toads and toadlets to be moving from breeding sites to upland areas and to cross roads, and for a spill to occur in a nearby wetland occupied by toads; therefore, they are considered in the assessment.
Deer (Mule and White-tailed)	X	-	-	X	No	No	Considered because this group is culturally important for the Nisga'a Nation, Gitksan and Gitanyow. It is also hunted by local residents. Deer are excluded because white-tailed deer and mule deer populations are secure and not at risk in BC and any effects of increased traffic along Highway 37 will be accounted for in the assessment by referring to the moose assessment.

(continued)

Table 5.3-2. Identification and Rationale for Wildlife Valued Component Selection/Exclusion (continued)

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	Normal Project Traffic?	Traffic Accidents?	
Mountain Goat	X	X	X	X	No	No	Considered because mountain goat are identified as a culturally important and hunted species for the Nisga'a Nation, Tahltan, Gitksan, Skii km Lax Ha and Gitanyow. Under the Nisga'a Final Agreement, mountain goat is also an initial designated species for which the Nisga'a have a wildlife allocation. Identified as an important species requiring increased management consideration by land management plans including Nass South SRMP (BC MFLNRO 2012b), Cassiar Iskut-Stikine LRMP (BC ILMB 2000b), Cranberry SRMP (BC MFLNRO 2012a), and the Nisga'a Land Use Plan (NLG 2002). Mountain goats are excluded because there is a very low likelihood of vehicle-related mortality of mountain goats in association with the Project along Highway 37. The highway is located at elevations below suitable goat habitat, thereby limiting the possibility of goats being present on or near the road. Mountain goat sensitivity to disturbance may also ensure that they remain a safe distance away from transportation infrastructure. This is supported by the complete absence of vehicle incidents involving mountain goats along highways in the Bulkley-Stikine District from 1983 to 2002 (Sielecki 2004).
Wolverine	X	X	X	X	No	No	Considered because wolverine is blue-listed in BC and of Special Concern by the Committee on the Status of Endangered Wildlife in Canada (COSEWIC 2003). Culturally important species for the Tahltan, Gitksan, and Skii km Lax Ha. Also identified in the Nass South SRMP (BC MFLNRO 2012b) and Cranberry SRMP (BC MFLNRO 2012a) as requiring enhanced management consideration. Wolverine are excluded because wolverines are habitat generalists and wolverine's low population density and large home range size mean there would be limited interaction with the proposed Project traffic. There is a very low likelihood of vehicle-related mortality of wolverine in association with the Project along highways 37 and 37A. This is supported by the complete absence of vehicle incidents involving wolverine along highways in the Bulkley-Stikine District from 1983 to 2002 (Sielecki 2004).
Fisher	X	-	X	X	No	No	Considered because fisher are provincially blue-listed. Culturally important and trapped species by the Nisga'a Nation, the Tahltan, Gitksan, Gitanyow and Skii km Lax Ha. Identified as an important species requiring increased management consideration by land management plans including the Nass South SRMP (BC MFLNRO 2012b), Cranberry SRMP (BC MFLNRO 2012a) and Cassiar Iskut-Stikine LRMP (BC ILMB 2000b). There is a very low likelihood of vehicle-related mortality of fisher in association with the Project along highways 37 and 37A. This is supported by the complete absence of vehicle incidents involving fisher along highways in the Bulkley-Stikine District from 1983 to 2002 (Sielecki 2004); therefore, fisher are excluded from the assessment.

(continued)

Table 5.3-2. Identification and Rationale for Wildlife Valued Component Selection/Exclusion (completed)

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	Normal Project Traffic?	Traffic Accidents?	
Lynx, fox, wolf, coyote, weasel, ermine, mink, river otter	X	-	-	-	No	No	These species were considered because they are identified as culturally important for the Nisga'a Nation (weasel, lynx, wolf, mink), the Tahltan (wolf, lynx, mink, river otter), Gitksan (lynx, fox, wolf, coyote, weasel, mink, river otter), Gitanyow (fox, lynx, coyote, wolf, ermine, mink) and Skii km Lax Ha (wolf). Lynx, fox, coyote and weasels were excluded because their populations are considered stable and not at risk, have low population density, are able to adapt to and tolerate human disturbance and encroachment well. There is a very low likelihood of vehicle-related mortality of these species in association with the Project along highways 37 and 37A. This is supported by the low number of vehicle incidents involving these species along highways in the Bulkley-Stikine District from 1983 to 2002 (Sielecki 2004); therefore, they are excluded from the assessment.
Rodents, rabbits, hares (beaver, squirrels, muskrat, gophers, porcupine, snowshoe hare)	X	-	-	-	No	No	Considered because these species were identified as culturally important for the Nisga'a Nation (beaver, rabbit, porcupine), the Tahltan (snowshoe hare, red squirrel, flying squirrel, ground squirrel, porcupine), Gitksan (beaver, squirrel), Gitanyow (beaver, muskrat, red squirrel, porcupine) and the Skii km Lax Ha (beaver, muskrat, rabbit, ground squirrel). These species are excluded because populations are considered stable and not at risk.

¹ "X" indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; "-" indicates that the group did not identify the VC as an issue.

² "Yes" indicates that the VC is selected for further analysis; "No" indicates that the VC is excluded from further analysis.

Table 5.3-3. Potential Traffic / Wildlife Valued Component Interaction Matrix

Traffic Type	VCs			
	Moose	Bears	Western Toad	Birds
<i>Project traffic</i>				
All traffic	X	X	X	X
<i>Traffic accidents: on-road</i>				
Non-hazardous cargo	-	-	-	-
Hazardous cargo	X	X	-	-
<i>Traffic accidents: off-road</i>				
All traffic	X	X	X	-

"X" indicates that a potential interaction has been identified.

"-" indicates that no potential interaction was identified.

Given the hierarchical nature of biological systems, potential wildlife effects are discussed with regard to changes at both the individual animal level (e.g., behaviour, physiological condition, survival) and the population level (population size, distribution, mortality rate, reproductive fitness). A population is defined as "a group of organisms coexisting at the same time and place and capable of interbreeding" or "as a group of non-specific organisms that occupy a loosely defined geographic region and exhibit reproductive continuity from generation to generation" (Futuyma 1979). Because the geographic

population boundaries for the local populations considered in this assessment are both unknown and dynamic, the assessment is generally qualitative. Effects at the population level are considered of greater concern because of their magnitude, compared to those at the individual level; thus, the assessment primarily focuses on potential effects on local populations.

The following sections (5.3.3.1 to 5.3.3.4) assess the risk of Project-related traffic effects on each VC. Each section is subdivided according to the issues deemed to be of concern for that VC. Within each section, the likelihood and severity (Table 5.3-4) of potential effects on wildlife VCs are predicted. A detailed description of the effects assessment methodology is presented in Chapter 4.

Table 5.3-4. Wildlife Risk Assessment Severity Scale Descriptors

Descriptor	Definition
Negligible	No detectable change from baseline conditions. Effect limited to a few individuals.
Minor	Differs from the average value for baseline conditions to a small degree (e.g., within the range of natural variation and well below a guideline or threshold value). Effect mainly limited to a few individuals.
Moderate	Differs substantially from the average value for baseline conditions and approaches the limits of natural variation, but below or equal to a guideline or threshold value. Effect limited to the local population.
Major	Differs substantially from baseline conditions beyond a guideline or threshold value, resulting in a detectable change beyond the range of natural variation. Effect limited to the local population.
Catastrophic	Differs substantially from baseline conditions beyond a guideline or threshold value, resulting in a detectable change beyond the range of natural variation. Effect extends beyond the local population to the regional population.

Three potential effects were identified for this assessment. These included disruption of movement patterns (which includes sensory disturbance), direct mortality, and chemical hazards (Tables 5.3-5 and 5.3-6). Each of these potential effects, including mitigation and predicted severity of effects is discussed in further detail in the following sections.

5.3.3.1 Disruption of Movement

Risk Identification

Wildlife movement corridors are linear landscape features that provide a linkage between daily or seasonal habitats, and facilitate movement. Movement between isolated patches of habitat is important to maintain wildlife populations and biodiversity (Bennett 2003). Disruption of movement patterns is often the result of increased habitat/landscape fragmentation (e.g., increased density of human access corridors such as roads, and increased cleared area) or higher road use levels, which may limit daily or seasonal wildlife travel. This section outlines the potential effects of Project traffic along the highways on moose and bear movement.

Individual wildlife movement patterns are associated with short-range movements (i.e., daily routine) and long-range movements (i.e., migration and dispersal). Short-range movements are day-to-day activities within a particular season. Long-range wildlife movements are typically passages or movement corridors from winter and summer ranges or dispersal of young individuals to new territories. Moving between summer and winter ranges is critical when one habitat cannot support a species in both seasons. Moose, for example, are known to migrate up and down river drainages, moving between their seasonal ranges (Demarchi 2003). Dispersal is critical for the maintenance of many populations (Clobert et al. 2001). Dispersal distances can be many times greater than home range distances. Typically, the greatest risk of disruption, blockage, and impediments to wildlife occurs with seasonal and dispersal movements.

Table 5.3-5. Wildlife Risk Assessment Matrix for Project Traffic

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Moose	All traffic types	Disruption of Movement	All phases	Adhere to speed limits and wildlife warning signs along highways, give wildlife right of way, limit traffic disturbance where possible	Possible	Minor	Roads with traffic may act as a barrier to movement for a few individual moose.
Bear	All traffic types	Disruption of Movement	All phases	Adhere to speed limits and wildlife warning signs along highways, give wildlife right of way, limit traffic disturbance where possible	Possible	Minor	Roads with traffic may act as a barrier to movement for a few individual bears.
Moose	All traffic types	Direct Mortality	All phases	Adhere to and enforce speed limits, yield to wildlife along roads, document vehicle/wildlife interactions, communicate observations of wildlife to other trucks	Possible	Moderate	An average of approximately 20 moose are killed per year due to vehicle collisions along Highway 37 between Kitwanga and Burrage (within the Project study area). Project traffic will increase the traffic volume along the highways and direct mortality to moose is possible. However, even through traffic volumes will be increasing considerably, the number of animal collisions will not increase by an equal percentage.
Bear	All traffic types	Direct Mortality	All phases	Adhere to and enforce speed limits, yield to wildlife along roads, document vehicle/wildlife interactions, communicate observations of wildlife to other trucks	Possible	Minor	Between 0 and 28 bears are killed per year due to vehicle collisions. Project traffic will increase the traffic volume along the highways and direct mortality to bears is possible. However, even through traffic volumes will be increasing considerably, the number of animal collisions will not increase by an equal percentage.
Western Toad	All traffic types	Direct Mortality	All phases	Adhere to and enforce speed limits, document vehicle/wildlife interactions v	Possible	Minor	Western toads may be impacted by increased traffic if migration events occur across the highways.
Birds	All traffic types	Direct Mortality	All phases	Adhere to and enforce speed limits, document vehicle/wildlife interactions v	Possible	Minor	Mortality events involving flocking bird species (e.g., pine siskin or crossbill) and vehicles may occur along the highway, particularly in winter or spring.

Table 5.3-6. Wildlife Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Moose	All traffic types	Chemical Hazards	All phases	Spills will be mitigated per the Spill Prevention and Emergency Response Plan. Part of the spill response plan is immediate cleanup, which will minimize if not eliminate effects on wildlife receptors. Wildlife will be excluded from the spill site if cleanup cannot occur immediately.	Unlikely	Minor	In the rare event of a traffic accident, chemical hazards may pose a risk to moose. It is anticipated that the cleanup will occur immediately and moose will be excluded from the spill site, reducing the risk.
Bear	All traffic types	Chemical Hazards	All phases	Spills will be mitigated per the Spill Prevention and Emergency Response Plan. Part of the spill response plan is immediate cleanup, which will minimize if not eliminate effects on wildlife receptors. Bears will be excluded from the spill site if cleanup cannot occur immediately.	Unlikely	Minor	In the rare event of a traffic accident, chemical hazards may pose a risk to bears. It is anticipated that the cleanup will occur immediately and bears will be excluded from the spill site, reducing the risk.
Western Toad	All traffic types	Chemical Hazards	All phases	Spills will be mitigated per the Spill Prevention and Emergency Response Plan. Part of the spill response plan is immediate cleanup, which will minimize the effects on toads.	Unlikely	Moderate	In the rare event of a traffic accident, chemical hazards may pose a risk to western toads if the spill occurs in a wetland occupied by toads.

Wildlife species and individuals within populations are not affected to the same degree by the potential barrier effect of roads and traffic. Roads may act as filters that stop some individuals, or allow others to pass through. However, by filtering out different species or portions of a population, habitat barriers can have important population level effects (Fahrig and Rytwinski 2009). The volume of vehicle traffic along a road will affect species differently. In general, large roads with relatively high traffic volume have the highest effect on wildlife crossing, while roads with lower volumes are crossed or used as travel pathways.

Increased traffic volumes along highways 37 and 37A may decrease moose and bear crossings, affecting movement. For the purpose of this assessment, it is assumed that vehicles will be used during construction, operation, closure, and post-closure for 365 days a year, 24 hours per day. The numbers of vehicles on the road per day, and per hour, are summarized in Tables 5.3-7 through 5.3-9.

Table 5.3-7. Average Annual Daily Traffic along Highway 37 (Eskay Creek Mine Access Road to Meziadin Junction)

Project Phase	Average Number of Vehicles*		Average Number of Vehicles with Hazardous Cargo	
	Vehicles/day	Vehicles/h	Vehicles/day	Vehicles/h
Construction (5-year period)	22	0.92	1	0.04
Operation (51.5-year period)	85	3.54	36	1.50
Closure (3-year period)	16	0.67	3	0.13
Post-closure (250-year period)	6	0.25	3	0.13

* Vehicles represent one-way trips.

Table 5.3-8. Average Annual Daily Traffic along Highway 37 (Meziadin Junction to Kitwanga)

Project Phase	Average Number of Vehicles*		Average Number of Vehicles with Hazardous Cargo	
	Vehicles/day	Vehicles/h	Vehicles/day	Vehicles/h
Construction (5-year period)	25	1.04	1	0.04
Operation (50 to 55-year period)	49	2.04	18	0.75
Closure (3-year period)	16	0.67	3	0.13
Post-closure (250-year period)	6	0.25	3	0.13

* Vehicles represent one-way trips.

Table 5.3-9. Average Annual Daily Traffic along Highway 37A

Project Phase	Average Number of Vehicles*		Average Number of Hazardous Vehicles	
	Vehicles/day	Vehicles/h	Vehicles/day	Vehicles/h
Construction	3	0.13	0	0
Operation (50 to 55-year period)	36	1.50	18	0.75

* Vehicles represent one-way trips.

Disruption of movement will begin during the construction phase of the Project along Highway 37, and continue through operation on both highways 37 and 37A, and closure and post-closure along Highway 37. Wildlife VCs that may be affected by disruption of movement include both moose and bears.

Risk Mitigation

Mitigation strategies that will be introduced to reduce the disruption to wildlife movement include minimizing potential vehicle-related disturbance to wildlife (e.g., wildlife right-of-way, speed limits, and adhering to signage in areas of wildlife crossing).

Risk Characterization

Moose

Disruption of moose movement may occur because of increased traffic volume along highways 37 and 37A. The effects on moose are likely to be related primarily to the physical presence of vehicles. While studies have documented the reactions of moose to vehicle traffic, it is unknown if the reactions result in a disruption of movement. In Denali National Park, for example, 50% of moose showed no reaction to buses, 20% showed a mild reaction, and 29% showed a strong reaction within 20 m of the road (Jalkotzy, Ross, and Nasserden 1997).

High quality moose winter habitat, UWRs, and movement corridors have been identified in the Study Area (Section 5.3.2). Therefore, increased traffic along Highway 37, particularly near movement corridors and high quality habitat, may reduce movement between these areas for moose.

Traffic volumes have decreased along the highways since 2000. Traffic at Meziadin Junction has decreased from approximately 500 annual average daily trips in 2000 (approximately 21 vehicles/hour), to approximately 200 in 2008 (approximately nine vehicles/hour; BC MOTI 2011e). Therefore, traffic volumes have decreased by more than half. Project traffic will add a maximum of four vehicles per hour along Highway 37, remaining below volumes reported in 2000.

Despite mitigation, it is possible that disruption of movement to moose may occur as a result of increased traffic on the highways (particularly Highway 37), but the severity is expected to be minor.

Bear

Grizzly bears maintain large individual home ranges that include separate seasonal habitats, such as wetlands in early spring and alpine areas in the late summer. Travel routes within and between habitats are variable and in most cases not easily identifiable in the landscape. The greatest potential impacts to grizzly bear movements are therefore when one seasonal habitat is completely isolated from another.

Roads may act as barriers to grizzly bear movements, effectively isolating seasonal habitats. Females are particularly sensitive and avoid crossing large roads in some parts of their range (Ross 2002; Waller and Servheen 2005). Roads can also act as an attractant, however, offering high quality vegetation forage along the roadside. Thus, the crucial point for bears is the amount of traffic on roads. When traffic volume rises above a threshold point, bears may avoid a particular road, making it a barrier to movement.

The numbers of vehicles on the road per day, and per hour, are summarized in Tables 5.3-7 through 5.3-9. The maximum number of vehicles will occur during the operation phase. During operation, the maximum traffic volume will increase by approximately four vehicles per hour along Highway 37 and approximately two vehicles per hour along Highway 37A. Bears were reported to cross roads when traffic volumes are less than 10 vehicles per hour (Waller and Servheen 2005). Given the current traffic volume (approximately nine vehicles per hour), the additional four Project-related vehicles per hour along Highway 37 will result in 13 vehicles per hour, which is slightly higher than the threshold of 10 vehicles per hour and may result in a barrier to movement for bears.

During construction and operation, potential vehicle-related disturbance to wildlife will be minimized by identifying wildlife right-of-ways, posting speed limits, and adhering to signage in areas of wildlife crossing. In addition, Project traffic volumes will decrease to six vehicles per day along Highway 37 in the post-closure phase. Despite mitigation, it is possible that disruption of movement to bears will occur as a result of increased traffic on the highways (particularly Highway 37), but the severity is expected to be minor.

5.3.3.2 *Direct Mortality*

Risk Identification

Direct mortality of wildlife could occur along highways 37 and 37A as a result of vehicle traffic from the Project to Stewart and Kitwanga. Records of mortalities of several wildlife species along the highway are kept by the Province (Sielecki 2004). This information is compiled in the Wildlife Accident Reporting System (WARS) database, which is maintained by BC MOTI. There are several limitations to the WARS data, including under-representation of wildlife mortalities and lack of information regarding locations of accidents. For example, in 2002, of 5,031 reports received, 28% lacked valid segment numbers, and 28% lacked valid kilometer references (Sielecki 2010). Therefore, although WARS data are the best available information, they must be interpreted with caution.

The Project will contribute to traffic volumes on highways 37 and 37A. During construction, a maximum of 25 Project trucks per day will be travelling along Highway 37 (Table 5.3-8), and will increase to a maximum of 85 Project trucks per day during operation (Table 5.3-7); therefore, potential vehicle interactions with moose, bear, western toad, and birds could occur.

Risk Mitigation

Vehicle-related mortality will be mitigated through the following measures:

- adhering to and enforcement of speed limits;
- yielding to wildlife observed along the road;
- communicating locations of observed wildlife to other trucks; and
- documenting cases and locations where collisions between wildlife and vehicles have occurred or have a higher likelihood of occurring and adapting mitigation strategies based on information gathered (Rea et al. 2006; Hesse et al. 2010).

Risk Characterization

Moose

Direct mortality of moose caused by vehicle collisions on highways 37 and 37A could occur during the construction, operation, closure and post-closure phases.

In general, ungulate-vehicle collisions tend to be aggregated in both time and space: temporal patterns include changing food availability, seasonal migrations, and snow cover; while spatial factors include location of preferred foraging habitat, landscape topography, and road and traffic characteristics. Increased collision risk with animals is also associated with linear landscape features that funnel animals alongside or across roads, such as riparian corridors, transmission lines and steep slopes and ridges (Seiler 2005).

The density of moose in particular areas may increase the risk of collisions with vehicles (Seiler 2005). During the growing season, moose may frequent edge habitats, such as road verges, because they

contain succulent and high-quality forage and provide easy movement. Vehicle-related animal strikes also depend on vehicle speed and traffic volume. Moose-vehicle collisions in northern BC appear to be more frequent in winter (December and January), coinciding with times of high snowfall when they are found near highways that are actively kept clear of snow (Sielecki 2004, 2010).

Moose-vehicle collisions occur throughout the species range and are highlighted as a problem from both wildlife management and traffic safety perspectives (Sielecki 2004; Rea et al. 2006). Along highways in the Bulkley-Stikine District (which includes highways 16, 37, and 37A), collisions with moose were the most commonly recorded road accident between 1988 and 2007 (1,022 incidents), representing 38% of all wildlife collisions, and an average of approximately 51 moose/year (Sielecki 2010).

Within the Bulkley-Stikine District, the WARS database is subdivided into highway LKI segments. These data are also an under-representation of the actual number of wildlife collisions, mainly due to reporting error. Despite being the best available data, the numbers must be interpreted with caution. The Project transport route covers a portion of Highway 37 from Kitwanga to the Eskay Creek Mine access road, which is included in LKI segments 3710, 3720, 3730, and 45 km of 3740 (LKI 3740 extends north from Bell II to Burrage, approximately 39 km north of the Eskay Creek Road). LKI segment 3740 is included in this assessment, as the Study Area includes 54% of this segment. The transport route along Highway 37A is LKI segment 3725. Wildlife accidents in the four LKI segments along Highway 37 between 1991 and 2010 consist primarily of moose (N = 111; average 5.8 moose/year; BC MOTI 2011a). The majority (51%) of moose collisions occurred in December (N = 22) and January (N = 35). Along Highway 37A, only three moose accidents were reported (BC MOTI 2011a).

It is estimated that the wildlife collision numbers recorded by the WARS system may only represent 25% to 35% of the actual number of animals killed on roads (Sielecki 2010). The average number of moose-vehicle collisions per year along Highway 37 within the Study Area is 5.8. Based on the estimate that only 25% to 35% of actual kills are reported, the number of vehicle/moose collisions could in fact range from 17 to 23 per year (average 18.5 moose per year).

In order to assess the potential effects of increased direct mortality of moose due to increased traffic, a population viability assessment was conducted of the Nass moose population. A population dynamics model received from the British Columbia Ministry of Environment was used to perform a historical reconstruction of the Nass population under known harvests and demographic rates.

A statistical reconstruction produced a best fitting model to empirical trends of abundance survey data and harvest survey data. A moose vehicle collision model was imbedded into the population dynamics model to emulate the fraction of moose mortality that could be explained by the current level of vehicle collisions. The parameters estimated in the statistical reconstruction were treated as predictors of how the Nass population behaves, and used to perform a sensitivity analysis of population predictions under future assumed conditions of harvest and vehicle traffic (see Appendix D).

The model results indicated that:

- Overall, the modeled population is very sensitive to small changes in survival rate – this result is partly due to the many age classes (20) used in the BC MOE model – yielding a modeled population which is likely more sensitive to changes in mortality than the true Nass moose population. Typical moose models use only 3 age classes and are typically less sensitive to small changes in survival.
- Historic reconstruction of the moose population indicates that hunting rates were the likely initial cause of the moose population decline from 1595 to 517 animals during 2001 - 2011.

- Under a scenario of current traffic and hunting levels, the model predicts that the Nass moose population will not decline substantially, on average, by 2030.
- The addition of traffic from the KSM project is projected to cause an additional <1% mortality to the moose population at the current population size, a mortality rate that does not predict a substantial decline from the base case scenario.
- Under a scenario of baseline traffic plus KSM traffic, if the modeled survival rate of moose is increased a small amount (2-3%) such as by altering hunting rates, the model predicts an increase in the Nass moose population by 2030 from current conditions.

After mitigation, it is possible that vehicle/moose collisions will occur resulting in direct mortality due to increased traffic on the highways (particularly Highway 37).

Because of the current status of the moose population in the area (i.e., with a history of declining), the high value habitat along Highway 37, and the modeled possible future scenarios with the addition of KSM, the severity is expected to be moderate.

Bear

Vehicle collisions will be of concern for both grizzly and black bears. Direct mortality caused by vehicle collisions could occur along highways 37 and 37A. In the spring, bears that have recently emerged from torpor often forage on roadside vegetation and carrion, and are typically less cognizant of potential dangers. Wildlife accidents involving bears increased between 1988 and 2007 in the Bulkley-Stikine District, ranging from 0 to 28 per year, with approximately 67% (of 248) reported from 1999 to 2007 (Sielecki 2004, 2010). However, traffic at Meziadin Junction (i.e., highways 37 and 37A) has decreased from 469 annual average daily trips in 2000, to 224 in 2008 (BC MOTI 2011e). There appears also to be a seasonal trend, with the majority of strikes occurring in the months of August and September (Sielecki 2004, 2010). There is no risk of vehicles colliding with bears in winter, as bears are in their dens during winter months.

Between 1991 and 2010, there were 108 reported vehicle accidents with bears in the four LKI segments along Highway 37 (average 5.7 bears/year; BC MOTI 2011a). The majority (68.5%) of bear collisions occurred in July (N = 21), August (N = 24), and September (N = 29). Along Highway 37A, 26 bear accidents were reported between 1996 and 2010 (BC MOTI 2011a).

It is estimated that the wildlife collision numbers recorded by the WARS system may only represent 25% to 35% of the actual number of animals killed on roads (Sielecki 2010). The average number of bear/vehicle collisions per year along Highway 37 within the Study Area is 5.7, and along Highway 37A is 2.2. Based on the estimate that only 25% to 35% of actual kills are reported, the number of bear/vehicle collisions along Highway 37 could in fact range from 16 to 23 per year (average 20 bears per year), and from six to nine per year along Highway 37A.

Project-related vehicles would add to traffic on highways, thus increasing the probability of bear-vehicle collisions. Along roads, bears will be at risk of vehicle collision along areas where habitat is suitable for grizzly bears and black bears, particularly near salmon spawning habitat in September (e.g., near Meziadin Lake and Cranberry River, the lower Bowser River to its confluence with the Bell-Irving River, Hanna and Tintina creeks near Meziadin Junction, and the large floodplain associated with the Bell-Irving River and Teigen Creek drainages near Bell II), or near proposed grizzly bear WHAs.

Potential project-related vehicle interactions with bears would be mitigated through adherence to road and traffic signs. Despite implementation of mitigation measures, bear collisions with Project vehicles are possible along the highways. The severity will be minor; even though traffic volumes will be

increasing considerably during the operation phase on Highway 37A and the northern sections of Highway 37 (in comparison to current traffic volumes, but not historical peaks) the number of animal collisions may not increase by an equal percentage.

Western Toad

Western toads use terrestrial habitats for most of the year (Bartelt and Peterson 1994) but return to aquatic habitats to breed. Western toads are capable of moving over 5 km between breeding sites; occasional long-distance excursions of up to 7.2 km have been noted for this species (Wind and Dupuis 2002). Young toads (toadlets) spend the first period of their terrestrial life within the riparian area, eventually dispersing upland. Little is known of the mechanisms that determine the direction and magnitude of toadlet dispersal.

The greatest concern for western toad populations near the highways will be direct mortality of adults and newly emerged terrestrial juveniles near roads and close to wetlands during the spring and late summer. High and low-traffic roads can both cause considerable mortality, particularly during breeding migrations (Lesbarrères, Lodé, and Merilä 2004). Western toads will disperse more than 600 m from breeding sites (Rittenhouse and Semlitsch 2007). Therefore, there is potential for toads and toadlets to be moving from breeding sites to upland areas and to cross a road. Toad mortality is possible along the highways, but the severity will be minor, as traffic already exists on the highways.

Birds

Direct mortality of birds, particularly flocking species such as pine siskins and crossbills, may occur as a result of increased traffic along the highways. Most road mortalities to these species occur during winter or early spring (Campbell et al. 1997). Crossbills, grosbeaks, and siskins are particularly vulnerable to vehicle collisions on highways, as they are attracted to road salts, gravel, and sand (Mineau and Brownlee 2005). It has also been noted that high traffic volume roads can have a repelling or avoidance effect on small vertebrates, thus potentially decreasing the risk of mortality to birds (Clevenger, Chruszcz, and Gunson 2003). The Project will be contributing a maximum of four additional vehicles per hour to the existing nine vehicles per hour north of Meziadin Junction. South of Meziadin Junction, the Project will contribute an additional two vehicles per hour, which is approximately 6% of the existing 33 vehicles per hour. Therefore, although bird mortality is possible along the highways, the severity will be minor.

5.3.3.3 *Chemical Hazards*

Risk Identification

Chemicals transported by truck along the highways could be released into the environment in the event of a motor vehicle accident (see Table 2.4-6 for a list of chemicals intended to be used in Project activities). For the purpose of this assessment, a chemical hazard is defined as “a chemical that has the potential to cause an adverse health effect on wildlife receptors (VCs) due to a chemical spill along the highway.” This potential depends on the concentration of a chemical in the environment and the exposure that a VC receives. However, the chemical concentrations occurring in the environment after an accident cannot be reliably predicted. Potential effects of chemical hazards on moose, bear, and western toad could occur and are described in greater detail in Table 6.4-5 in Section 6.4.4.

Risk Mitigation

Spills will be mitigated as per the Spill Prevention and Emergency Response Plan. Part of this plan is immediate clean-up, which will minimize if not eliminate effects on wildlife receptors. In addition, wildlife would be excluded from the spill site until effective clean-up of the area. However, in the

event of a major spill, soil, water, and vegetation within the spill area will be monitored to ensure that the chemical levels are within the appropriate regulatory guidelines.

Risk Characterization

In the event of a chemical spill, the time that elapses between occurrence and subsequent clean-up represents the potential for acute effects on VCs near the spill. However, these potential effects cannot be evaluated at this time because the volume of the spill and the concentrations that may enter the environmental media are unknown. Other information required in evaluating this risk, such as the location of the spill or the time of year, is also unknown; therefore, in the event of a spill a risk assessment that evaluates acute exposure to VCs will be implemented.

Moose

Habitats along the highway used by moose, particularly the calving area on the Bell Irving River below Bell II, may be vulnerable to effects from traffic accidents, such as chemical spills. It is possible that individuals may ingest chemicals through soil, water, or vegetation, particularly if the contaminant is in the form of a salt. Although effects on individuals are possible, the fact that moose move great distances indicate that no population level effects from exposure to chemicals along the highway in the event of a spill are expected to occur. An event of this nature occurring is unlikely, and severity would be minor, depending on the location and the amount of time that lapses between occurrence and clean-up.

Bear

Habitats along the highways may be used by bears during spring, summer, and fall (near salmon spawning habitat). Although grizzly bears hibernate for six months of the year and their home range sizes are typically large (25 to 200 square kilometres for females and 60 to 700 square kilometres for males; Demarchi and Johnson 2000), it is possible that individuals may ingest chemicals through soil, water, vegetation and prey. Thus, although effects on individuals are possible, the relatively large home ranges of grizzly bears, and the fact that their home ranges do not substantially overlap, indicate that no population level effects from exposure to chemicals along the highway in the event of a spill are expected to occur. An event of this nature occurring is unlikely, and severity would be minor, depending on the location and the amount of time that lapses between occurrence and clean-up.

Western Toad

Western toads have the potential to be exposed to chemicals in the event of a traffic accident involving the spill of chemicals into a wetland occupied by western toads. Toads could be exposed to the chemicals via the ingestion of soil, water, and prey species and via dermal absorption. Although toads hibernate for up to six months of the year, amphibians are particularly sensitive to environmental contaminants. For example, exposure to liquid chlorine (sodium hypochlorite) is severely toxic to amphibians (Section 6.4.4, Table 6.4-5). An event of this nature occurring is unlikely; however, the severity of the event if it occurred could be moderate, depending on the location (i.e., breeding pond) and the amount of time that lapses between occurrence and clean-up.

5.4 TERRESTRIAL ECOSYSTEMS

5.4.1 Baseline Data Overview

Baseline conditions for terrestrial ecosystems VCs selected for this assessment along the highways are described below.

Highway 37 passes primarily through the valley bottoms, lower slopes, and mid-slopes of valley systems running predominantly north-south. It crosses a variety of ecosystem types, including a network of

mature forest, seral forest, wetlands, and non-treed ecosystems such as avalanche tracks. The highway crosses four biogeoclimatic ecosystem classification zones, which are divided into eight subzones and variants, each with unique vegetation, soil, topographical, and climatic characteristics.

According to existing mapping, more than 86% of the Project’s transportation route is classified as forest (Rescan 2009). Approximately 51% is classified as mesic (intermediate moisture) forest and is characterized by intermediate soil moisture and nutrient regimes that occur on mid-slope positions, and moderately deep to deep soils with unrestricted drainage (Banner et al. 1993). Mesic forests are the dominant ecosystem type in each of the subzones apart from Interior Cedar Hemlock moist cold Nass Variant (ICHmc1), where the moist forest ecosystem type is more dominant. Overall, the moist forest ecosystem type also accounts for a considerable portion of the highway route, while dry forests and wet forests are less common.

5.4.1.1 *Disturbance History*

Many areas along highways 37 and 37A have been disturbed by logging and other development, leading to fragmented late seral forests and the prominence of early seral stages. Few areas of valley bottom intact old growth forests remain, while the remaining forests are heavily fragmented and contain a network of active, inactive, and unmaintained forestry roads.

5.4.2 **Issue Scoping**

5.4.2.1 *Terrestrial Ecosystems Scoping*

Project activities are expected to result in additional traffic volumes on highways 37 and 37A, although not exceeding historical peaks. The principal issues for terrestrial ecosystems associated with Project traffic and traffic accidents are summarized in Table 5.4-1.

Table 5.4-1. Terrestrial Ecosystems Scoping Matrix

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
Project traffic All traffic	Yes	An increase in Project traffic may result in the potential for introduction and spread of invasive plants, and increased incidence of wildfire from improper disposal of smoking material.
Traffic accidents All traffic	Yes	Traffic accidents may result in increased incidence of wildfire and chemical contamination.

5.4.2.2 *Valued Component Scoping*

The selected terrestrial ecosystem VCs and the rationales for their inclusion or exclusion in the assessment are presented in Table 5.4-2. The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise).

5.4.2.3 *Potential Traffic/Valued Component Interactions*

The potential interactions between Project traffic and terrestrial ecosystems VCs along highways 37 and 37A are shown in Table 5.4-3.

Table 5.4-2. Identification and Rationale for Terrestrial Ecosystems Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		
	AG	G	P/S	O	Project Traffic?	Traffic Accidents?	Rationale for Selection/Exclusion
Rare and Sensitive Ecosystems	X	X		X	Yes	Yes	Plant communities (ecosystems) listed by the BC Conservation Data Centre (CDC) have particular threats, declining population trends, or restricted distributions which indicate they require special attention. Managing these communities and plants is a goal outlined in each of the applicable LRMPs.
Old Growth Forest and Management Areas	X	X	X		Yes	Yes	Old growth forests were identified by First Nations, LRMPs, and SRMPs as an important issue. Old Growth Forest and Management Areas are set aside to protect current or future old growth forests.
Other Terrestrial Ecosystems	X			X	Yes	Yes	Other terrestrial ecosystems are important for continued diversity of natural ecosystems and seral stages; they provide a range of wildlife habitat, recreation areas, etc.; and include plant species that are traditionally harvested by Aboriginal groups.

¹ "X" indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; "-" indicates that the group did not identify the VC as an issue.

² "Yes" indicates that the VC is selected for further analysis; "No" indicates that the VC is excluded from further analysis.

Table 5.4-3. Potential Traffic / Terrestrial Ecosystems Valued Component Interaction Matrix

Traffic Type	VCs		
	Rare and Sensitive Ecosystems	Old Growth Forests	Other Terrestrial Ecosystems
Project traffic			
All traffic	X	X	X
Traffic accidents: on-road			
All traffic	X	X	X
Traffic accidents: off-road			
All traffic	X	X	X

"X" indicates that a potential interaction has been identified.

"-" indicates that no potential interaction was identified.

5.4.3 Risk Analysis

The effects assessment addresses potential issues and risks associated with Project traffic interactions with terrestrial ecosystem VCs along highways 37 and 37A.

The following sections describe each potential effect and how it relates to terrestrial ecosystem VCs. Each of these potential effects, including mitigation and predicted likelihood and severity of effects (Table 5.4-4) is discussed in further detail in the following sections.

Three potential effects relevant to terrestrial VCs are identified in relation to Project traffic. These are: (1) introduction and spread of invasive plants, (2) incidence of wildfire, and (3) chemical contamination (Tables 5.4-5 and 5.4-6).

Table 5.4-4. Terrestrial Ecosystems Risk Assessment Severity Scale Descriptors

Descriptor	Definition
Negligible	No detectable change from baseline conditions. Effect limited to a few individuals.
Minor	Differs from the average value for baseline conditions to a small degree (e.g., within the range of natural variation and well below a guideline or threshold value). Effect mainly limited to a few individuals.
Moderate	Differs substantially from the average value for baseline conditions and approaches the limits of natural variation, but below or equal to a guideline or threshold value. Effect limited to the local population.
Major	Differs substantially from baseline conditions beyond a guideline or threshold value, resulting in a detectable change beyond the range of natural variation. Effect limited to the local population.
Catastrophic	Differs substantially from baseline conditions beyond a guideline or threshold value, resulting in a detectable change beyond the range of natural variation. Effect extends beyond the local population to the regional population.

5.4.3.1 *Introduction and Spread of Invasive Species*

Risk Identification

Invasive plants are a considerable threat to natural habitats (Canadian Food Inspection Agency 2008) as they can aggressively establish in disturbed areas, thereby reducing biodiversity (Polster 2005). Their establishment can have a negative effect on ecosystem function, particularly in areas that are maintained in an early seral state, such as road rights-of-way. Roads and other linear corridors provide a continuous zone of such habitat. An increase in vehicular traffic travelling along such corridors provides additional exposure and dispersal mechanisms. Vehicles of any size (e.g., heavy machinery to all-terrain vehicles) can carry plant propagules in tires, the undercarriage, or in mud on the vehicle, and inadvertently transport them to previously unaffected areas.

Invasive plant species can influence ecosystem diversity, structure, and function through invasion, establishment and hybridization. Invasive plants can alter the structure of a natural ecosystem and ultimately change the way in which the site is used by wildlife, insects and microorganisms. Changes to nutrient cycling, hydrology, erosion and fire regimes may also occur (Canadian Food Inspection Agency 2008).

Risk Mitigation

Preventing the initial establishment of invasive plants is the most effective method of control (Clark 2003; Polster 2005; BC MOFR 2010a). Introduction and spread of invasive plants into terrestrial VCs will be avoided through inspections by provincial government staff on Project sites. Where risk of invasive plant introduction and establishment is identified, appropriate action will be taken. Identification of target plants will be based on the management plans outlined by the Northwest Invasive Plant Council (2011).

Risk Characterization

Efforts will be made to avoid invasive plant introduction and establishment. After mitigation, however, if invasive plants are unintentionally introduced, these plants will be managed by the BC MOTI, who controls noxious weeds on rights-of-way within BC. Many invasive plants are not shade-tolerant and do not thrive in the low light conditions found in many riparian and floodplain forests or old growth forests. Thus, the likelihood of invasive plant introduction and spread in rare and sensitive ecosystems is unlikely. Subsequently, the severity is negligible. Nevertheless, the likelihood of invasive plant introduction into other terrestrial ecosystems is likely. Invasive plants can spread from highway rights-of-way to forest edges, which are susceptible to the introduction of invasive species propagules from adjacent clearings (Murphy and Lovett-Doust 2004). The severity is expected to be minor, depending on the invasive plant species involved and the density and distribution of the population.

Table 5.4-5. Terrestrial Ecosystems Risk Assessment Matrix for Project Traffic

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Rare and Sensitive Ecosystems	All traffic types	increase in invasive plant in riparian area and floodplains adjacent to highway	All phases	Ensure vehicles are washed during appropriate time of year prior to leaving areas with known invasive weeds	Unlikely	Minor	Increase in invasive weeds along cleared road right of ways. Some of these cleared right of ways may intersect with riparian areas and floodplains
Old Growth Forests	All traffic types	increase in invasive weeds in old growth forests	All phases	Ensure vehicles are washed during appropriate time of year prior to leaving areas with known invasive weeds	Unlikely	Minor	Old growth forests do not usually have a light regime that promotes invasive plant establishment, as many are not shade tolerant. Old growth forest tend to be located away from the highway
Other Terrestrial Ecosystems	All traffic types	increase in invasive weeds in terrestrial ecosystems	All phases	Ensure vehicles are washed during appropriate time of year prior to leaving areas with known invasive weeds	Likely	Minor	Increase in invasive weeds along cleared road right of ways, which can lead to migration of invasive plants into the adjacent terrestrial ecosystems. Since many invasives are not shade tolerant, compromise of ecosystem function is not expected
Rare and Sensitive Ecosystems	All traffic types	increased wildfire incidence	All phases	No smoking in vehicle policies, proper disposal of smoking materials, proper vehicle maintenance	Rare	Moderate	Wildfire is not common in the ecosystems associated with Highway 37. Risk going forward will depend greatly on larger climate trends. Many rare ecosystems are associated with riparian areas, which are at limited risk for fire. Depends on duration and severity of the wildfire. Ranges from beneficial to detrimental to the ecosystem depending on the extent of removal of the forested ecosystems from the landscape.
Old Growth Forests	All traffic types	increased wildfire incidence	All phases	No smoking in vehicle policies, proper disposal of smoking materials, proper vehicle maintenance	Rare	Moderate	Wildfire is not common in the ecosystems associated with Highway 37. Risk going forward will depend greatly on larger climate trends. Depends on duration and severity of the wildfire. Ranges from beneficial to detrimental to the ecosystem depending on the extent of removal of the forested ecosystems from the landscape.
Other Terrestrial Ecosystems	All traffic types	increased wildfire incidence	All phases	No smoking in vehicle policies, proper disposal of smoking materials, proper vehicle maintenance	Rare	Minor	Wildfire is not common in the ecosystems associated with Highway 37. Risk going forward will depend greatly on larger climate trends. depends on duration and severity of the wildfire. Ranges from beneficial to detrimental to the ecosystem depending on the extent of removal of the forested ecosystems from the landscape.

Table 5.4-6. Terrestrial Ecosystems Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Rare and Sensitive Ecosystems	All traffic types	Increase in vehicle traffic may result in increased accidents involving spilling of deleterious substances, which can result in damage to ecosystem structure and function.	All phases	none	Rare	Negligible to Moderate*	Tissue damage to vegetation and contamination of soil. Circumstances of spill will determine extent and severity of damage.
		Increased incidence and severity of wildfires due to flammable material spills	All phases	none	Rare	Moderate	Depends on duration and severity of the wildfire. Ranges from beneficial to detrimental to the ecosystem depending on the extent of removal of the forested ecosystems from the landscape.
Old Growth Forests	All traffic types	Increase in vehicle traffic may result in increased accidents involving spilling of deleterious substances, which can result in damage to ecosystem structure and function.	All phases	none	Rare	Negligible to Moderate*	Tissue damage to vegetation and contamination of soil. Circumstances of spill will determine extent and severity of damage.
		Increased incidence and severity of wildfires due to flammable material spills	All phases	none	Rare	Moderate	Depends on duration and severity of the wildfire. Ranges from beneficial to detrimental to the ecosystem depending on the extent of removal of the forested ecosystems from the landscape.
Other Terrestrial Ecosystems	All traffic types	Increase in vehicle traffic may result in increased accidents involving spilling of deleterious substances, which can result in damage to ecosystem structure and function.	All phases	none	Rare	Negligible to Moderate*	Tissue damage to vegetation and contamination of soil. Circumstances of spill will determine extent and severity of damage.
		Increased incidence and severity of wildfires due to flammable material spills	All phases	none	Rare	Moderate	Depends on duration and severity of the wildfire. Ranges from beneficial to detrimental to the ecosystem depending on the extent of removal of the forested ecosystems from the landscape.

*See Section 5.4.3.2 for justification of this rating.

5.4.3.2 *Incidence of Wildfire*

Risk Identification

A wildfire is an unplanned natural or anthropogenic fire that may require suppression. On average, about 2,000 wildfires occur in BC every year, half of which are caused by human activity and half by lightning ignition (BC Forest Service Protection Branch 2008). An increase in vehicle traffic along highways 37 and 37A may result in an increased risk of wildfire in comparison to current conditions, but not in comparison to historical peaks in traffic. Such an increase would be related to traffic accidents and improper disposal of smoking materials as ignition sources.

Wildfires have the potential to alter terrestrial ecosystems in terms of plant community species composition, structure and ecosystem function. The potential to alter terrestrial ecosystems is dependent on the severity of a fire, which is determined by both the areal extent and intensity. For example, fires that are of low intensity can be spatially extensive, but still benefit ecosystem function, as they can promote wildlife habitat through increased berry production. Severe fires (or stand replacement events) are spatially extensive and intensive. These result in the wholesale removal of vegetation from the landscape, along with the ecological functions provided by the forest.

Risk Mitigation

Preventing an increase in wildfire incidence will involve reducing the risk of vehicle accidents and enacting strong policies requiring the proper disposal of smoking materials. Reduction of vehicle accidents will be accomplished with policies that address vehicle maintenance, speed limits, driver attention, drug and alcohol prohibition and driving under poor weather conditions.

Risk Characterization

Highway 37 runs through the Kalum Forest District (Northwest Fire Centre) of northwestern BC, which has seen few major (>4 ha burned area) and several minor (<4 ha burned area) wildfires during the past decade (BC MOFR 2008). This low incidence of wildfire is due to the regional climate characteristics (long winters and short, wet summers), and limited access to backcountry areas.

After mitigation, the likelihood of an increase in wildfire incidence due to an increase in traffic is rare. This rating is due mainly to the low background level of fire incidence in this area of BC. Mitigation will be most important during summer months, when weather conditions can result in higher risk of wildfire. The severity of wildfire occurrence is highly variable, and depends on local climate conditions, the time of wildfire ignition, the resources available to respond, and the speed at which it is suppressed.

5.4.3.3 *Chemical Contamination*

Risk Identification

Traffic accidents and malfunctions have the potential to damage terrestrial ecosystems and vegetation through introduction of deleterious substances into the environment. For the purpose of this assessment, a chemical hazard is defined as “a chemical that has the potential to cause an adverse health effect on terrestrial ecosystems (VCs) due to a chemical spill along the highway.” Chemicals transported by trucks along the highway could be released into the environment in the event of a vehicle accident (see Section 2.4.5 for a list of hazardous cargo intended to be used by the Project). These substances could cause loss of vegetation through tissue damage (in the case of lime and reagent spills), or through increased fire incidence and intensity (in the case of fuel and lubricant spills). This potential depends on the concentration of a chemical in the environment and the exposure that a VC receives. Potential effects of chemical hazards on terrestrial ecosystems are described in greater detail in Table 6.4-5 in Section 6.4.4.

Risk Mitigation

Preventing the introduction of deleterious substances into the environment is the most effective way to avoid effects to terrestrial VCs. Specific preventative measures that will be implemented include conducting a vehicle assessment (for oil leaks, secure cargo, etc.), checking road conditions prior to departure, maintaining an appropriate distance between vehicles, adhering to speed limits, and adjusting driving styles to suit road conditions.

In the event of a spill, the guidelines and procedures outlined in the Spill Prevention and Emergency Response Plan will be followed in order to avoid contamination and degradation of terrestrial VCs. However, in the event of a major spill, soil, water, and vegetation within the spill area will be monitored and managed to ensure that the chemical levels are within the appropriate regulatory guidelines.

Risk Characterization

In the event of a chemical spill, the more time that elapses between occurrence and clean-up, the higher the potential for effects on VCs near the spill. However, the full nature of potential effects cannot be evaluated at this time because the volume of the spill and the concentrations that may enter the environmental media are unknown. Other information required in evaluating this risk, such as the location of the spill or the time of year, is also unknown; therefore, in the event of a spill, a risk assessment that evaluates exposure to VCs will be conducted.

After mitigation, the likelihood of chemical contamination to terrestrial VCs is rare. The severity ranges from negligible to moderate depending on the type, frequency and size of the spill as well as the elapsed time between the occurrence and the removal of contaminants.

5.5 WETLANDS

5.5.1 Baseline Data Overview

Although there is limited wetland baseline information for the Highway 37 corridor, data from the publicly available Terrain Resource Information Management (TRIM) Program identifies two types of TRIM wetlands and covers the entire Study Area (Figure 5.1-1):

1. **marsh:** a water-saturated, poorly drained, treeless area, intermittently or permanently water-covered, having cattail, rushes, or grass-like vegetation; and
2. **swamp:** a water-saturated area, intermittently or permanently water-covered, having shrubs.

TRIM data are summarized in Table 5.5-1, which presents areas of TRIM swamp and TRIM marsh within 500 m, 100 m, and less than 10 m of highways 37 and 37A within the Study Area.

Table 5.5-1. Areas of TRIM Wetlands along Highways 37 and 37A within the Study Area

	TRIM Wetlands within 500 m of Highways 37 and 37A		TRIM Wetlands within 100 m of Highways 37 and 37A		TRIM Wetlands within 10 m of Highways 37 and 37A	
	Number	Surface Area	Number	Surface Area	Number	Surface Area
TRIM Marsh	122	7,16.4 ha	32	482.8 ha	15	425.8 ha
TRIM Swamp	122	1,917.6 ha	43	1,069.1 ha	18	427.0 ha
TOTAL	244	2,634.0 ha	75	1551.9 ha	33	852.8 ha

Note: The area of wetlands presented is for the entire polygon even though only a portion of the wetland may be within the area of interest (500 m, 100 m, or 10 m)

5.5.2 Issue Scoping

5.5.2.1 Wetlands Scoping

Project activities are expected to result in additional traffic volumes on highways 37 and 37A, although not exceeding historical peaks. The primary way wetlands may be affected by development is through direct interactions or changes to local hydrology. Direct interactions include constructing infrastructure on wetlands. This activity generally involves in-filling, whereby non-wetland material is deposited in a wetland. Additionally, direct interactions can also result in changes to wetland hydrology. As wetlands are an interface between terrestrial and aquatic systems, subtle changes can result in a significant change in an ecological community. For example, if a road is constructed adjacent to a seepage slope, the impermeable road bed may prevent natural draining, causing a small pond to form, and potentially altering the functions provided by wetlands in that area.

This assessment of potential risks is for the use of existing roads (highways 37 and 37A) and does not consider road alterations, upgrades, or maintenance. Thus, no potential risks to wetlands from Project traffic are anticipated except for potential risks to wetlands associated with traffic accidents (Table 5.5-2).

Table 5.5-2. Wetlands Scoping Matrix

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
<i>Project traffic</i>		
All traffic	No	This assessment is for the use of existing roads; alterations, upgrades, or maintenance to the road are not considered. Thus no, Project traffic/wetland interactions are expected given that wetlands will not be altered.
<i>Traffic accidents</i>		
All traffic	Yes	Traffic accidents have the potential to affect wetlands if accidents occur in or near wetlands, as hydrocarbon contamination may result.

A total of 2,634.0 ha of wetlands were identified within 500 m of the centreline of the highways. However, only wetlands immediately adjacent to the highway (less than 10 m) may be at risk due to traffic accidents. Potential risks for traffic accidents are rationalized in Table 5.5-2.

5.5.2.2 Valued Component Scoping

The VCs usually considered when considering environmental effects on wetlands are extent and function. Wetland extent includes the area of wetlands, the size of individual wetlands, and the type of wetlands present in a given area. Wetland function includes the process that wetlands carry out: principally hydrological, biochemical, ecological, and habitat processes.

This assessment focuses on an activity (the use of existing highways) rather than Project infrastructure. Thus, no affects to wetland extent are expected; the wetland extent as a VC was scoped out of this assessment. The use of the existing highways will also not affect wetland function as the assessment is not considering alterations, upgrades, or maintenance. The use of the highways may affect components of wetland function such as vegetation structure or wildlife, but these effects are addressed elsewhere within this document.

Traffic accidents have the potential to affect one or more wetland functions. For example, a vehicle accident involving a transport truck driven into a wetland may contribute environmental contaminants

to the wetland, which will in turn affect the wetland’s ability to maintain good water quality or provide habitat to the area’s wildlife. Traffic accidents and their effect on wetland function are considered in this document (Table 5.5-3). The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise).

Table 5.5-3. Identification and Rationale for Wetlands Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	...Project Traffic?	...Traffic Accidents?	
Wetland Extent	X	X		X	No	No	Extent is affected by direct footprint interactions. As this assessment is based on use of existing highways potential effects to extent are not expected.
Wetland Function	X	X		X	No	Yes	The use of existing highways will not affect wetlands ability to continue to perform the functions they currently provide; this VC was therefore scoped out. Traffic accidents have the potential to affect wetland function if vehicle crashes or spills occur in wetlands.

¹ “X” indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; “.” indicates that the group did not identify the VC as an issue.

² “Yes” indicates that the VC is selected for further analysis; “No” indicates that the VC is excluded from further analysis.

5.5.2.3 Potential Traffic/Valued Component Interactions

A potential interaction with a VC and the potential consequences to wetland function were only identified for a traffic accident scenario (Table 5.5-3). Traffic accidents are defined as involving one or more vehicles. The accidents can happen in one of two locations: (1) on the road, or (2) off the road. The vehicles will be transporting either non-hazardous or hazardous cargo. Thus four potential traffic accident scenarios were considered with respect to wetland function (Table 5.5-4).

Table 5.5-4. Potential Traffic / Wetlands Valued Component Interaction Matrix

Traffic Type	VCs
	Wetland Function
<i>Project traffic</i>	
All traffic types	-
<i>Traffic accidents: on-road</i>	
All non-hazardous cargo	-
All hazardous cargo	X
<i>Traffic accidents: off-road</i>	
All non-hazardous cargo	X
All hazardous cargo	X

“X” indicates that a potential interaction has been identified.

“-” indicates that no potential interaction was identified.

On-road traffic accidents involving non-hazardous cargo were determined to pose little to no risk to wetland function. An on-road, non-hazardous traffic accident may include a malfunction where one or more vehicles remain on the road and no hazardous substances are involved. A hazardous substance is

defined as any substance that, in the concentrations present, may adversely affect a functioning ecological system.

On-road traffic accidents involving hazardous cargo were determined to pose a risk to wetland function. An on-road, hazardous traffic accident may include any malfunction where one or more vehicles transporting hazardous substances remain on the road. To be included in this traffic accident category, there must be a risk of a hazardous substance being released into the environment. The risk to wetland function arises if the hazardous substance was to migrate from the road surface into a wetland or watercourse.

Off-road traffic accidents involving non-hazardous cargo were determined to pose a risk to wetland function. An off-road, non-hazardous traffic accident may include a malfunction where one or more vehicles leave the road and end up in a wetland. The risk to wetland function arises because every vehicle contains hazardous substances (principally gasoline or diesel) and there is potential that these substances could be released into the wetland.

Off-road traffic accidents involving hazardous cargo were determined to pose a risk to wetland function. An off-road, hazardous traffic accident may include any malfunction where one or more vehicles transporting hazardous substances leave the road and end up in or adjacent to a wetland. The risk to wetland function arises if the hazardous substance were to be deposited in a wetland or watercourse.

5.5.3 Risk Analysis

A risk analysis was completed on the three traffic accident scenarios identified in Table 5.5-4 as having an effect on wetland function. The risk analysis involved assigning a descriptor to the traffic accidents. Wetland risk descriptors are defined in Table 5.5-5.

Table 5.5-5. Wetlands Risk Assessment Severity Scale Descriptors

Descriptor	Definition
Negligible	No measurable effect results.
Minor	A measurable effect results but the effect does not affect a wetland's ability to carry out its functions. For example, a kitchen supply truck crash deposits baked goods into a wetland.
Moderate	A measurable effect results and the ability of a wetland to perform a given function is affected. For example, a kitchen supply truck crash deposits baked goods into a wetland drainage temporarily retarding water release.
Major	A measurable effect results and the wetland can no longer provide a given function. For example, a kitchen supply truck crash deposits cleaning products and chemicals which make the wetland hazardous to animals.
Catastrophic	A measurable effect results and the wetland can no longer provide two or more functions at multiple wetlands. For example, a kitchen supply truck crash deposits cleaning products and chemicals which make the wetland hazardous to animals and the accident severely alters the wetland drainage pattern. This in turn has numerous downstream effects resulting in changes to multiple wetlands.

The risk assessment was generalized for all traffic types because all traffic types are susceptible to accidents. The potential risks were identified as:

- on-road traffic accidents involving hazardous cargo;
- off-road traffic accidents involving non-hazardous cargo; and
- off-road traffic accidents involving hazardous cargo.

The wetland risk assessment matrix for these traffic accident scenarios is presented in Table 5.5-6.

Table 5.5-6. Wetlands Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Wetland Function	All traffic types	deposition of deleterious substances in wetlands from: <ul style="list-style-type: none"> • on road, toxic, unintended events • off road, non-toxic, unintended events • off road, toxic, unintended events 	All phases	Limit the extent of contamination; Limit the time a contaminant may be in contact with a wetland, and follow Spill Prevention and Emergency Response plans	Unlikely	Major	A loss of wetland function at a wetland

5.5.3.1 Vehicle Accident in Wetland

Risk Identification

These potential risks were identified as possible in all Project phases because highway use is expected in some capacity during each Project phase and wetlands are distributed along the travel corridor.

Risk Mitigation

Mitigation measures for potential effects on wetland function include:

- limiting the time any vehicle or deleterious substance remains in a wetland after a traffic accident (Spill Prevention and Emergency Response Plan); and
- limiting the extent to which a deleterious substance can migrate through a wetland; and following standard spill prevention and emergency response planning.

Risk Characterization

The likelihood of any one Project-related traffic accident releasing deleterious substances into a wetland was identified as unlikely. The severity of one of these traffic accidents was assessed as major; however, depending on the specific location and type of vehicle, the severity could range from minor to catastrophic for a specific wetland. Potential effects of chemical hazards on wetlands are described in greater detail in Section 6.4.4, Table 6.4-5.

5.6 NOISE

5.6.1 Baseline Data Overview

Baseline noise data was calculated by BKL using traffic data counts at two locations in the Study Area (Appendix E). Noise baseline information is required to quantify the potential increase in noise levels near the Project traffic corridor (northern segment) and near the town of Kitwanga (southern segment). The *northern segment* noise level was calculated based on the traffic count on Highway 37 at Meziadin Lake Junction Station (47-016-NS; located 1 km north of the Highway 37/37A intersection on Highway 37); the *southern segment* noise level was calculated based on the traffic count data at the intersection of Highway 37 and Highway 16 by Kitwanga.

The predicted A-weighted baseline noise levels, averaged over 24 hours, are summarized in Table 5.6-1. The receiver distance of 50 m and 25 m for northern and southern segments, respectively, is the distance from the Highway to the closest house⁸ based on Google Earth imagery, close to the locations of the traffic counts.

5.6.2 Issue Scoping

5.6.2.1 Noise Scoping

Project activities are expected to result in additional traffic volumes on highways 37 and 37A, although not exceeding historical peaks. Project traffic over all phases of the Project may lead to an increase in noise levels in the Study Area. The magnitude of the increase will depend on the traffic volume as it is more or less continuous for the duration of the Project.

⁸ NAD83 UTM Zone 9: North segment receiver is at an easting of 480966.78 m, and a northing of 6217255.63 m; South segment receiver is at an easting of 559072.81 m, and northing of 6106353.34 m.

Table 5.6-1. Estimated Baseline Traffic Noise Levels Averaged Over 24 Hours

Count Station	Case	Existing Noise Level (dBA)	Receiver Distance (m)
North Segment (47-016-NS)	AADT	47	50
	SADT	49	
South Segment (P47-9-NS)	AADT	58	25
	SADT	59	

Source: BKL 2013, Appendix E

Traffic accidents may also contribute to increases in noise levels depending on the type and severity of the accident. However, these events are short-term and temporary, and not considered to be a risk. For the purposes of this study, noise resulting from traffic accidents is not considered further. Table 5.6-2 identifies the potential noise issues related to traffic.

Table 5.6-2. Noise Scoping Matrix

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
<i>Project traffic</i>		
All traffic	Yes	Increasing noise levels in the vicinity of the traffic
<i>Traffic accidents</i>		
All traffic	No	May cause short-term noise events, but these are not considered to be a risk

5.6.2.2 Valued Component Scoping

The selected noise VCs and the rationales for their inclusion or exclusion in the assessment are presented in Table 5.6-3. The party who identified each potential VC is also referenced in the table, including Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise).

Table 5.6-3. Identification and Rationale for Noise Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	...Project Traffic?	...Traffic Accidents?	
Human Health	-	X	X	X	Yes	No	Noise from increased vehicle traffic increases the noise levels in the Study Area, which may contribute to effects on human health.
Wildlife	X	X	X	X	Yes	No	Noise from increased vehicle traffic increases the noise levels in the Study Area, and may contribute to effects on wildlife.

¹ "X" indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; "-" indicates that the group did not identify the VC as an issue.

² "Yes" indicates that the VC is selected for further analysis; "No" indicates that the VC is excluded from further analysis.

Since vehicle transportation generates noise and therefore increased noise levels, all Project traffic will contribute to effects on VCs during the Project's life span on a regular basis.

5.6.2.3 Potential Traffic/Valued Component Interactions

Environmental noise is comprised of ambient sound levels as well as natural events such as thunder and rain, and human activities such as traffic and industry. Human health and wildlife have been selected as the relevant noise VCs (Table 5.6-4) for the Project. Excess noise can lead to direct or indirect human health effects such as stress, annoyance, and lower sleeping quality and quantity. Disturbance to wildlife from noise from highway traffic can also be important depending on the species affected and length and type of noise disturbance.

Table 5.6-4. Potential Traffic / Valued Component Interaction Matrix – Noise

Traffic Type	VCs	
	Human Health	Wildlife
<i>Project traffic</i>		
All traffic	X	X

“X” indicates that a potential interaction has been identified.

“.” indicates that no potential interaction was identified.

5.6.3 Risk Analysis

Baseline noise levels and predictions for the Project’s operation phase are summarized in Table 5.6-5. Also see Section 5.8.3.2 for further analysis in regards to human health.

Table 5.6-5. Estimated Traffic Noise Levels Averaged Over 24 Hours – Baseline and Predicted during Operation Phase

Count Station	Case	Existing Level (dBA)	Project Operation Phase (dBA)	Receiver Distance (m)
Northern Segment (47-016-NS)	AADT	47	50	50
	SADT	49	52	
Southern Segment (P47-9-NS)	AADT	58	59	25
	SADT	59	60	

Note: Estimated by BKL using the existing traffic and predicted operation (i.e., maximum) phase traffic estimations (Appendix E).

In Section 5.6.2, two noise VCs were identified: human health and wildlife. Risk assessments of increased noise levels on community well-being and human health are presented in Section 5.1, and Section 5.8. Effects on wildlife of increased noise are considered in the assessment of the risk of barrier to movement, presented in Section 5.3.

5.7 CLIMATE AND AIR QUALITY

5.7.1 Baseline Data Overview

The best available estimates of background concentrations for sulphur dioxide (SO₂) are from ambient background concentrations monitored by Environment Canada’s Canadian Air and Precipitation Monitoring Network (CAPMoN). CAPMoN is a non-urban air quality monitoring network with siting criteria designed to ensure that measurement locations are regionally representative (i.e., not affected by local sources of air pollution). The closest CAPMoN measurement site to the Project is the Saturna Station, off the southern tip of Vancouver Island in the middle of the Strait of Georgia (also known as the Salish Sea). Although the station is almost 1,000 km southeast of the Study Area, it provides the best available estimate of background concentrations available for non-urban BC (Environment Canada 2010).

Daily measurements of SO₂ concentration are available from the Saturna Station from 1996 to 2002 (except 1997, from which data are missing). The average annual SO₂ concentration for this period was 2.3 micrograms per cubic metre (µg/m³), with an average standard deviation of 2 µg/m³ (Environment Canada 2010).

Background concentrations for SO₂, nitrogen dioxide (NO₂), and carbon monoxide (CO) from the Diavik Diamond Mine in the Northwest Territories were also estimated in a study done by Cirrus (1998; see Table 5.7-1).

Table 5.7-1. Background Air Contaminant Measurements – Diavik Diamond Mine

Contaminant	Averaging Time Period	Background Concentration (µg/m ³)
SO ₂	1-hour and 24-hour	4.0
	Annual	2.0
NO ₂	1-hour and 24-hour	21.0
	Annual	5.0
CO	All averaging times	100

Source: Cirrus (1998)

The annual average SO₂ background concentration of 2.0 µg/m³ for the Diavik Mine is generally in agreement with the average concentration observed at the Saturna Station. Accordingly, for the purposes of this study, NO₂ and CO background concentrations from the Diavik Mine were assumed to be representative of the conditions of a northern, undisturbed remote area such as the Study Area.

Concentrations of PM_{2.5} are available from McKendry (2006); however, this data does not contain PM₁₀ concentrations, reportedly due to a general lack of PM₁₀ data in pristine environments in BC. However, data from the Galore Creek Project measured 98th percentile background concentrations of PM₁₀ and PM_{2.5} as defined by the province's air dispersion modelling guidelines (BC MOE 2008; see Table 5.7-2).

Table 5.7-2. Background Air Contaminant Measurements – Galore Creek Project

Contaminant	Averaging Time Period	Background Concentration (µg/m ³)
PM ₁₀	24-hour	3.4
PM _{2.5}	24-hour	1.3

Source: RTEC (2006)

The Galore Creek project's background concentration for PM_{2.5} is in general agreement with those measured in the McKendry study. The latter estimated the mean annual PM_{2.5} background as 2.5 µg/m³, with a seasonal range of 1 to 4 µg/m³, and short term peaks of up to 250 µg/m³ from local forest fires. These background levels are well below the BC Air Quality Objectives and Standards level of 8 µg/m³ and the Canadian guide 24-hour level of 25 µg/m³ (Government of BC 2009a).

5.7.2 Issue Scoping

5.7.2.1 Climate and Air Quality Scoping

There are potential climate and air quality issues and risks associated with Project traffic as well as accident scenarios (Table 5.7-3). The main source of air emissions is from vehicle tail-pipe exhaust which will contribute to changes in air quality and climate change.

Table 5.7-3. Climate and Air Quality Scoping Matrix

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
<i>Project traffic</i>		
All traffic	Yes	Air emissions* from vehicle exhaust.
<i>Traffic accidents</i>		
<u>Personnel and non-hazardous cargo</u>		
Personnel vehicle	Yes	Air emissions in case of fire.
Non-hazardous cargo	Yes	Air emissions in case of fire and/or spills.
<u>Hazardous cargo</u>		
All hazardous cargo	Yes	Air emissions in case of fire or spills.

* "Air emissions" are not limited to CACs and GHGs, but refer to air emissions in general.

CACs are the primary pollutants from combustion engines. CACs include oxides of nitrogen (NO_x), SO₂, CO, and particulates, which include both visible (smoke) and non-visible emissions. Air emissions due to Project traffic will lead to an increase in ambient concentrations of CACs during the life of the Project.

Climate change resulting from anthropogenic greenhouse gases (GHGs) is an issue that has been demonstrated by international authorities (IPCC 2007) and recognized by federal and provincial governments (CEA Agency 2003). In general, GHG inventories can be quantified (and reported depending on the size of the Project) for activities such as traffic, and steps can also be taken to mitigate GHG emissions, as will be discussed further in Section 5.7.3.

5.7.2.2 Valued Component Scoping

Project traffic will emit GHGs and CACs during all phases of the Project, affecting both air quality and climate. Traffic accidents may also contribute to effects on air quality and climate if the accidents cause fires or large spills (e.g., chemical reagent spills, burned fuel containers). For these reasons, both climate and air quality were selected as VCs for this risk assessment.

The climate and air quality VCs, and the rationales for their inclusion or exclusion in the assessment are presented in Table 5.7-4. The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise).

Table 5.7-4. Identification and Rationale for Climate and Air Quality Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	... Project Traffic?	...Traffic Accidents?	
Climate	-	X	X	X	Yes	Yes	GHGs from vehicle exhaust contribute to total atmospheric GHGs during operation; therefore, effects may contribute to climate change.
Air Quality	X	X	X	X	Yes	Yes	Air emissions from vehicle exhaust will increase air pollutant concentrations in ambient air during operation. Air contaminants may be emitted in the event of a traffic accident resulting in fire and/or spills from traffic accidents.

¹ "X" indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; "-" indicates that the group did not identify the VC as an issue.

² "Yes" indicates that the VC is selected for further analysis; "No" indicates that the VC is excluded from further analysis.

5.7.2.3 Potential Traffic/Valued Component Interactions

Potential interactions between traffic types identified in Table 5.7-3 and VCs identified in Table 5.7-4 are identified in Table 5.7-5. All traffic types are expected to interact with both climate and air quality.

Table 5.7-5. Potential Traffic / Climate and Air Quality Valued Component Interaction Matrix

Traffic Type	VCs	
	Climate	Air Quality
<i>Project traffic</i>		
All traffic	X	X
<i>Traffic accidents: on-road</i>		
All traffic	X	X
<i>Traffic accidents: off-road</i>		
All traffic	X	X

“X” indicates that a potential interaction has been identified.

“-” indicates that no potential interaction was identified.

5.7.3 Risk Analysis

This assessment evaluates climate and air quality concerns and risks associated with Project traffic-related air emissions resulting from Project operation, as well as traffic accidents.

5.7.3.1 Climate and Air Quality

Risk Identification

Potential effects on climate and air quality VCs will exist during all Project phases. However, the magnitude of climate and air quality effects will be different for each phase because Project traffic volumes will change over time.

Traffic accidents may contribute to climate and air quality effects if flammable cargo or fuel tanks are ignited. For example, an accident involving a fuel truck could cause a fire which results in concentrated, short-term air emissions.

Table 5.7-6 describes the definitions in risk assessment matrices related to climate and air quality.

Table 5.7-6. Climate and Air Quality Risk Assessment Severity Scale Descriptors

Descriptor	Definition
Negligible	No detectable change in ambient concentrations from the baseline conditions.
Minor	Ambient concentrations differ from the baseline conditions to a small degree, but are within the range of natural variation and well below a guideline or threshold value.
Moderate	Ambient concentrations differ from the baseline conditions and approach the limits of natural variation, but are below or equal to a guideline or threshold value.
Major	Ambient concentrations differ from baseline conditions beyond the range of natural variation, resulting in a measurable change beyond a guideline or threshold value..
Catastrophic	Ambient concentrations differ substantially from the baseline conditions beyond the range of natural variation, resulting in a measurable change that goes well beyond a guideline or threshold value.

Air Quality

CACs are the primary pollutants from combustion engines. They include NO_x, SO₂, CO, and particulates, which include both visible (smoke) and non-visible emissions. NO_x formation relates directly to high pressures and temperatures during the combustion process, while sulphur compound formation—mainly in the form of SO₂—relates to the sulphur content of fuel.

Other pollutants, such as CO and smoke, are primarily the result of incomplete combustion in engines. Regarding particulate matter, PM₁₀ and PM_{2.5} are considered, in particular PM_{2.5}, which has been identified as a potential health risk in BC due to its small size, potential lung penetration ability and association with cancer and respiratory health issues (potential effects on human health are discussed in Section 5.8).

Potential risks to air quality associated with traffic accidents are the same, whether the accident results in the vehicle remaining on the road or travels off-road. Small traffic accidents, which do not involve fires or spills, do not have any potential risks to air quality. On the other hand, larger accidents that result in fires or spills may contribute to effects on air quality, with the effects varying with the severity of an accident. The type, likelihood, and severity of effects are defined in Table 5.7-8.

It is assumed that the potential risk of accidents involving vehicles with non-hazardous cargo (i.e., personnel and supplies) is limited to regular vehicle fuel tanks, and is therefore considered a negligible risk to air quality. Traffic accidents will contribute to effects on air quality only if the accident is large and/or vehicles are carrying hazardous cargo which may be lead to a major chemical spill or fire.

Climate

During operation, any kind of vehicle that emits GHGs has potential to interact with the Climate VC. GHGs from engine fossil fuel combustion include primarily CO₂, as well as N₂O and methane (CH₄). GHGs are measured and reported in carbon dioxide equivalents, CO₂e. These GHGs contribute to the greenhouse gas effect; as their atmospheric concentration levels increase, climate changes. Therefore, GHG emissions from Project vehicles have the potential to contribute to climate change (see Table 5.7-7). Estimated Project-related GHGs will be characterized qualitatively and compared to annual industrial and provincial totals in the Project's Application/EIS.

The contribution of GHG emissions as a result of traffic accidents depends on the accident type; therefore, traffic accidents have also been identified as a potential risk for climate. As described above for air quality, there is no difference between “on-road” and “off-road” accidents, and it is assumed that the potential risks of accidents involving vehicles with non-hazardous cargo are considered negligible. Table 5.7-8 describes the potential risks to climate associated traffic accidents.

Risk Mitigation

Since the risks of the Project's contribution to climate change, and potential contribution to a reduction in ambient air quality, arise from the air emissions associated with fuel combustion, mitigation measures will focus on vehicle fuel efficiency, fuel type and fuel consumption.

Air emissions cannot be eliminated from Project traffic activities, since most vehicles will likely have to use fossil-fuel-based engines. However, in addition to the expected emission reductions from technology improvements over the Project lifespan, emissions will be minimized using the following mitigation measures:

- switching fuel to more efficient blends to reduce GHGs;
- optimizing the vehicle load rates to minimize the number of trips;

- following procedures and schedules provided by the vehicle manufacturers to increase fuel efficiency;
- having fleets with newer engines;
- minimizing idling; and
- ensuring diesel vehicles use low sulphur content fuel as required by law.

Many of the above emission reducing measures will lead to fuel conservation and a reduction in GHGs, and ultimately result in cost savings for the Project. Fuel standards, regulations and best practices to mitigate tail pipe emissions from the transport sector are likely to evolve during the Project lifetime. For instance, the BC Climate Action Plan seeks to achieve targets such as overall provincial GHG reductions of 33% by 2020 compared to 2007 levels (BC Government 2008), and there are new national GHG emission regulations for the transport sector under the provisions of the *Canadian Environmental Protection Act* (1999) that are slated to come into effect in 2014. Aside from promoting the voluntary mitigation measures such as the ones listed above, the Project proponent will ensure that traffic emissions will comply with new legislation and codes of practice as they are introduced.

Risk Characterization

Air Quality

Even after mitigation, Project traffic will contribute to emissions of CACs regularly during the Project. The maximum contribution of emissions is expected to occur during the operation phase and along the northern segment of Highway 37, where the maximum traffic volume increase is expected.

A detailed quantification of potential Project effects on air quality requires computer modelling that considers vehicle and engine types, fuel types and consumption, etc. This type of assessment will be included in the Application/EIS. However, vehicle emissions along roads can be roughly correlated to traffic volumes. Given baseline levels of CACs and the level of expected traffic increase, CACs contribution to ambient air quality is expected to remain well below BC air quality objectives and standards. Background concentrations of CACs were approximately ten times below the maximum desirable concentrations for all CACs. The annual average background concentration of SO₂ was estimated at 2.0 µg/m³, while the 2009 Air Quality Objectives and Standards for British Columbia and Canada state the desirable maximum annual arithmetic mean for sulphur dioxide is 30 µg/m³ (Government of BC 2009b). Background annual average concentration of NO₂ was estimated at 5.0 µg/m³, while BC air quality objectives state that 60.0 µg/m³ the desirable maximum annual arithmetic mean. While the likelihood of emissions from Project operation is certain, the severity of the effect is considered to be minor. For Project-related vehicle accidents, the likelihood is considered rare and the severity is negligible to minor depending on the type of cargo (Table 5.7-7). Traffic accidents that do not involve fires or large spills will not contribute to effects on air quality. Predicted increases in total traffic accidents as a result of the Project are expected to be very low, as outlined in Section 2.5, and the probability of an accident resulting in a spill or fire is even lower. Accordingly, the likelihood of traffic accidents resulting in a situation that affects ambient air quality is rare and severity is negligible to minor depending on the cargo being transported (Table 5.7-8).

Climate

Project traffic emissions from combustion engines will contribute to GHG emissions. Levels of GHGs resulting from the Project will vary from phase to phase as traffic volumes change. When comparing historical traffic volumes in the Study Area and the estimated Project traffic, the contribution of the Project will be minor in terms of climate (see Section 2.3).

Table 5.7-7. Climate and Air Quality Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Climate	Personnel	Increase in GHG emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other sources of GHG emissions	Rare	Negligible	Contribution to climate change risk
	Materials, equipment, and supplies	Increase in GHG emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other sources of GHG emissions	Rare	Negligible	Contribution to climate change risk
	Diesel fuel and lubricants	Increase in GHG emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other sources of GHG emissions	Rare	Minor	Contribution to climate change risk
	Concentrates	Increase in GHG emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other sources of GHG emissions	Rare	Negligible	Contribution to climate change risk
	Lime and reagents	Increase in GHG emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other sources of GHG emissions	Rare	Minor	Contribution to climate change risk
	Explosives	Increase in GHG emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other sources of GHG emissions	Rare	Minor	Contribution to climate change risk
Air Quality	Personnel	Increase in air contaminant emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other potential vapourization from spills	Rare	Negligible	Contribution to air contaminant emissions and reduction of ambient air quality
	Materials, equipment, and supplies	Increase in air contaminant emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other potential vapourization from spills	Rare	Negligible	Contribution to air contaminant emissions and reduction of ambient air quality
	Diesel fuel and lubricants	Increase in air contaminant emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other potential vapourization from spills	Rare	Minor	Contribution to air contaminant emissions and reduction of ambient air quality
	Concentrates	Increase in air contaminant emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other potential vapourization from spills	Rare	Negligible	Contribution to air contaminant emissions and reduction of ambient air quality
	Lime and reagents	Increase in air contaminant emissions from fuel combustion	All phases	Take preventive measures to reduce risk of fire. In the event of an accident, follow emergency response procedures to mitigate fires and other potential vapourization from spills	Rare	Minor	Contribution to air contaminant emissions and reduction of ambient air quality
	Explosives	Increase in air contaminant emissions from fuel combustion	All phases	Stay up to date for all regulatory acts used to transport explosives. Vehicles outlined in the act must have explosives vehicle certificate	Rare	Minor	Contribution to air contaminant emissions and reduction of ambient air quality

Table 5.7-8. Climate and Air Quality Risk Assessment Matrix for Project Traffic

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Climate	All traffic types	Increase in GHG emissions from fuel combustion	All phases	Use well maintained vehicles to optimize combustion; use hybrid or electric vehicles.	Certain	Minor	Contribution to climate change risk
Air Quality	All traffic types	Increase in air contaminant emissions from fuel combustion	All phases	Use well maintained vehicles to optimize combustion; use low sulphur content fuel for diesel vehicles or use biodiesel; use hybrid or electric vehicles.	Certain	Minor	Contribution to air contaminant emissions and reduction of ambient air quality

Similar to air quality, traffic accidents that do not involve fire or large spills will not contribute to effects on climate, as these will not involve combustion related emissions to the atmosphere. In the event of large accidents, such as fuel truck fires, air emissions will be released immediately. Since the duration of such incidents would be short and the frequency rare, the possibility of incremental effects to identified VCs is low.

Mitigation measures previously described will reduce the risks to climate from Project traffic, but the risks cannot be eliminated fully as Project vehicles will likely be dependent on fossil fuel combustion. Nevertheless, overall effects to climate are classified as minor for Project activities and minor or negligible for traffic accidents (Tables 5.7-7 and 5.7-8).

5.8 HUMAN HEALTH

5.8.1 Baseline Data Overview

This section assesses the human health risks due to Project traffic and traffic accidents. Potential risks to country foods, drinking water, air quality, and human safety are considered.

The human health traffic effects assessment considers the communities and settlements in the traffic Study Area (Figure 5.1-1). The settlements include Bob Quinn Lake (just north of the Eskay Creek Mine access road junction), Bell II, Meziadin Junction, and the villages of Gitanyow and Kitwanga. A 500 m buffer on either side of the highways was included to encompass any land use activities, such as trap lines and other economic activities that could potentially be affected by Project traffic on the transport routes.

Aboriginal people are the predominant residents of most of the smaller communities near the Study Area, including the Tahltan Nation communities of Iskut and Telegraph Creek. Other Aboriginal groups include the Nisga'a Nation, Skii km Lax Ha, Gitanyow First Nation, and Gitxsan Nation. Aboriginal groups in the region practice subsistence activities such as fishing, hunting, trapping, and gathering, which are important to maintaining culture. A more detailed description of subsistence activities can be found in the *KSM Project: 2012 Economic Baseline Report* (Rescan 2012a).

Bob Quinn Lake and Bell II are generally classified as tourist destinations and facilities, and are significantly smaller than the other communities in the region. Most businesses are based on seasonal outdoor activities including fishing, hunting, hiking, backcountry skiing, heli-skiing and snowmobiling. Tourism activities focus on wilderness opportunities and draw tourists from around the world.

Project traffic will travel through three major watersheds: the Nass River, Skeena River, and North Coast rivers watersheds. The Nass South SRMP Socio-economic Assessment (Pierce Lefebvre Consulting 2008) provides a detailed assessment of country foods harvests by native and non-native residents and tourists in the SRMP area. The Nass South SRMP overlaps the Study Area and therefore provides a reasonable estimate of land use and especially country food use for this study.

Section 5.2 describes the details of the fish and water resources within the Study Area. Commercial fishing is very important to communities surrounding the Nass South SRMP area, especially to Aboriginal groups. The Skeena Native Development Society reports that in 2006, the commercial fishing sector generated employment for 65 people residing in the Nisga'a villages and eight people residing in the Gitanyow/Gitxsan villages (SND 2006). The Nass Watershed supports the provincially significant Nass salmon fishery. Meziadin Lake and its major tributaries- Hanna, Tintina and Surprise creeks- account for up to 80% of the total Nass sockeye assessment (DFO 2004). Meziadin Lake is also the main sport-fishing lake in the Nass South SRMP area. It features a number of popular sport fishing species including salmon, whitefish, Dolly Varden, kokanee, rainbow trout, bull trout and steelhead (Pierce Lefebvre Consulting 2008).

The Study Area traverses valuable moose and bear habitat, and Highway 37A’s location at elevations below suitable mountain goat habitat provides access to hunters (Section 5.3; Pierce Lefebvre Consulting 2008). Guided hunting by tourists and hunting by Aboriginal groups and BC residents are important components of the local economy.

Non-timber forest products, especially the harvest of wild pine mushrooms is common in the area (Pierce Lefebvre Consulting 2008). The largest northwestern BC pine mushroom harvesting sites are in the Nass River Valley (Kalum District), which includes mushroom harvesting on Nisga’a Lands as well as in the Nass South SRMP area, and the Hazeltons-Kispiox Valley (Kispiox District). Since the NFA was implemented, pine mushroom harvesting on Nisga’a Lands has been monitored through the sale of permits to Nisga’a and non-Nisga’a pine mushroom harvesters. In 2008, the Nisga’a harvested 11,656 kg of mushrooms, which generated over \$43,000 in revenue (NLG 2009).

Based on the land uses described above, this report focuses on human health risks to Aboriginal groups, local residents, guide outfitters, anglers, trappers, and recreational land users (e.g., campers, fishers, hunters) as these are the people likely living and travelling along highways 37 and 37A.

5.8.2 Issue Scoping

5.8.2.1 Human Health Scoping

Potential risks to human health are associated with Project traffic and Project-related traffic accidents (Table 5.8-1)

Table 5.8-1. Human Health Scoping Matrix

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
<i>Project traffic</i>		
All traffic	Yes	Project traffic may decrease air quality and increase noise potentially causing human health effects.
<i>Traffic accidents</i>		
<u>Personnel and non-hazardous cargo</u>		
All non-hazardous	Yes	Traffic accidents involving vehicles carrying non-hazardous cargo could result in a spill from the vehicle’s fuel tank into aquatic and terrestrial environments.
<u>Hazardous cargo</u>		
Diesel fuel and lubricants	Yes	Traffic accidents resulting in diesel spills pose a risk to human health from inhalation of volatiles and ignition/explosion. Combustion particulates are probably carcinogenic to humans (IARC 1998) if exceeding certain limits. Hydrocarbons may bioaccumulate in fish that people consume. Diesel spills could contaminate drinking water.
Concentrates	Yes	Concentrate spills pose risk to human health if not handled properly. Direct human health risks develop when fires from accidents produce dangerous sulphur dioxide fumes; indirect risks develop when metals leach from concentrate and accumulate in aquatic habitat and fish consumed by people. Metals may bioaccumulate in plants if concentrate remains in the terrestrial environment.

(continued)

Table 5.8-1. Human Health Scoping Matrix (completed)

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
Lime and reagents	Yes	Spills of lime and reagents are hazardous to human health if not handled properly and can cause problems if in contact with eyes, skin, or inhaled. Spills in aquatic habitat could affect fish.
Explosives	Yes	Spills of ammonium nitrate pose risks to human health if not handled properly. These spills are hazardous in the case of skin or eye contact, ingestion, or inhalation, and slightly hazardous in the case of skin contact as a permeator. Thermal decomposition produces toxic fumes of nitrogen oxides such as: NO, NO ₂ , N ₂ O, N ₂ O ₃ , etc. This material may explode, and is toxic to aquatic life.

Project traffic may decrease air quality and increase noise potentially causing human health effects. Project traffic is not expected to generate dust because highways 37 and 37A are paved and concentrate will be trucked in covered containers. Human health effects are therefore unlikely to occur as a result of ingestion of berries, mushrooms and medicinal plants from the Study Area or from the ingestion of animals foraging on plants in the Study Area. This risk is not considered further.

On-road and off-road traffic accidents resulting in the discharge of hazardous materials into the receiving environment could potentially affect human health. Traffic accidents involving spillage and/or ignition of hazardous materials could affect human health if not handled properly by trained professionals according to emergency response protocols. People may be exposed to hazardous materials or combustion fumes through accidental skin contact, inhalation or ingestion. If not contained and remediated, diesel spills could enter surface water or groundwater used as drinking water sources by communities. For traffic accidents to affect human health via consumption of fish, the accident must occur at a stream crossing or where the highway runs in close proximity to a fish-bearing watercourse used for recreational or subsistence fishing. Off-road spills of hazardous materials into the terrestrial environment may affect human health via the ingestion of berries, mushrooms, and medicinal plants, or via the consumption of the animals that forage on these plants and may bioaccumulate contaminants of concern.

5.8.2.2 Valued Component Scoping

The selected human health VCs and the rationales for their inclusion or exclusion in the assessment are presented in Table 5.8-2. The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise). The VCs include country foods (plants such as berries, medicinal plants, mushrooms; fish; birds such as grouse; and mammals such as hare, moose, deer and bear), noise, air quality, drinking water quality, and human safety. The VCs are relevant to the health of workers (personnel and truck drivers, emergency response teams), and members of the communities of Bell II, Meziadin Junction, Cranberry Junction, Gitanyow and Kitwanga. Country foods are consumed by community members as well as sports fishermen and hunters from outside the local communities. The quality of animal foods (such as moose and fish) can be indirectly affected through bioaccumulation of contaminants in the food chain.

5.8.2.3 Potential Traffic/Valued Component Interactions

The potential interactions between Project traffic along proposed haul routes and the identified VCs are identified in Table 5.8-3. Where there is potential for an interaction between a traffic type and a VC, the potential is identified with an "X". Only traffic types that have been identified to potentially affect one or more VCs will be included in the Risk Analysis (Section 5.8.3).

Table 5.8-2. Identification and Rationale for Human Health Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	Project Traffic?	Traffic Accidents?	
Country foods	X	X	X	X	No	Yes	Project traffic will not affect country foods. Traffic accidents may affect plants, fish, birds, and mammals in the Study Area during all Project phases of the Project’s life span. Moose, bear, deer and small mammals are identified as culturally important and hunted species for the Nisga’a Nation, Skii km Lax Ha, Tahltan, Gitxsan and Gitanyow. Moose, bear, deer, and small mammals are economically important species to local hunters and guide outfitters.
Noise	X	X	X	X	Yes	No	An increase in truck traffic may result in an increase in noise from engines and friction affecting health of local residents.
Air quality	X	X	X	X	Yes	Yes	An increase in truck traffic may lead to an increase in ambient air quality concentrations of CACs such as carbon monoxide (CO), sulphur dioxide (SO ₂), nitrogen dioxides (NO ₂), and particulate matter, harmful to human health of local residents. Traffic accidents resulting in vehicle fires may release toxic fumes from diesel, reagents, and concentrate harmful to human health.
Drinking water quality	X	X	X	X	No	Yes	In the event of an accident, large diesel spills could enter surface water or ground water used as drinking water resource by downstream communities if not contained and remediated.
Human safety	X	X	X	X	No	Yes	Traffic accidents may physically impact the driver, personnel, or other highway users.

¹ “X” indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or O = Other) has identified the VC as an issue; “-” indicates that the group did not identify the VC as an issue.

² “Yes” indicates that the VC is selected for further analysis; “No” indicates that the VC is excluded from further analysis.

Table 5.8-3. Potential Traffic / Valued Component Interaction Matrix – Human Health

Traffic Type	VCs						
	Country Foods (plants)	Country Foods (fish)	Country Foods (birds, large and small mammals)	Noise	Air Quality	Drinking Water	Human Safety
<i>Project traffic</i>							
All traffic	-	-	-	X	X	-	-
<i>Traffic accidents: on-road</i>							
All traffic	-	-	-	-	X	-	X
<i>Traffic accidents: off-road</i>							
All non-hazardous cargo	X	X	-	-	X	-	X
<u>Hazardous cargo</u>							
Diesel fuel and lubricants	X	X	X	-	X	X	X
Concentrates	X	X	X	-	X	X	X
Lime and reagents	X	X	X	-	X	X	X
Explosives	-	X	-	-	X	X	X

“X” indicates that a potential interaction has been identified.

“-” indicates that no potential interaction was identified.

5.8.3 Risk Analysis

The effects assessment addresses potential human health issues and risks associated with Project traffic along highways 37 and 37A. It is based on an assessment of VCs identified in Table 5.8-2, and focused on selected plant and wildlife species. Interactions identified in Table 5.8-3 are analysed and assigned a risk severity according to the definitions in Table 5.8-4. The traffic types, their potential risks, mitigation measures and severity are shown in Table 5.8-5 and Table 5.8-6. A more detailed description of the risks and mitigation measures can be found in the sections following.

Table 5.8-4. Human Health Risk Assessment Severity Scale Descriptors

Descriptor	Definitions			
	Country Foods and Drinking Water	Noise	Air Quality	Safety
Negligible	No human health effect from consumption of country foods/water	Noise not perceived as elevated above background	No detectable change from baseline conditions. Effect limited to a few individuals.	No harm
Minor	Minor risk of acute toxic effects due to low probability that food/water is contaminated and low consumption rates of food	Noise level elevated, but not disruptive to normal sleep patterns and not interfering with normal conversation	Differs from the average value for baseline conditions to a small degree (e.g., within the range of natural variation and well below a guideline or threshold value. Effect limited to a few individuals up to the local population.	Minor injuries not requiring hospitalization
Moderate	Moderate risk of acute toxic effects due to low probability that food/water is contaminated but higher consumption rates of food	Noise level elevated, but not disruptive to normal sleep patterns during night-time, but interfering with normal conversation during day time	Differs substantially from the average value for baseline conditions and approaches the limits of natural variation, but below or equal to a guideline or threshold value. Effect limited to the local population.	Moderate injuries requiring hospitalization
Major	Major risk of acute toxic effects due to high probability that food/water is contaminated and frequent consumption	Noise level elevated and at frequency that disrupts normal sleep patterns and interferes with normal conversation	Differs substantially from baseline conditions beyond a guideline or threshold value, resulting in a detectable change beyond the range of natural variation. Effect limited to the local population.	Critical injuries requiring hospitalization
Catastrophic	Severe acute and chronic toxic effects from consumption of country foods and water	Temporary and permanent loss of hearing	Differs substantially from baseline conditions beyond a guideline or threshold value, resulting in a detectable change beyond the range of natural variation. Effect extends beyond the local population.	Mortality

5.8.3.1 Country Foods

Risk Identification

Country foods are animals, plants, and fungi used by humans for nutritional and medicinal purposes that are harvested in the wild. The quality of country foods is directly related to the quality of the surrounding environmental media (e.g., soil, water and vegetation).

Hunting and fishing are important components of the local subsistence and tourism economies. The traditional subsistence economy is still strongly evident, and traditional hunting camps are also

widely pursued (Rescan 2012a). Bell II Lodge serves as a base for sports fishing on the Bell-Irving and Upper Nass Rivers (Bell 2 Lodge 2012), while the Tatogga Lake Resort advertises fly-in hunting and fishing (Tatogga Lake Resort 2012).

Contamination of country foods is not predicted to occur during normal Project traffic, but may result from traffic accidents in the event that hazardous materials are spilled into the terrestrial or aquatic environment. Although country foods harvesting data are largely unavailable for the Study Area, it is assumed that the highway is used to access and collect plant foods (berries, mushrooms, medicinal plants) by Nisga'a Nation, First Nations and local residents. Animals such as moose, deer, bear, and some bird species, which are consumed as country foods, will forage at least part of the time in the Study Area and may thus be affected if contaminants are released into the environment. Fish may be affected if contaminants are allowed to enter the aquatic environment.

Petroleum hydrocarbons from diesel and lubricants are very complex mixtures and may enter the aquatic and terrestrial environments during an off-road accident. Most petroleum hydrocarbon constituents present adverse effects through human and environmental toxicity. Lighter hydrocarbons are mobile and migrate considerable distances from their point of release and may enter groundwater resources. Larger and branched-chain hydrocarbons are persistent in the environment. Petroleum hydrocarbons may create problems such as offensive odour, taste or appearance of water and fish. Some fractions of petroleum hydrocarbons may bioaccumulate in aquatic organisms.

Concentrate may spill off-road into the terrestrial and aquatic environment during traffic accidents involving concentrate haul trucks. The toxicological properties of concentrates have not been fully investigated (see Table 2.4-5 in Section 2.4.5 for an analysis of KSM copper concentrate toxicity). The Toxicity Characterization Leaching Procedure -EPA 1311 test was performed by ALS Environmental assess whether metals can leach in the longer term from the copper concentrate after off-road spillage into the aquatic environment under worst case scenario conditions (acidic, aerobic). This test is used in screening level risk assessments for BC contaminated sites. The metal concentrations in the resulting extract were compared to Canadian (CCME) and BC water quality guidelines for the protection of aquatic life to detect exceedances. Leachable antimony, arsenic, cadmium, chromium, copper, iron, lead, mercury, nickel, selenium, silver, thallium, vanadium, and zinc concentrations exceeded either the CCME or the BC water quality guidelines, or both. However, environmental conditions of receiving waters are far less acidic than the leach test conditions and the concentrate itself is alkaline. As a result, in the event of a concentrate spill metals will leach into receiving waters at much lower rates and concentrations and will be diluted (the EPA1311 test does not take dilution into account). Direct comparison to CCME Sediment and Soil Quality Guidelines is not possible, since the mass of sediment and/or soil that would be affected by metal-rich leachate from a concentrate spill has not been determined. Spillage into the terrestrial environment is expected to have minimal effects due to implementation of risk mitigation measures and negligible exposure of plants and animals to metals in the concentrate.

Lime and reagents may spill off-road into the terrestrial and aquatic environment during traffic accidents. The effect of reagents on human health through the consumption of country foods depends on the nature of the reagents. Lime will increase the pH in the environment, damage plant tissues and may thereby be harmful to ecological health. Cyanide is acutely toxic to fish and wildlife, but degrades quickly in the environment and does not bioaccumulate or biomagnify in the food chain. Plants and berries may be affected, and collection of plants from an area affected by a spill would have to be avoided in the short term. There is no toxicological health effect to humans through consumption of country foods that have bioaccumulated lime or cyanide, but the amount of fish and plants harvested may be affected negatively. Potential effects of chemical hazards are described in greater detail in Section 6.4.4, Table 6.4-5.

Table 5.8-5. Human Health Risk Assessment Matrix for Project Traffic

VCs	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Traffic Noise	All traffic types	Increase in noise levels due to an increase in project-related traffic, especially from heavy trucks.	All phases	Source mitigation: Enforced speed limits; avoid use of engine brakes and reversing; vehicle maintenance; Receptor mitigation: barriers (e.g., vegetation, berms)	Certain	Minor	Small increase in percentage of highly annoyed receptors
Air Quality	All traffic types	Low ambient air quality because of air emissions to the atmosphere with minor risks to human health	All phases	Enforce speed limits; use well maintained vehicles to optimize combustion, using low sulphur fuel	Certain	Minor	Increase in local ambient air quality concentrations with minor health risks.

Table 5.8-6. Human Health Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Country foods - Plants	Diesel fuel and lubricants	Fuel or lubricant spill into terrestrial environment may result in inhibition of plant germination and growth. Plants may take up hydrocarbons and bioaccumulate, metabolize or volatilize HCs thus introducing them into the food chain.	All phases	Use of best management practices to minimize spill entry to the terrestrial environment; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Moderate	Localized, moderate effects on consumption of plant species. Refrain from collection of plants from spill area and test plants before resuming collection.
Country foods - Plants	Concentrates	Metals from spilled concentrate may be taken up by plants and subsequently ingested by human harvesters.	Operations	Use of best management practices to minimize spill entry to the terrestrial environment; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Minor	Localized, short-term, minor effects on consumption of plant species. Refrain from collection of plants from spill area and test plants before resuming collection.
Country foods - Plants	Lime and reagents	Lime and reagent spills into terrestrial environments result in changes in pH and may result in inhibition of plant germination and growth.	All phases	Use of best management practices to minimize spill entry to the terrestrial environment; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Negligible	Localized, short-term, minor effects on consumption of plant species. Refrain from collection of plants from spill area and mitigate recovery.
Country foods - Fish	Diesel fuel and lubricants	Fuel or lubricant spill into waterbody may cause localized or far-reaching effects. Petroleum products are toxic to fish species. Hydrocarbons may bioaccumulate in the food chain.	All phases	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup	Unlikely	Moderate	Localized, short-term, moderate effects on consumption of fish species. Tainting of fish at small concentrations of hydrocarbons possible. Fish should be tested for potential contamination.
Country foods - Fish	Concentrates	Metal concentrate spill into waterbody may be toxic at the point source and exceed water quality guidelines at a distance; smothering of eggs and fish. Some metals may bioaccumulate in the food chain.	Operations	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup; Low moisture concentrate.	Unlikely	Moderate	Moderate effects confined to local area and on a short-term basis, rapid clean-up of concentrates required. Fish should be tested for potential metal contamination.
Country foods - birds, small and large mammals	Diesel fuel and lubricants	Exposure of animals may result from direct contact with spill or from ingesting contaminated plant material via the food chain. Meat for human consumption may become tainted.	All phases	Use of best management practices to minimize spill entry to the terrestrial environment; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup will minimize if not eliminate effects on wildlife and hence human consumption. Large mammals (moose, deer, bear) will be excluded from the spill site if cleanup cannot occur immediately.	Rare	Minor	Minor effect on human consumption of wildlife.
Country foods - birds, small and large mammals	Concentrates	Metals from spilled concentrate may be taken up by plants and subsequently ingested by wildlife. Metals may bioaccumulate in wildlife meat used for human consumption.	Operations	Use of best management practices to minimize spill entry to the terrestrial environment; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup will minimize if not eliminate effects on wildlife. Large mammals (moose, deer, bear) will be excluded from the spill site if cleanup cannot occur immediately.	Rare	Minor	Minor effect on human consumption of wildlife.

(continued)

Table 5.8-6. Human Health Risk Assessment Matrix for Traffic Accidents (completed)

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Country foods - birds, small and large mammals	Lime and reagents	Chemical hazard to wildlife from changes in pH. No bioaccumulation potential.	All phases	Use of best management practices to minimize spill entry to the terrestrial environment; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup will minimize if not eliminate effects on wildlife. Large mammals (moose, bear) will be excluded from the spill site if cleanup cannot occur immediately.	Rare	Negligible	Negligible effect on human consumption of wildlife
Air Quality	All non-hazardous cargo	Poor ambient air quality because of air emissions to the atmosphere, harmful fuel fires emissions	All phases	Initiate emergency response procedure to minimize fire duration (if exists) and spill response procedure to contain the spill therefore minimize vaporization	Rare	Negligible	Increasing local ambient air quality concentrations with negligible risk to human health
Air Quality	All hazardous cargo	Poor ambient air quality because of air emissions to the atmosphere, harmful fuel fire emissions	All phases	Initiate emergency response procedure to minimize fire duration (if exists) and spill response procedure to contain the spill therefore minimize vaporization	Rare	Minor	Increasing local ambient air quality concentrations with overall minor risk to human health
Air Quality	Diesel fuel and lubricants	Poor ambient air quality because of air emissions to the atmosphere, large and harmful diesel fuel fire emissions	All phases	Initiate emergency response procedure to minimize fire duration (if exists) and spill response procedure to contain the spill therefore minimize vaporization	Rare	Moderate	Increasing local ambient air quality concentrations with minor risk to human health. Moderate human health risks realized by emergency response teams during diesel spill clean-up and fire response.
Drinking Water Quality	Diesel fuel and lubricants	Fuel or lubricant spill into surface water used for drinking or into the terrestrial environment located above an aquifer used for drinking water may cause localized or far-reaching effects of hydrocarbon contamination of drinking water resources.	All phases	Use of best management practices to minimize spill entry to the terrestrial environment and water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup.	Unlikely	Moderate	Localized, short-term, moderate effects on drinking water. Water should be tested for potential contamination.
Drinking Water Quality	Concentrates	Metal concentrate spill into waterbody may be toxic at the point source and exceed water quality guidelines at a distance. Spills may interfere with the beneficial use of surface water as drinking water.	Operations	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup; Low moisture concentrate.	Unlikely	Unknown*	Moderate effects confined to local area and on a short-term basis, rapid clean-up of concentrates required. Water should be tested for potential metal contamination before consumption.
Drinking Water Quality	Lime and reagents	Should lime and reagents spill into surface water, the resulting change in pH and water chemistry may affect drinking water quality.	All phases	Use of best management practices to minimize spill entry to water bodies; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment, neutralization and cleanup.	Unlikely	Minor	Minor, short-term and localized effects on drinking water quality. Rapid clean-up required. Water should be tested before consumption.
Drinking Water Quality	Explosives	Ammonium nitrate spills into waterbodies or onto terrestrial environments may lead to nitrate contamination of surface water or ground water resources used for drinking. Small babies are susceptible to poisoning.	Operations	Use of best management practices to minimize spill entry to water bodies and terrestrial environments; Enforced speed limits and traffic safety; Adhere to the Spill Prevention and Emergency Response Plan; Prompt containment and cleanup.	Unlikely	Moderate	Minor, short-term and localized effects on drinking water quality. Rapid clean-up required. Water should be tested before consumption.
Traffic Victims	All traffic types	Accidents of varying severity leading to injury and death of drivers, personnel, and other highway users	All phases	Enforce speed limits and other traffic rules; Company zero-tolerance policy on alcohol; Adhere to accident first aid, emergency response and other procedures; Highway maintenance	Possible	Catastrophic	Accidents are rare, but may affect human health to a large degree, including death

*See Section 5.8.3.4 for rationale for this rating.

Explosives are transported as ammonium nitrate and may spill off-road into the terrestrial and aquatic environment during traffic accidents. There are no direct toxicological effects on human health through the consumption of country foods expected from the spillage of ammonium nitrate into the terrestrial or aquatic environment, but the amount of fish harvested may be affected negatively, due to the toxicity of ammonium nitrate to aquatic life.

Risk Mitigation

Prevention of traffic accidents resulting in spills is the best way to reduce the risk of hazardous materials entering the environment. Correct transport procedures for dangerous goods and hazardous materials, following the Dangerous Goods and Hazardous Materials Management Plan, will assist in ensuring that spills do not occur. Drivers will be TDG, WHMIS (Workplace Hazardous Materials Information System) and CPPI (Canadian Petroleum Products Institute) certified as required.

Enforcement of speed limits and traffic safety rules, regular vehicle inspections, a scheduled maintenance program, and operation of vehicles that meet or exceed Transport Canada's minimum requirements (Transport Canada n.d.) will also prevent traffic accidents resulting in spills.

In the event of an accident, communication devices (VHF radio, satellite phone) and emergency contacts will be readily accessible to drivers. As part of the Emergency Response Plan, procedures for emergency response and occupational first aid will be developed, and workers and contractors will undergo required training. In the unlikely event of a fire, emergency response procedures to minimize fire duration and extent will be initiated promptly.

The Spill Prevention and Emergency Response Plan will be developed and implemented to limit effects on country foods and human health. The Spill Prevention and Emergency Response Plan, for example, will limit the infiltration of leachate from spilled concentrate into the soil environment. In the event of a spill into the aquatic environment, metal concentrations would be monitored in the sediment and water. Exceedance of guidelines will be included in human health and ecological risk assessments, if required.

Risk Characterization

The characterization of risk of off-road spillage is based on traffic accident data from 1996 to 2011 (ICBC 2011a, 2011b), as described in Chapter 2.

The risk to water quality or fish is lower than the risk to plants or animals foraging on affected plants. The severity of the risk of spills into the terrestrial environment is mitigated by the assumption that spills can be contained and cleaned up quickly and effectively and that long-term contamination of plants is therefore unlikely. Spillage into the aquatic environment is unlikely, but the severity of residual risks will depend on effective containment and clean-up.

5.8.3.2 *Noise*

Risk Identification

Noise has the potential to induce adverse human health effects. There is a potential for frequent night-time traffic to produce sleep disturbance, and the increase in daytime traffic noise may be perceived as an annoyance.

Highway traffic due to Project activities will occur 24 hours a day, although some suppliers may prefer daytime deliveries. It is assumed for the assessment of human health effects from traffic noise that

traffic predominantly occurs during the day (7 a.m. to 10 p.m.), but that 25-30% of traffic will occur between 10 p.m. and 7 a.m.

The percent highly annoyed (% HA) endpoint is recommended by Health Canada to assess potential human health effects from an increase in noise. High annoyance (HA), which can be measured in community surveys or modelled, is an indicator of CWB. An increase in % HA of 6.5% is deemed acceptable (Health Canada 2011). Table 5.8-7 provides a summary of sound levels and calculated impact from Project traffic following Health Canada guidance on calculating the change in % HA.

Table 5.8-7. Predicted and Adjusted Sound Levels for Baseline and Project Traffic Noise and Calculated Impact from Project Traffic on Percentage Change in High Annoyance

	Adjusted Baseline L_{eq}^1 (dBA) ² for 24 Hour Average	Adjusted Baseline L_{dn}^3 (dBA)	% HA Baseline	Adjusted Project L_{eq}^1 (dBA) ² for 24 Hour Average	Adjusted Project L_{dn}^3 (dBA)	% HA Operation	% HA Project - % HA Baseline	Exceeds 6.5% Increase in % HA (Y/N)
<i>Northern Section</i>								
AADT	47	59.7	7.4	50	60.5	8.2	0.8	N
SADT	49	61.7	9.5	52	62.5	10.5	1.0	N
<i>Southern Section</i>								
AADT	58	70.7	25.6	59	70.9	26.2	0.6	N
SADT	59	71.7	28.2	60	72	28.8	0.6	N

¹ L_{eq} Equivalent continuous sounds level

² dBA A-weighted decibels, A-weighting refers to weighting of the frequencies in a sound that approximates the response of the human ear to frequencies in moderately loud sounds (sound pressure levels in the range of 45 to 65 dBA).

³ L_{dn} Day-night sound level

Baseline daytime noise levels are assumed to be equivalent to night-time noise levels. It was further assumed that the night-time Project noise level would be similar to the night-time baseline noise level, because Project traffic is expected during night-time hours. Because noise predictions were made based on traffic during the operation phase, the predicted changes in % HA is a conservative, worst case estimate. The resulting change in % HA was less than or equal to 1% for AADT and SADT for both the northern and southern sections. The lower number for SADT accounts for the fact that the SADT baseline noise levels are generally higher than the estimated AADT baseline noise level. The predicted change in % HA is below the recommended maximum of 6.5% for AADT and SADT.

For individual noise events during the night, the WHO guideline (1999) recommends that indoor sound pressure levels should not exceed 45 dBA more than 10 to 15 times per night. Health Canada (2011) draft guidance states that an increase in the percentage of awakenings is not expected to occur at indoor sound exposure levels of 55 to 60 dBA with house windows either partially or fully closed during the night.

Risk Mitigation

Risk mitigation for traffic noise can include measures at the source as well as measures at the receptor. Source risk mitigation will include: reducing speeds to 50 km/h in residential areas; avoiding the use of engine brakes in residential areas; adhering to a truck maintenance program; and avoiding reversing (use of reverse-alarm) in residential areas. Mitigation on the part of the receptor is beyond the scope of Seabridge to address.

Risk Characterization

Human health risks due to the minor predicted increase in traffic noise are expected to be negligible in the context of daytime activities and normal sleep patterns.

5.8.3.3 *Air Quality*

Risk Identification

Air contaminants are an important factor to consider for human health in this study. Air emissions due to normal Project traffic during all phases of the proposed Project's operating life may lead to an increase in ambient air quality concentrations of CACs such as CO, SO₂, NO₂, and suspended particulate matters (Section 5.7). In addition, traffic accidents leading to fires of hydrocarbon fuel and other materials may release gases and particulates harmful to human health in the short-term.

Concentrates are unlikely to be released during normal traffic as vehicles will be covered. Accidental releases of dust during traffic accidents may have a small effect on human health. The toxicological properties of leachable components of Project copper concentrates have been investigated, but this data does not inform on the specifics on the effects of concentrate dust; however, the Highland Valley Copper project has a Materials Safety Datasheet (MSDS) for concentrate issued by Teck Metals Ltd. The information contained in the MSDS is based on information in the technical and scientific literature about the material's constituent components (Teck 2010). It concludes that concentrate dust is an irritant through inhalation and ingestion, but is not readily absorbed within the body. Also, if set fire in as a result of an accident, concentrate can burn and release copper oxide fumes, as well as toxic SO₂ gas.

Diesel and lubricants will not be released to the air; however, combustion products and particulate matter from diesel combustion will increase. During traffic accidents, small or large volumes of diesel may be released from truck fuel tanks or diesel fuel trucks, respectively. The light-weight molecules of diesel and lubricants are highly volatile and the inhalation of vapours can be harmful to human health. Excessive exposure can cause irritation to the nose, throat, lungs, and respiratory tract and effects to the central nervous system. Vapours can also ignite rapidly and release dangerous fumes containing CO and particulate matter (PM). PM can be inhaled at sizes smaller than 10 µm, and PM_{2.5} is recognized as having the largest health risks due to deeper lung penetration (Liu 2004). PM_{2.5} has been identified by the BC Lung Association as the air emission of the most concern from a human health perspective (BC MOE 2007), and linked to health problems such as respiratory diseases and lung cancer (BC Air Smart 2010). A health threat can also occur from aspiration (breathing into the lungs) of liquid droplets of diesel. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death. Diesel has been characterized as a possible carcinogen after prolonged exposure. A short occasional exposure to diesel will not normally cause any long-term health effects.

Risk Mitigation

Risks to human health from increases in air emissions from normal traffic will be minimized by enforcing speed limits and operating well maintained vehicles powered by low sulphur fuel to optimize combustion. Further mitigation measures can be found in Section 5.7. In the event of traffic accidents, emergency response procedures to prevent fires or minimize fire duration and extent will be initiated promptly. Responsible personnel will be trained in spill response procedures to contain the spill, thereby minimizing vaporization or evolution of concentrate dust. Personnel will also be trained in safety and personal protection procedures to avoid contact with spilled material. Potentially affected residents will be informed of a spill, and access to the spill site will be restricted in consultation with regulators. These actions will largely eliminate health risks from inhaling dust, vapours or combustion fumes.

Risk Characterization

The contribution of Project traffic to air quality is unavoidable because all vehicles will require fuel combustion engines. However as described in Section 5.7, given baseline levels of CACs and the level of expected traffic increase, CAC contribution to ambient air quality is expected to remain well below BC air quality objectives and standards. This conclusion will be quantified by the detailed dispersion study that will be presented in the Application/EIS, where the modelling domain will be extended to include a sufficient part of Highway 37 (i.e., the section between Bowser Lake and the Highway 37/Eskay Creek access road intersection) for the assessment of Project air emissions.

Traffic accidents that do not involve fires or large spills will not contribute to the effects on air quality and human health because they will not involve combustion-related emissions or dust releases to the atmosphere. In the event of large accidents, such as fuel truck fires or concentrate spills, air emissions will be released immediately. Since the duration of such incidents would be short and localized, and since spill response procedures would be implemented, the probability of adverse effects is rare.

5.8.3.4 *Drinking Water Quality*

Risk Identification

Local communities mostly rely on well water for their drinking water needs (BC MOE 2012). For any health effects to occur from the consumption of drinking water, contaminants need to infiltrate a groundwater aquifer used as a source for drinking water. Highly soluble (e.g., ammonium nitrate) and mobile (e.g., ammonium nitrate and light diesel/lubricant fractions) substances could come in contact with groundwater aquifers used for drinking water in the event of an accident. Metals leached from spilled concentrates, hydrocarbons, and nitrates can be harmful to human health if not mitigated and if ingested at sufficiently high concentrations.

The aforementioned EPA 1311 test for copper concentrate toxicity (see Section 2.4.5) provided data on metal concentrations in the resulting leachate that were compared to Canadian Drinking Water Guidelines to detect exceedances. Acid-leachable antimony, arsenic, barium, cadmium, chromium, iron, lead, and selenium exceeded the Canadian Drinking Water Guidelines (BC MOE 2006)(Table 2.4-5). However, environmental conditions are unlikely to be as acidic as tested with the EPA 1311 test, and the pH of the copper concentrate itself is alkaline. As a result, lower concentrations of metals will leach into receiving waters should a spill occur. In addition, the EPA 1311 test does not take dilution into account.

Lime spills may result in an increase of local pH above the Drinking Water Guideline of 6.5 to 8.5 (Health Canada 2011) but has no long-term toxic effects. Potential effects of chemical hazards are described in greater detail in Table 6.4-5, Section 6.4.4.

Risk Mitigation

BMPs will be used to minimize spill contact with waterbodies or the terrestrial environment. This will include regular truck inspections, a scheduled maintenance program, and operation of trucks that meet or exceed Transport Canada's minimum requirements (Transport Canada n.d.). Drivers and personnel will receive training and industry-related education and conduct monthly safety meetings in order to handle challenges effectively. Drivers will be TDG, WHMIS and CPPI-certified as required. Speed limits and traffic safety rules will be enforced. Communication devices (VHF radio, satellite phone) and emergency contacts will be readily accessible to drivers. The Spill Prevention and Emergency Response Plan will be developed and implemented to limit effects on drinking water and human health. Water quality will be monitored in the event that a spill enters the aquatic environment.

Risk Characterization

Human health effects from the ingestion of contaminated drinking water are unlikely. This assessment is based on the low number of historic and predicted traffic accidents (as described in Chapter 2) and the commitment to BMPs in spill management planning. Immediate clean-up of spills will prevent hazardous materials from entering local drinking water sources. However, to determine the severity of risks from a concentrate spill into surface water, metal concentrations in a test leachate will be incorporated into the risk assessment for Human Health in the EA document.

5.8.3.5 Human Safety

Risk Identification

Vehicle collisions may result in immediate human health effects (i.e., injury or fatality). Historical police accident reports for highways 37 and 37A (Chapter 3) distinguish between accidents resulting in injury or fatality, and accidents resulting in PDO; however, accidents causing either injuries or fatalities are not further distinguished. Thus, the severity of health risks to a person is difficult to assess. Between 1996 and 2011, 119 severe accidents were recorded on Highway 37 between Bob Quinn Camp and Kitwanga (an average of 7.4 severe accidents per year) and 12 severe accidents for Highway 37A between Stewart and Meziadin (an average of 0.75 accidents per year). Of the total number of severe accidents, there were 23 involving commercial vehicles (average 1.4 per year) on Highway 37, and 3 involving commercial vehicles (average 0.2 per year) on Highway 37A. Police data do not indicate whether injuries or fatalities were incurred among pedestrians or cyclists. ICBC data, which are incomplete and can therefore not be cross-referenced with police data, indicate no injuries or fatalities among cyclists or pedestrians for the accidents they recorded on highways 37 and 37A.

Risk Mitigation

Speed limits and other traffic rules will be strictly enforced. All contractors and workers are required to adhere to the BC Occupational Health and Safety Regulation (BC Reg 296/97), as well as a zero-tolerance policy on alcohol and drugs. Procedures for emergency response and occupational first aid will be developed, and workers and contractors will undergo required training. Information on weather and highway conditions as well as communication devices (VHF radio, satellite telephone) will be made available to all drivers before departure.

Risk Characterization

Historically, an annual average of 1.4 and 0.2 severe collisions (resulting in injury or fatality) per year occurred on highways 37 and 37A, respectively. Accident statistics show a downward trend between 1996 and 2011. A minor increase in the *predicted* number of severe collisions per year is expected during operation on the northern segment of Highway 37, and a negligible increase in severe collisions is predicted for the south segment of Highway 37 and on Highway 37A. Construction, closure and post-closure phases of the Project will not negatively affect human health due to severe collisions. Human health risks from accidents cannot be eliminated, but while the number of accidents may increase slightly during the operation phase, the severity of injury cannot be determined from the available data.

5.9 HERITAGE

5.9.1 Baseline Data Overview

The heritage effects assessment focuses on the first 200 m area on either side of the highways in the Study Area (Figure 5.1-1). A search of the BC Archaeology Branch's Remote Access to Archaeological Data (RAAD) application, and a review of pertinent maps and reports, were conducted to identify protected

archaeological sites within this range in the Study Area. The results of this search are presented in Table 5.9-1. According to RAAD, no archaeological sites have been recorded within 200m of Highway 37A.

Table 5.9-1. Archaeological Sites within 200 Metres of Highway 37

Borden Number	Distance to Highway 37 (m)	Site Type	Site Location
GhTa-1	200	Village site	Near Gitanyow
GhTa-3	143	Historic mill	Near Gitanyow
GhTa-5	176	Culturally Modified Trees (CMTs)	Near Gitanyow
GiTa-4	216	Cultural depressions, CMTs	Near Gitanyow
GiTa-5	182	Historic camp, CMTs	Near Gitanyow
GiTa-6	137	Cultural depressions, CMTs	Near Gitanyow
GiTa-7	78	Subsurface lithics	Near Gitanyow
GiTa-8	78	Subsurface lithics	Near Gitanyow
GjTb-1	14	Grave site	Near Cranberry River
GjTd-1	113	Cabin, trail	Near Cranberry Junction
GkTf-1	200	Village site	Near Van Dyke Camp
GkTf-2	126	Grave site, CMTs, arbourglyph	Near Van Dyke Camp
GkTf-3	185	Historic cache	Near Van Dyke Camp
GlTg-1	120	Cultural depressions	Near Meziadin Lake
HbTh-1	27	Grave site, CMTs	Near Bell I bridge
HeTk-1	200	Surface and subsurface lithics	Near Bell II
HeTk-3	95	Bell Irving Telegraph Cabin	Near Bell II
HeTl-2	42	Snowbank Creek Telegraph Cabin	Near Bell II
HfTm-1	198	Subsurface lithics	Near Bob Quinn
HfTm-2	14	Subsurface lithics	Near Bob Quinn
HfTm-3	5	Subsurface lithics	Near Bob Quinn
HfTm-4	155	Trail, CMT	Near Bob Quinn
HfTn-1	58	Echo Lake Telegraph Cabin	Near Bob Quinn

The 23 archaeological sites described in Table 5.9-1 are all those sites that are presently recorded in the assessment area. There may be additional sites that have not yet been recorded. In addition to the 23 archaeological sites, three Aboriginal and/or historically documented trails may run within 200 m of portions of highways 37 and 37A. The routes of the Kitwancool Grease Trail, the Stikine Trail and the Yukon Telegraph Trail paralleled some of the segments of Highway 37 under consideration in this study. However, in general, the trails themselves have not been recently ground-truthed, and their current condition is not well documented.

5.9.2 Issue Scoping

5.9.2.1 Heritage Scoping

Normal Project traffic is rated as posing no risk to archaeological sites, as it would not be expected to result in substantial off-highway disturbance to ground and vegetation. Even if an off-road forest fire or a serious accident or spill (involving hazardous materials resulting in emergency remediation) were to occur, the likelihood of such an event affecting one of the 23 known sites in the assessment area is

assessed to be low to nil, as the majority of those sites are small, and 18 of them are greater than 50 m from the highway (Table 5.9-2).

Table 5.9-2. Heritage Scoping Matrix

Traffic Type	Potential Risk? (Yes/No)	Rationale for Selection/Exclusion
<i>Project traffic</i>		
All traffic	No	Project activity confined to highway.
<i>Traffic accidents</i>		
All traffic	Yes	Potential risk for off-road disturbance to ground and vegetation.

5.9.2.2 Valued Component Scoping

This assessment considers archaeological sites protected by the BC *Heritage Conservation Act* as a VC (Table 5.9-3). The party who identified each potential VC is also referenced in the table: Aboriginal groups (AG); government (G); public/stakeholder (P/S); or other (O) (e.g., legislation, technical expertise).

Table 5.9-3. Identification and Rationale for Heritage Valued Component Selection/Exclusion

VC	Identified by ¹				Selected for... ²		Rationale for Selection/Exclusion
	AG	G	P/S	O	Normal Project Traffic?	Traffic Accidents?	
Archaeological sites		X			No	Yes	Sites are legally protected. Potential effects from an off-road vehicle accident.

¹ "X" indicates that the corresponding group (AG = Aboriginal Group, G = Government, P/S = Public/Stakeholder, or = Other) has identified the VC as an issue; "-" indicates that the group did not identify the VC as an issue.

² "Yes" indicates that the VC is selected for further analysis; "No" indicates that the VC is excluded from further analysis.

5.9.2.3 Potential Traffic/Valued Component Interactions

Potential interactions between traffic accidents along proposed routes and archaeological sites are summarized in Table 5.9-4. Scenarios that could pose a potential risk to archaeological sites are off-highway incidents such as a hazardous materials accident or a spill that results in emergency remediation of contaminated soils or a forest fire along the highway.

Table 5.9-4. Potential Traffic/Heritage Valued Component Interaction Matrix

Traffic Type	VCs
	Archaeological Site Condition
<i>Project traffic</i>	
All traffic	-
<i>Traffic accidents: on-road</i>	
All traffic	-
<i>Traffic accidents: off-road</i>	
All traffic	X

"X" indicates that a potential interaction has been identified.

"-" indicates that no potential interaction was identified.

5.9.3 Risk Analysis

This section analyses the risks associated with Project traffic on archaeological sites. Interactions identified in Table 5.9-3 are analysed and assigned a risk severity according to the definitions in Table 5.9-5. The traffic types, their potential risks, mitigation measures and severity are shown in Table 5.9-6.

Table 5.9-5. Heritage Risk Assessment Severity Scale Descriptors

Descriptor	Definition
Negligible	No disturbance to the integrity of the site.
Minor	Small-scale disturbance to the site (<5% disturbance of site area).
Moderate	Moderate-scale disturbance to the site (6-20% disturbance of site area).
Major	Large-scale disturbance to the site (20-50% disturbance of site area).
Catastrophic	Total or near total disturbance of the site (>50% disturbance of site area).

Risk Identification

Scenarios that could pose a potential risk to archaeological and heritage sites are off-road incidents that result in disturbance to ground or vegetation. Examples of such events could include a hazardous materials accident or a spill that results in emergency remediation of contaminated soils. The likelihood of such an event affecting one of the 23 known sites and three trails in the assessment area is low, as these sites represent very small portions of the assessment area and the majority of the sites are greater than 50 m from the highway.

5.9.3.1 Chemical Contamination

Risk Mitigation

Preventing the introduction of hazardous substances into the environment is the most effective way to avoid effects to heritage VCs. Specific preventative measures that may be implemented include conducting a vehicle assessment (for oil leaks, secure cargo, etc.) and checking road conditions prior to departure, maintaining an appropriate driving distance between vehicles, adhering to speed limits, and adjusting driving styles to suit road conditions.

In the event of a spill, the guidelines and procedures outlined in the Spill Prevention and Emergency Response Plan will be followed in order to avoid contamination and degradation of archaeological sites.

Risk Characterization

The potential impact to archaeological soils would depend on the type of chemical and proximity to archaeological and heritage sites to the spill. The full nature of potential effects cannot be evaluated at this time because the volume of the spill and the concentrations that may enter the environment are unknown; therefore, in the event of a spill, a risk assessment that evaluates exposure to VCs will be conducted.

After mitigation, the likelihood of chemical contamination to heritage VCs is rare. The severity ranges from negligible to moderate depending on the type, frequency and size of the spill as well as the elapsed time between the occurrence and the removal of contaminants.

Table 5.9-6. Heritage Risk Assessment Matrix for Traffic Accidents

VC	Traffic Type	Description of Potential Risk (pre-mitigation)	Project Phase	Description of Mitigation Measures	Post-mitigation		
					Likelihood	Severity	Description of Consequence of Realized Risk
Archaeological and Heritage Sites	All traffic types	Increase in vehicle traffic may result in increased accidents involving spilling of deleterious substances, which can result in damage to archaeological and heritage sites	All phases	Conducting a vehicle assessment; checking road conditions prior to departure; maintaining appropriate distance between vehicles; adhering to speed limits; adjusting driving styles to suit road conditions; and adhering to the Spill Prevention and Emergency response Plan	Rare	Negligible	The circumstances of the spill will determine the extent of potential contamination of subsurface components of the site.
Archaeological and Heritage Sites	All traffic types	Increased incidence and severity of wildfires due to flammable material spills	All phases	Policy requiring the proper disposal of smoking materials; and fire watch and reporting program	Rare	Moderate	Depends on duration and severity of the wildfire. Can range from minor disturbance to the site to removal of surficial features if present and contamination of subsurface components

5.9.3.2 *Incidence of Wildfire*

Risk Identification

An increase in vehicle traffic along Highway 37 may result in an increased risk of wildfire. Such an increase would be related to traffic accidents as ignition sources and improper disposal of smoking materials.

Wildfires have the potential to alter archaeological and heritage sites by destroying surface features (if present), and to introduce contamination of subsurface components of sites when roots are burned.

The potential to alter archaeological and heritage sites is dependent on the severity of the fire, which is determined by both the areal extent and intensity.

Risk Mitigation

Preventing an increase in wildfire incidence involves reducing the risk of vehicle accidents and enacting policies requiring the proper disposal of smoking materials. Reduction of vehicle accidents can be accomplished with policies that address vehicle maintenance, driving under poor conditions (snow-covered or icy roads, night driving), and driver fatigue. Accidental ignition due to improper disposal of smoking materials can be addressed by strong policies requiring their proper disposal. Risk will further be reduced by instituting a fire watch and reporting program by drivers who will be on the road 24 hours a day, and an Emergency Response Plan (which will be included in the Project's Application/EIS).

Risk Characterization

Highway 37 runs through the Kalum Forest District (Northwest Fire Centre) of northwestern BC, which has seen few major (>4 ha burned area) and several minor (<4 ha burned area) wildfires during the past decade (BC Forest Service Protection Branch 2008). This low incidence of wildfire is due to the regional climate characteristics (long winters and short, wet summers), and limited access to backcountry areas.

After mitigation, the likelihood of increase in wildfire due to an increase in traffic is rare. This rating is due mainly to the low background level of fire incidence in this area of BC. Mitigation will be most important during the summer months, when drier weather can result in higher risk of wildfire.

The severity of wildfire occurrence is highly variable, and depends on local climate conditions, the time of wildfire ignition, and the resources available for response.

6. Summary of the Potential Risks of Project Traffic Accidents

6.1 INTRODUCTION

This chapter assesses the potential for Project-related traffic accidents on highways 37 and 37A. Using a risk assessment approach, the probability and severity of various potential accidents and malfunctions was assessed for effects to: social and economic environments; fish and aquatic habitat; wildlife; terrestrial ecosystems; wetlands; noise; climate and air quality; human health; and heritage (Sections 5.1 through 5.9, respectively). This chapter also summarizes the potential risks of traffic accidents particular to each of these detailed assessments.

Traffic accidents exclude any risks associated with traffic from the Project. Traffic accidents are categorized as “on-road” or “off-road,” and involving either hazardous or non-hazardous cargo. Utilizing available data on traffic accidents along the segments of highway scoped into this study, collision prediction modelling (Section 3.2) was used to make determinations about the probability and potential severity of traffic accidents on each VC. Each topic-specific traffic assessment (Sections 5.1 through 5.9) used the prediction analysis to classify the likelihood and severity of a traffic accident.

Examples of potential results of traffic accidents related to Project traffic are spills of hazardous materials (including hydrocarbon leakage from fuel tanks), detonation of explosives, fires, and human injury or mortality as a result of Project-related traffic on highways 37 and 37A. Traffic accidents may occur due to malfunctioning equipment, driver error or fatigue, poor weather, unexpected road conditions, or unforeseen circumstances. The Mitigation and Management chapter (Chapter 7) discusses the precautions that will be taken to minimize the likelihood and severity of traffic accidents.

6.2 SCOPE AND OBJECTIVE

The objective of this section is to determine the potential risk and severity of traffic accidents which could occur in spite of mitigation measures implemented for Project-related-traffic. VCs discussed relate specifically to biophysical and human environment components included in Chapter 5. The section also includes a summary discussion on mitigating and managing the potential risks arising as a result of the accidents themselves.

6.3 POTENTIAL TRAFFIC ACCIDENT SCENARIOS

Project-related vehicles will transport non-hazardous cargo, such as tools and building materials, as well as personnel along Highway 37. For non-hazardous cargo, the risk of a traffic accident resulting in hydrocarbon leakage and/or human effects is considered in the risk assessment. Additionally, Project related vehicles will carry hazardous cargo. The following section includes a description of potential accident scenarios that were considered in the risk assessment in each topic-specific study (Chapter 5).

6.3.1 Discharge of Hazardous Materials into the Environment

Risks include:

- Discharge of hazardous cargo into the receiving environment for both on-road (with potential seepage) and off-road vehicle accidents.
- Hydrocarbon leakage from vehicles, both on-road (with potential seepage) and off-road, into the receiving environment.

- Particulate dispersion from cargo containing solid or powdered hazardous material, including cyanide, due to high winds, failure of containment or storage measures or other unforeseen circumstances, into the receiving environment.

6.3.2 Detonation of Explosives

A proportion of Project-related traffic will be carrying explosive materials. Potential risks from the accidental detonation of explosives were considered. Detonation could occur in the event of ignition of the engine and/or vehicle fuel as a result of an accident. Detonation could occur if the fire were to reach the explosive materials, potentially leading to further property damage and impacts on human health.

6.3.3 Fires

Fires could occur following traffic accidents, particularly when collisions involve more than one vehicle, as a result of hydrocarbon leakage or overheating engines. Fires could lead to additional property damage (vehicles or buildings), environmental effects, as well as negatively affect human health.

6.3.4 Injury or Mortality

Accidental collisions involving two or more vehicles pose potential risks of injury or mortality to humans.

6.4 RISKS BY ACCIDENT SCENARIO

Traffic accidents are a rare occurrence that may take place in spite of the mitigation and management measures that are put into place for Project-related traffic. The biophysical and human risks associated with these events for both on-road and off-road accidents, involving non-hazardous or hazardous cargo, are detailed in the following section. Additional mitigation and management measures to minimize risks arising from traffic accidents are also discussed.

6.4.1 On-road, Non-hazardous Cargo

Risks associated with on-road traffic accidents involving non-hazardous cargo are detailed in Table 6.4-1.

The likelihood of such events is predominantly characterized as unlikely or rare. The severity of potential, unintended consequences is predominantly characterized as minor or moderate. The level of consequence of effects on the biophysical environment depends on the location and time lapse between occurrence and clean-up. In case of an on-road accident with non-hazardous cargo, the following measures will be implemented to minimize potential risks detailed in Table 6.4-1:

- Project-related drivers and personnel will be certified in First Aid.
- All Project-related vehicles will be equipped with fire extinguishers.
- BMPs will be employed to minimize spill entry into waterbodies.
- Discussions and training will be carried out with community first responders and local emergency service providers to ensure they are appropriately trained and equipped to implement emergency response procedures.
- A prompt spill response procedure will be implemented to contain any potential hydrocarbon spill and minimize both vaporization and/or biophysical environmental contamination (including any effects on wildlife). The procedure will limit the time and extent a contaminant may be in contact with the biophysical environment.
- An emergency response procedure in the event of fire will be carried out to minimize fire duration and extent.

Table 6.4-1. Potential Risks and Severity of On-road Traffic Accidents (Non-hazardous Cargo)

Assessment Topic	Risk
Socio-economic	Reduction in safety for other vehicle traffic along the highway. Potential human injury or death.
Fish and Aquatic Habitat	Fuel or lubricant spill(s) from the vehicle(s) fuel tanks could extend beyond the road surface resulting in the deposition of deleterious substances into aquatic habitat.
Wildlife	Toads, moose and bears could be exposed to hydrocarbons from spilled fuel tanks via the ingestion of soil, water and prey species and via dermal absorption. Habitats along the highway used by moose and bears may be vulnerable to traffic accidents, such as gasoline spills.
Terrestrial Ecosystems	Tissue damage to vegetation and contamination of soil.
Wetlands	Wetland function could be compromised if fuel or lubricant spill(s) from the vehicle(s) extend beyond the road surface resulting in the deposition of deleterious substances into a wetland.
Noise	None.
Climate and Air Quality	A localised reduction in air quality from potentially harmful emissions due to fuel fires. Potential contribution of GHG emissions.
Human Health	Potential human injury or death. Potential for fuel or lubricant spill(s) into drinking water.
Heritage	Fuel or lubricant spill(s) from the vehicle(s) could extend beyond the road surface. Deleterious substances could damage archaeological and heritage sites.

6.4.2 On-road, Hazardous Cargo

Risks associated with on-road traffic accidents involving hazardous cargo are detailed in Table 6.4-2, while a more detailed description of the risks and mitigation associated with the transport of Process Plant reagents are detailed in Table 6.4-5.

Table 6.4-2. Potential Risks and Severity of On-road Traffic Accidents (Hazardous Cargo)

Assessment Topic	Risk
Socio-economic	Reduction in safety for other vehicle traffic along the highway. Potential human injury or death.
Fish and Aquatic Habitat	Hazardous cargo spill(s) could extend beyond the road surface resulting in the deposition of deleterious substances into the aquatic habitat.
Wildlife	Toads, moose and bears could be exposed to the chemicals via the ingestion of soil, water and prey species and via dermal absorption. Habitats along the highway used by moose and bears may be vulnerable to traffic accidents, such as chemical spills, including gasoline.
Terrestrial Ecosystems	Tissue damage to vegetation and contamination of soil.
Wetlands	Wetland function could be compromised if hazardous cargo spill(s) extend beyond the road surface resulting in the deposition of deleterious substances into a wetland.
Noise	None.
Climate and Air Quality	A localised short term reduction in air quality from potentially harmful emissions due to fuel fires. Potential contribution of GHG emissions.
Human Health	Potential human injury or death. Potential for hazardous cargo spill(s) into drinking water.
Heritage	Hazardous cargo spill(s) could extend beyond the road surface. Deleterious substances could damage archaeological and heritage sites.

The likelihood of such events is predominantly characterized as unlikely or rare. The severity of potential, unintended consequences is predominantly characterized as minor or moderate. The severity could be minor to moderate for the biophysical environment, depending on the location and time lapse between occurrence and clean-up. In case of an on-road accident with hazardous cargo, the following measures, in addition to the aforementioned measures in Section 6.4.1, will be implemented to minimize any potential risk detailed in Table 6.4-2:

- Use of best technologies and practices, including the International Cyanide Management Code (ICMI n.d.), for containing chemicals and explosives.
- Shipment of low moisture concentrate where and when possible.
- Neutralization of active materials, including lime.

6.4.3 Off-road, Non-hazardous Cargo

Risks associated with off-road traffic accidents involving non-hazardous cargo are detailed in Table 6.4-3.

Table 6.4-3. Potential Risks and Severity of Off-road Traffic Accidents (Non-hazardous Cargo)

Assessment Topic	Risk
Socio-economic	Reduction in safety for other vehicle traffic along the highway. Potential human injury or death.
Fish and Aquatic Habitat	Fuel or lubricant spill(s) from the vehicle(s) could result in the deposition of deleterious substances into the aquatic habitat.
Wildlife	Toads, moose and bears could be exposed to the chemicals via the ingestion of soil, water and prey species and via dermal absorption. Habitats along the highway used by moose and bears may be vulnerable to traffic accidents, such as gasoline spills.
Terrestrial Ecosystems	Tissue damage to vegetation and contamination of soil.
Wetlands	Wetland function could be compromised by any vehicle presence within a wetland system. Wetland function could be affected if fuel or lubricant spill(s) from the vehicle(s) result in the deposition of deleterious substances into the wetland.
Noise	None.
Climate and Air Quality	A localised short term reduction in air quality from potentially harmful emissions due to fuel fires. Potential contribution of GHG emissions.
Human Health	Potential human injury or death. Potential fuel or lubricant spill(s) into drinking water.
Heritage	Fuel or lubricant spill(s) from the vehicle(s) could extend beyond the road surface. Deleterious substances and potential fires could damage archaeological and heritage sites.

The likelihood of such events is predominantly characterized as unlikely or rare. The severity of potential, unintended consequences is predominantly characterized as minor to moderate. The severity could be minor to moderate for the biophysical environment, depending on the location and time lapse between occurrence and clean-up. In case of an off-road accident with non-hazardous cargo, the following measures will be implemented to minimize any potential risk detailed in Table 6.4-3:

- Project-related drivers and personnel will be certified in First Aid.
- All Project-related vehicles will be equipped with fire extinguishers.
- BMPs will be employed to minimize spill entry into waterbodies.
- Discussions and training will be carried out with community first responders and local emergency service providers to ensure they are appropriately trained and equipped to implement emergency response procedures.

- A prompt spill response procedure will be implemented to contain any potential hydrocarbon spill and minimize both vaporization and/or environmental contamination (including any effects on wildlife). The procedure will limit the time and extent a contaminant may be in contact with the biophysical environment.
- An emergency response procedure in the event of fire will be carried out to minimize fire duration and extent.

6.4.4 Off-road, Hazardous Cargo

General risks associated with off-road traffic accidents involving hazardous cargo are detailed in Table 6.4-4. Table 6.6-5 provides a more detail on the risks associated with an off-road accident involving a vehicle carrying Process Plant reagents. The severity associated with reagent spills is categorized as acute (the effect would be immediate and potentially severe), chronic (the effect would be of long duration), and/or bioaccumulating.

The likelihood of such an event is rare, and severity could be minor to catastrophic for the biophysical environment, depending on the location, the substance spilled, and time lapse between occurrence and clean-up. In case of an off-road accident with hazardous cargo, the following measures, in addition to the aforementioned measures in Section 6.4.1, will be implemented to minimize any potential risk detailed in Tables 6.4-4 and 6.4-5:

- Use of best technologies and practices, including International Cyanide Management Code (ICMI n.d.), for containing chemical and explosives.
- Shipment of low moisture concentrate where and when possible.
- Neutralization of active materials, including lime.

Table 6.4-4. Potential Risks and Severity of Off-road Traffic Accidents (Hazardous Cargo)

Assessment Topic	Risk
Socio-economic	Reduction in safety for other vehicle traffic along the highway. Potential human injury or death.
Fish and Aquatic Habitat	Hazardous cargo spill(s) would result in the deposition of deleterious substances into the aquatic habitat.
Wildlife	Toads, moose and bears could be exposed to the chemicals via the ingestion of soil, water and prey species and via dermal absorption. Habitats along the highway used by moose and bears may be vulnerable to traffic accidents, such as chemical spills, including gasoline.
Terrestrial Ecosystems	Tissue damage to vegetation and contamination of soil.
Wetlands	Wetland function could be compromised by any vehicle presence within a wetland system. Wetland function could be compromised if hazardous cargo spills result in the deposition of deleterious substances into a wetland.
Noise	None.
Climate and Air Quality	A localised short term reduction in air quality from potentially harmful emissions due to fuel fires. Potential contribution of GHG emissions.
Human Health	Potential human injury or death. Potential for hazardous cargo spill(s) into the terrestrial and aquatic environments and affecting country foods and drinking water.
Heritage	Deleterious substances and fire could damage archaeological and heritage sites.

Table 6.4-5. Potential Risks and Severity of Traffic Accidents involving Process Plant Reagent Spills

Reagent	Description and Potential Risk Considering Mitigation			Description
	Acute	Chronic	Bioaccumulating	
Sodium Hydrosulphide (NaHS)	Y	N	N	<p>Fish and Wildlife: Acute toxic effects. LC50 (96 hr) ranges from 46 - 6,080 mg/L depending on species.</p> <p>Wetlands and Terrestrial Ecosystems: If dissolved in water, exposure to plants is acutely toxic and will damage contacted plant tissues.</p> <p>Human Health: Acute toxic effects. Causes burns by all exposure routes. Develops highly toxic hydrogen sulfide gas if exposed to acid or heat source (fire). Substance may have chronic effects but they are unlikely to occur given spill clean-up protocol.</p>
Sodium Cyanide (NaCN)	Y	Y	N	<p>Fish and Wildlife: Acute toxic effects causing death. LD50 range from 2.7 - 28 mg/kg body weight depending on species. Chronic effects in nature are rare as cyanide is short-lived, but prolonged exposure can cause damage to skin, eyes and nervous system.</p> <p>Wetlands and Terrestrial Ecosystems: If dissolved in water, exposure to plants is acutely toxic and will damage contacted plant tissues.</p> <p>Human Health: Maximum allowable cyanide concentration in drinking water is 0.2 mg/L (US EPA 1994) , or 200 µg/L for free cyanide(Health Canada 1991) , and higher concentrations are considered extremely harmful to life (Lordi et al. 1980). Chronic effects include adverse reproductive effects (maternal and paternal fertility) based on animal data. Acute effects include irritation to skin, eyes, respiratory tract, and may be fatal if inhaled or swallowed.</p>
Sodium Silicate (Na ₂ SiO ₃) (Sodium Metasilicate)	Y	Y	N	<p>Fish and Wildlife: Oral toxicological effects include ulceration or bleeding in the stomach, duodenum, and small intestine. LD50s range from 200 mg/kg to 2400 mg/kg depending on the species. If dissolved in water, alkaline pH is harmful to aquatic life. As a dust, causes mild eye and skin irritation.</p> <p>Wetlands and Terrestrial Ecosystems: If dissolved in water, alkaline pH may harm plant tissues.</p> <p>Human Health: Dust may cause mild skin and eye irritation. Inhalation is irritating to the respiratory tract. Chronic exposure to the lungs is a cancer hazard, but this risk is highly unlikely given the spill clean-up protocol.</p>
Activated Carbon	Y	N	N	<p>Fish and Wildlife: Not toxic, in its original state. LD50 (oral, rat) > 10,000 mg/kg. May become toxic as used activated carbon may exhibit characteristics of the absorbed material.</p> <p>Wetlands and Terrestrial Ecosystems: No adverse effect in original state.</p> <p>Human Health: Minor skin and eye irritant with prolonged exposure.</p>
Hydrochloric Acid (HCl)	Y	Y	N	<p>Fish and Wildlife: Exposure can lead to burns and damage of target organs. Acutely toxic to fish and may cause death LC50 = 10 -100 ppm in most sensitive species. pH shifts outside of the range of 5-10 standard units may be toxic to aquatic organisms.</p> <p>Wetlands and Terrestrial Ecosystems: Exposure of plants is acutely toxic and will damage contacted plant tissues; effects will not persist following neutralization. Chronic plant toxicity at 100 ppm.</p> <p>Human Health: Adverse effects if in contact with skin or eyes, if ingested, or inhaled. Substance may have chronic toxic effects to kidneys, liver, mucous membranes, upper respiratory tract, skin, eyes, circulatory system, teeth. This is highly unlikely given spill cleanup protocol.</p>
Sodium Hydroxide (NaOH) (Caustic soda)	Y	Y	N	<p>Fish and Wildlife: Exposure can lead to burns and damage of target organs and death LC50 = 35-100 mg/L in freshwater.</p> <p>Wetlands and Terrestrial Ecosystems: Exposure to plants is acutely toxic and will damage contacted plant tissues; effects will not persist following neutralization.</p> <p>Human Health: Adverse effects if in contact with skin or eyes, if ingested, or inhaled. Substance may have chronic toxic effects to lungs. This is highly unlikely given spill clean-up protocol.</p>
Sodium Metabisulfite (MBS)	Y	Y	N	<p>Fish and Wildlife: Acute oral toxicity LD50 ~ 1,000 mg/kg (Guinea pig, Rat). Lung irritant.</p> <p>Wetlands and Terrestrial Ecosystems: No toxic or adverse effect is predicted.</p> <p>Human Health: Skin irritant and hazardous in case of ingestion or inhalation. May be mutagenic or cause adverse reproductive effects. Potential chronic effects to upper respiratory tract if repeated or prolonged exposure. Prolonged exposure is unlikely.</p>
Copper Sulphate Pentahydrate (CuSO ₄ .5H ₂ O)	Y	Y	Y	<p>Fish and Wildlife: Practically nontoxic to birds, but highly toxic to fish and other aquatic life especially in soft or acidic waters. May cause effects such as behavioral changes at low concentration to death at concentration of 0.39 mg/L over 96-hours. May be poisonous to mammals if ingested.</p> <p>Wetlands and Terrestrial Ecosystems: This material has serious potential for phytotoxicity and kills plants by disrupting photosynthesis. When released into the soil or water, this material is not expected to biodegrade.</p> <p>Human Health: Acute effects include hazards in case of skin contact (irritant), of eye contact (irritant), of ingestion and inhalation. Chronic effects include mutagenesis and toxicity to kidneys, and liver. Repeated or prolonged exposure to the substance can produce target organs damage.</p>
Sulphuric Acid (H ₂ SO ₄)	Y	Y	N	<p>Fish and Wildlife: Sulphuric acid is toxic to aquatic life in very low concentrations. It may be dangerous if it enters water intakes and may cause death.</p> <p>Wetlands and Terrestrial Ecosystems: Endangers drinking water supply if allowed to enter soil and/or waters in large quantities. Exposure to plants is acutely toxic and will damage/kill plants with contact. Effects will not persist after a spill is cleaned up.</p> <p>Human Health: When inhaled, results in damage of mucous membranes of mouth, nose, throat and lungs. Causes severe pain, nausea, vomiting and diarrhea if ingested. Causes severe burns with skin contact. Leads to cornea damage and risk of blindness with eye contact. Chronic toxicity includes bronchitis, emphysema erosion of the teeth, chronic runny nose, tearing of the eyes, nose bleeds, and stomach upset. Has potential to cause lung cancer. Chronic exposure is highly unlikely given spill clean-up protocol.</p>

(continued)

Table 6.4-5. Potential Risks and Severity of Traffic Accidents involving Process Plant Reagent Spills (completed)

Reagent	Description and Potential Risk Considering Mitigation			Description
	Acute	Chronic	Bioaccumulation	
PAX (potassium amyl xanthate)	Y	Y	N	Fish and Wildlife: Skin or eye contact may be irritating. Harmful if absorbed through skin. May be toxic to aquatic biota at concentrations of less than 1 mg/L. Wetlands and Terrestrial Ecosystems: No adverse effect is predicted. Human Health: Minor skin and eye irritant. Prolonged exposure may cause adverse reproductive effects. Prolonged exposure is unlikely.
A208 (Diethyl Dithiophosphate)	Y	N	N	Fish and Wildlife: Low toxicity to aquatic organisms due to limited bioavailability. May be lethally toxic (LD50 = 7,900 mg/kg (oral, rat). May cause skin or eye irritation. Wetlands and Terrestrial Ecosystems: No adverse effect is predicted. Human Health: Minor skin and eye irritant.
3418A (Dialkyl Dithiophosphinate)	Y	N	N	Fish and Wildlife: Low toxicity to fish and wildlife. Wetlands and Terrestrial Ecosystems: No adverse effect is predicted. Human Health: Minor skin and eye irritant.
MIBC (Methyl Isobutyl Carbinol)	Y	Y	N	Fish and Wildlife: This material is practically non-toxic to fish and wildlife. Unlikely to persist in the environment. Wetlands and Terrestrial Ecosystems: This material is slightly adsorptive in soils and sediments and has an evaporation half-life of 23-hrs (rivers) to 10.6 days (pond). No effects on plants reported. Human Health: Harmful if swallowed, inhaled or absorbed through skin. Causes irritation to skin, eyes and respiratory tract. High concentrations cause central nervous system effects, such as dullness, dizziness, anesthesia.
Floculant (Magnafloc 336)	Y	Y	N	Fish and Wildlife: May contain cationic polymers that may be toxic to aquatic organisms; toxicity reduced by natural particles in the water. Wetlands and Terrestrial Ecosystems: No adverse effect is predicted. Human Health: This material has a low order of oral toxicity.
Anti-scalant	Y	N	N	Fish and Wildlife: No toxic effects predicted. Mild skin irritant. Wetland and Terrestrial Ecosystems: No adverse effects predicted. Human Health: Mild irritation to eyes and skin upon contact.
Fuel Oil	Y	Y	N	Fish and Wildlife: Cause harm to wildlife through physical contact, ingestion, inhalation and absorption. Light oils (gasoline, diesel aviation fuel) generally affect aquatic life and may be toxic to fish and invertebrates including reproductive impairment, and toxicity impacts to eggs and larvae. Wetland and Terrestrial Ecosystems: High mobility in soils may cause soil and/or groundwater contamination. Human Health: Irritation to eyes and skin upon contact. Inhalation may cause irritation, anesthetic effects, and respiratory system effects. Long-term exposure may cause target organ damage. Benzene is a known carcinogen.
Lime	Y	N	N	Fish and Wildlife: Exposure will lead to tissue damage due to direct contact or increase in water pH. Expected to be toxic to aquatic life. Wetland and Terrestrial Ecosystems: Exposure of plants will damage tissues; effects will not persist following clean up. Human Health: Severe damage to eyes and skin upon contact. Gastrointestinal tract burns, severe pain, nausea, vomiting when ingested. May cause circulatory system failure if in direct contact with large amounts.
Ferric Chloride (FeCl ₃)	Y	N	N	Fish and Wildlife: Corrosive if mixed with water due to acidic pH. Very hazardous in case of skin or eye contact or if ingested. No chronic effects. Wetland and Terrestrial Ecosystems: Corrosive if mixed with water due to acidic pH. Damaging to plant tissue. Human Health: Very hazardous in case of skin or eye contact or if ingested. No chronic effects.
Calcium Chloride (CaCl ₂)	Y	Y	N	Fish and Wildlife: Toxic to fish (LC50 (fish) 100 mg/L). Hazardous to wildlife upon contact or ingestion. Wetland and Terrestrial Ecosystems: Will burn plants. Human Health: Acute: Irritant to skin and eyes. Hazardous if ingested or inhaled. Chronic: May affect genetic material (mutagenic, carcinogenic) based on animal data. May affect taste of drinking water.
Copper Chloride (CuCl ₂ .2H ₂ O)	Y	Y	N	Fish and Wildlife: Acute and long-term toxicity to aquatic organisms in freshwater and marine environments. LC50 range from 0.08 - 0.9 mg/L in fish. Very hazardous in case of skin- and eye contact or ingestion. Wetland and Terrestrial Ecosystems: Acute and long-term toxicity to aquatic organisms in wetlands. Long-term toxic effect in plants. Human Health: Very hazardous in case of skin contact (irritant, blistering, permeator), of eye contact (irritant, blindness), of ingestion, of inhalation. Chronic effects: May affect genetic material (mutagenic).
Antifoam	Y	Y	N	Fish and Wildlife: No toxic effects predicted. Mild skin irritant. Wetland and Terrestrial Ecosystems: No adverse effects predicted. Human Health: Mild irritation to eyes and skin upon contact. May cause adverse reproductive effects if repeatedly inhaled, which is unlikely. Chronic exposure by inhalation may affect blood, respiration, behavior and liver.
Liquid Chlorine (Sodium Hypochlorite)	Y	N	N	Fish and Wildlife: Severely toxic to fish, amphibians and other aquatic life. Severe irritant to skin, eye, lungs or when ingested by wildlife. No chronic effects. Wetland and Terrestrial Ecosystems: Severely toxic to aquatic plants. Immediate damage to plants. Human Health: Severe irritant to skin, eye, lungs or when ingested. No chronic effects.

7. Summary of Mitigation and Environmental Management

7.1 INTRODUCTION

The Application/EIS will identify proposed mitigation and monitoring plans, including a Traffic and Access Management Plan, Dangerous Goods and Hazardous Materials Management Plan, Emergency Response Plan, and Spill Prevention and Emergency Response Plan. These plans will include mitigation and monitoring plans for the Project site, access roads and highway transportation routes in greater detail than provided for in this report. For this study, mitigation is focussed on the Project traffic along highways 37 and 37A.

Measures to avoid or mitigate potential effects associated with highway traffic are described in Section 7.3. These measures will be included in the Application/EIS as part of the Traffic and Road Management Plan and the Dangerous Goods and Hazardous Materials Management Plan.

Measures to avoid or mitigate potential effects associated with traffic accidents are described in Section 7.4. These measures will be included in the Application/EIS in the Emergency Response Plan (for emergencies other than spills), and the Spill Prevention and Emergency Response Plan. Additionally, the Accidents and Malfunctions chapter in the Application/EIS will address accidents and malfunctions on the Project site and along access roads.

Risk mitigations in this chapter are described relative to the social and environmental topics included in the individual traffic risk assessments (see Chapter 5).

7.2 MITIGATION AND MANAGEMENT OBJECTIVES

The objective of mitigation and management is to minimize potential environmental effects and effects on humans from Project-related traffic. The mitigation measures detailed here are intended to provide guidance for conducting Project activities along highways 37 and 37A in accordance with this objective. They are to ensure, for example, that Project activities are conducted in a manner that maximizes road safety, reduces potential for vehicle accidents, and avoids vehicle/wildlife interactions.

All components of the environmental management plans will be in compliance with regulatory requirements and will utilize BMPs as an additional guiding principle. Objectives and targets for the management plans related to traffic will continue to be refined as the Application/EIS is developed.

7.3 HIGHWAY TRAFFIC MANAGEMENT

7.3.1 Action to Avoid or Mitigate

This section identifies the measures that will help minimize and mitigate potential risks of Project-related traffic activities.

7.3.1.1 *Traffic and Access Management Plan Risk Mitigation Measures*

The following actions will be included in the Traffic and Road Management Plan in the Application/EIS:

- Posted speed limits will be enforced.

HIGHWAYS 37 AND 37A TRAFFIC EFFECTS ASSESSMENT

- All heavy vehicles travelling to and from the Project area will follow dedicated heavy vehicle routes.
- Vehicle load rates will be optimized to minimize the number of trips.
- Noise suppression technologies will be used where possible.
- Speeds will be reduced to 50 km/h in designated residential areas or as otherwise directed. Along the travelled portion of Highway 37, the only residential area is within Kitwanga Village near the gas station, speed limits are posted accordingly.
- Use of engine brakes, and reversing (use of reverse-alarm) will be avoided in residential areas.
- Vehicle idling will be minimized.

Vehicle specification and maintenance activities will also be identified in the Traffic and Road Management Plan:

- Project trucks will meet or exceed Transport Canada's minimum requirements (e.g., maximum allowable noise levels from heavy duty trucks).
- Vehicle manufacturers' procedures and maintenance schedules will be followed.
- Vehicles will undergo regular, scheduled maintenance to ensure that engines, brakes and other mechanical parts are in an acceptable working condition.
- Regular vehicle inspections (for leaks, secure cargo, etc.) will be conducted.
- Excess dust and dirt will be removed from vehicles before leaving site, if necessary.

Traffic-related mitigation measures related to general safety procedures will also be provided in the Plan:

- Contractors and workers will be required to adhere the BC Occupational Health and Safety Regulation (BC Reg 296/97), as well as a zero-tolerance policy on alcohol and drugs while transporting goods and materials to and from the site.
- Policies regarding proper disposal of smoking materials will be implemented to prevent forest fires.
- A driver fire watch and reporting program by drivers and a response plan will be implemented.
- Workers and contractors will follow a specified journey management procedure, including departure and arrival check-ins.
- Information on weather and highway conditions will be made available to all drivers before departure. Drivers will be required to check road conditions prior to departure, and will adjust driving styles to conditions.
- Drivers and personnel will receive appropriate training (e.g., safe driving practices such as maintaining appropriate distances between vehicles, adjusting driving styles to suit road conditions, noise awareness training).

Other measures to be implemented relate to communication with community and governments:

- If required, traffic control and/or road shutdowns will be used on Highway 37 near the entry to Project access roads during peak construction periods.
- Project traffic plans will be communicated to the provincial and local governments to ensure adequate signage is posted beside public roads.

- Local communities will be advised of driving routes, peak transportation periods and potential road shutdowns when transporting heavy/wide loads.

7.3.1.2 *Wildlife and Terrestrial Ecosystems Specific Risk Mitigation Measures*

The following measures will be undertaken to minimize interactions between wildlife and vehicles, reduce disruption to wildlife movement, and mitigate potential effects on terrestrial ecosystems:

- Project drivers will yield to wildlife observed along the highways.
- Project drivers will adhere to signage in areas of wildlife crossing.
- Project personnel (including drivers) will communicate locations of observed wildlife to drivers.
- Locations of collisions between wildlife and vehicles will be documented.
- Vehicle inspection stations will be established on site for vehicles entering and exiting the Project access roads, and appropriate action will be taken where risk of invasive plant introduction is identified.

7.3.1.3 *Climate and Air Quality Specific Risk Mitigation Measures*

The following measures will be taken to minimize potential traffic effects on climate and air quality:

- Diesel vehicles will use low sulphur content fuel, as required by law.
- Use of more efficient fuel blends will be considered.

7.3.1.4 *Dangerous Goods and Hazardous Materials Management Plan Risk Mitigation Measures*

Project activities involving dangerous goods or hazardous materials will be guided by the Dangerous Goods and Hazardous Materials Management Plan, which will be included in the Application/EIS. In relation to highway traffic, adherence to this plan is intended to prevent the introduction of hazardous and/or deleterious substances into the environment during their transportation.

Correct transport procedures for dangerous goods and hazardous materials will assist in ensuring that chemicals and dangerous goods do not cause environmental or human harm. In the Application/EIS, transport procedures will be developed that adhere to all applicable municipal, provincial and federal regulations and legislation such as the *Transportation of Dangerous Goods Act*(1992), WHMIS, Canadian Environmental Code of Practice for Metal Mines (Environment Canada n.d.), the BC Occupational Health and Safety Regulation (BC Reg 296/97), and the Health, Safety and Reclamation Code for Mines in BC (BC MEMPR 2008). Additionally, industry best practice standards will be adhered to, such as the International Cyanide Management Code (ICMI n.d.).

The following measures will be included in the Dangerous Goods and Hazardous Materials Management Plan:

- Drivers transporting dangerous goods or hazardous materials will be required to have appropriate safety training (e.g., TDG, WHMIS, and CPPI certification).
- All Project employees and contractors will be required to follow correct, cargo-specific transport procedures.
- Transportation of explosives will be in enclosed trailers/closed containers.
- Regular vehicle inspections (for oil leaks, secure cargo, etc.) will be conducted.
- Concentrate will be dewatered to a low moisture content before transport.

- Concentrate will be trucked in covered transport vehicles.
- Procedures will outline specific measures to be adhered to when transporting materials over or near any aquatic systems (wetlands and water bodies), including designated route selection.
- Requirements of the International Cyanide Management Code will be followed, and contractors delivering cyanide will be verified under the International Cyanide Management Code (ICMI n.d.) for transportation.

7.4 TRAFFIC ACCIDENTS MANAGEMENT

7.4.1 Action to Avoid or Mitigate

This section identifies the procedures that will be followed in the unlikely event of a traffic accident. Actions to prevent cargo (hazardous and non-hazardous) release into the environment as a result of a traffic accident are also identified. The items discussed below will provide the frameworks for the Emergency Response Plan, and the Spill Prevention and Emergency Response Plan, which will be included in the Application/EIS.

7.4.1.1 *Emergency Response Plan Risk Mitigation Measures*

The Emergency Response Plan that will be developed as part of the Application/EIS is intended to ensure that in the event of an emergency (other than a spill), all available resources are used appropriately to minimize the extent and severity of the effect on the safety of personnel, the public, and the environment.

Examples of actions taken in the event of an emergency include:

- The plan will include a description of communication and warning systems.
- Emergency contacts will be readily accessible to drivers.
- Procedures for emergency response and occupational first aid will be developed and workers and contractors will undergo required training.
- In the unlikely event of a fire, emergency response procedures to minimize fire duration and extent will be promptly initiated.

7.4.1.2 *Spill Prevention and Emergency Response Plan Risk Mitigation Measures*

Potential spills of hazardous and non-hazardous cargo will be mitigated as per the Spill Prevention and Emergency Response Plan, which will be developed in accordance with standards and Best Management Practices and included in the Application/EIS.

The Spill Prevention and Emergency Response Plan will include actions that are intended to prevent hazardous and non-hazardous spills into the environment as a result of traffic accidents, and to ensure that if accidental spills occur, all available resources are used appropriately to minimize the extent and severity of the effect on the safety of personnel, the public, and the environment. The plan will include the following:

- Specifications for preventing and controlling the release of materials during traffic accidents.
- Provisions for spill availability on vehicles transporting dangerous goods or hazardous materials, and set up at select locations along the Project haul route.

- Provisions for isolating, containing and managing all transported fuels, solvents, and other chemicals.
- Specifications for conducting vehicle assessments for oil leaks, secure cargo, etc.

The plan will include the following responses measures:

- Provide details on the location and nature of spill response equipment.
- Identify the steps to be taken to properly contain, recover, and clean up any spills that may take place.
- Outline procedures to minimize response time and ensure prompt clean-up.
- Train personnel (including drivers) in spill response procedures relevant to the materials present being transported.
- Train personnel (including drivers) in personal protection procedures to avoid contact with spilled material.
- Perform spill simulation drills to assess the effectiveness of the Spill Prevention and Emergency Response Plan and the adequacy of personnel training.
- Provide notification and reporting procedures in the event of a spill; for example, project staff and contractors will be required to report incidents of spills, seepages, leaks, or similar occurrences to the environmental staff.
- Use BMPs to minimize spill entry to waterbodies or into the terrestrial environment.
- Inform residents of the spill and restrict access to the spill site.
- Exclude wildlife (e.g. bears, moose) from the spill site until effective clean-up of the area.
- Monitor, soil, water, and vegetation within the spill area in the event of a major spill to ensure that the chemical levels are within the appropriate regulatory guidelines.
- Avoid directing spilled substances into closed storm drains or sewage line systems in the event of a volatile chemical spill (to prevent fires).
- Prepare a detailed cyanide management plan during the detailed design phase which will be consistent with the International Cyanide Management Code (ICMI n.d.). The plan will include provisions related to cyanide transportation, spill prevention and spill containment measures.
- Develop a procedure to respond to an unplanned release of process concentrate which will include: recovery of the material; re-processing or disposal; and confirmatory sampling to confirm no residual contamination is present above industrial standards.

Table 7.4-1 outlines spill response measures for specific reagents contained in Transport Canada's TDG Emergency Response Guidebook (2008).

7.5 MONITORING AND REPORTING

Monitoring and enforcement is fundamental to ensuring that the management plans are functioning to their full extent over the life span of the Project. Monitoring of selected environmental performance indicators in relation to developed targets assists in determining whether management plans require updating to improve the level of environmental protection.

HIGHWAYS 37 AND 37A TRAFFIC EFFECTS ASSESSMENT

A framework for monitoring risk mitigations described in the Traffic and Access Management Plan, the Hazardous Materials Management Plan, the Emergency Response Plan, and the Spill Prevention and Emergency Response Plan, will be included in the Application/EIS.

Additionally, details on the frequency and type of reporting, and to whom reports are to be submitted, will be included in the Application/EIS, as well as identification of the person responsible (e.g. Mine Manager, environmental officer, construction engineer, etc.).

Table 7.4-1. Spill Response Measures for Specific Reagents

Process Plant Reagent	Description	Description of Spill Response Measures
Sodium Hydrosulphide (NaHS)	Corrosive; spontaneously combustible	In the event of a spill, dust generation will be avoided, all ignition sources removed, and measures to prevent NaHS from entering the environment will be taken.
Sodium Cyanide (NaCN)	Poisonous (toxic) and infectious substance; Toxic and/or corrosive (non-combustible/water sensitive)	In the event of a spill, ICMI 2012 Guidelines for spill containment measures will be followed. Personnel will not get water inside containers, all ignition sources will be removed, small spills will be covered with dry earth or sand and plastic sheeting to minimize spreading or contact with rain, and other measures to prevent runoff from contacting spilled material.
Sodium Silicate (Na ₂ SiO ₃) (Sodium Metasilicate)	High pH, noncombustible	In the event of a spill, material will be carefully shoveled into suitable container(s); dust generation will be avoided, and in case of contact with water, runoff will be prevented from entering into storm sewers and ditches which lead to natural waterways.
Activated Carbon	Flammable and combustible; on contact with water emits flammable gases	In event of a spill, all ignition sources will be removed, small spill would be placed into clean dry container, cleared and removed; large spill would be wetted with water, diked for later disposal, entry into waterways, sewers, or confined areas will be prevented.
Hydrochloric Acid (HCl)	Toxic and/or Corrosive (non-combustible/water sensitive)	Personnel will not get water inside containers, all ignition sources will be removed; water spray may be used to reduce vapors or divert vapor cloud drift; spill residue will be neutralized with dilute solution of sodium carbonate; spill will be absorbed with dry earth or sand and contact with runoff will be prevented.
Sodium Hydroxide (NaOH) (Caustic soda)	Toxic and/or Corrosive (non-combustible)	Personnel will not get water inside containers, all sources of ignition will be removed; spill residue will be neutralized with a dilute solution of acetic acid; Contact with water, and contact with runoff will be prevented.
Sodium Metabisulfite (MBS)	Low pH (Acidic); moisture and air sensitive; non-flammable; non-corrosive in the presence of glass	A shovel will be used to put material into a waste disposal container, and cleaning will be finished by spreading water on the contaminated surface.
Copper Sulphate Pentahydrate (CuSO ₄ .5H ₂ O)	Air sensitive; corrosive to finely powdered metals; non-flammable	In case of a large spill, appropriate tools will be used to place material in a suitable container for reclamation or disposal, using a method that does not generate dust.
Sulphuric Acid (H ₂ SO ₄)	Corrosive; water-reactive; not combustible	Spills will be cleaned up immediately; emergency personnel will wear self-contained breathing apparatus, rubber boots and heavy rubber gloves; spilled material will be covered with sand, dry lime or soda ash, and place in a closed container and marked for disposal.

(continued)

Table 7.4-1. Spill Response Measures for Specific Reagents (continued)

Process Plant Reagent	Description	Description of Reagent-specific Spill Response Measures
PAX (potassium amyl xanthate)	Corrosive; spontaneously combustible	In event of a spill, dust generation will be avoided, all sources of ignition removed, material will be collected for proper disposal, and measures to prevent chemical from entering the environment will be taken. In case of fire, flooding amounts of water will be used to stop the reaction as smothering will not work for these materials.
A208 (Diethyl Dithiophosphate)	Proprietary reagent	Spill response measures specific for this reagent will be developed and outlined in the MSDS.
3418A (Dialkyl Dithiophosphinate)	Proprietary reagent	Spill response measures specific for this reagent will be developed and outlined in the MSDS.
Sodium Hydrosulphide (NaHS)	Corrosive; spontaneously combustible	In the event of a spill, dust generation will be avoided, all ignition sources removed, and measures to prevent NaHS from entering the environment will be taken.
Sodium Cyanide (NaCN)	Poisonous (toxic) and infectious substance; Toxic and/or corrosive (non-combustible/water sensitive)	In the event of a spill, ICMI Guidelines for spill containment measures will be followed. Personnel will not get water inside containers, all ignition sources will be removed, small spills will be covered with dry earth or sand and plastic sheeting to minimize spreading or contact with rain, and other measures to prevent runoff from contacting spilled material.
Sodium Silicate (Na ₂ SiO ₃) (Sodium Metasilicate)	High pH; non-combustible	In the event of a spill, material will be carefully shoveled into suitable container(s); dust generation will be avoided, and in case of contact with water, runoff will be prevented from entering into storm sewers and ditches which lead to natural waterways.
Activated Carbon	Flammable and combustible; on contact with water emits flammable gases	In event of a spill, all ignition sources will be removed, small spill would be placed into clean dry container, cleared and removed; large spill would be wetted with water, diked for later disposal, entry into waterways, sewers, or confined areas will be prevented.
Hydrochloric Acid (HCl)	Toxic and/or Corrosive (non-combustible/water sensitive)	Personnel will not get water inside containers, all ignition sources will be removed; water spray may be used to reduce vapors or divert vapor cloud drift; spill residue will be neutralized with dilute solution of sodium carbonate; spill will be absorbed with dry earth or sand and contact with runoff will be prevented.
Sodium Hydroxide (NaOH) (Caustic soda)	Toxic and/or Corrosive (non-combustible)	Personnel will not get water inside containers, all sources of ignition will be removed; spill residue will be neutralized with a dilute solution of acetic acid; Contact with water, and contact with runoff will be prevented.
Sodium Metabisulfite (MBS)	Low pH (Acidic); moisture and air sensitive; non-flammable; non-corrosive in the presence of glass	A shovel will be used to put material into a waste disposal container, and cleaning will be finished by spreading water on the contaminated surface.

(continued)

Table 7.4-1. Spill Response Measures for Specific Reagents (continued)

Process Plant Reagent	Description	Description of Reagent-specific Spill Response Measures
Copper Sulphate Pentahydrate (CuSO ₄ .5H ₂ O)	Air sensitive; corrosive to finely powdered metals; non-flammable	In case of a large spill, appropriate tools will be used to place material in a suitable container for reclamation or disposal, using a method that does not generate dust.
Sulphuric Acid (H ₂ SO ₄)	Corrosive; water-reactive; not combustible	Spills will be cleaned up immediately; emergency personnel will wear self-contained breathing apparatus, rubber boots and heavy rubber gloves; spilled material will be covered with sand, dry lime or soda ash, and place in a closed container and marked for disposal.
PAX (potassium amyl xanthate)	Corrosive; spontaneously combustible	In event of a spill, dust generation will be avoided, all sources of ignition removed, material will be collected for proper disposal, and measures to prevent chemical from entering the environment will be taken. In case of fire, flooding amounts of water will be used to stop the reaction as smothering will not work for these materials.
A208 (Diethyl Dithiophosphate)	Proprietary reagent	Spill response measures specific for this reagent will be developed and outlined in the MSDS.
3418A (Dialkyl Dithiophosphinate)	Proprietary reagent	Spill response measures specific for this reagent will be developed and outlined in the MSDS.
MIBC (Methyl Isobutyl Carbinol)	Flammable and combustible liquids (polar/water-miscible/noxious)	In event of spill, MIBC will be absorbed using an inert material (e.g., vermiculite, dry sand, earth) and placed in a chemical waste container. All ignition sources will be removed; personnel will wear personal protection equipment including a full face-piece respirator, protective clothing, boots, and gloves.
Flocculant (Magnafloc 336)	Proprietary reagent; Slippery; low corrosivity	Spills would be cleaned up immediately. Dry spills would be left dry and swept up. Avoid dust formation. If the polymer becomes wet, an absorbent material should be applied to the spill, then swept up and discarded; aluminum and galvanized equipment will be avoided.
Anti-scalant	Proprietary reagent; interferes with precipitation reactions	Spill response measures specific for this reagent will be developed and outlined in the MSDS.
Fuel Oil	Flammable and combustible liquids (non-polar/water-immiscible)	All ignition sources will be eliminated; spilled material will be absorbed or cover with dry earth, sand or other non-combustible material and transfer to containers. Large spills will be diked far ahead of liquid spill for later disposal. Measures will be taken to prevent entry into waterways, sewers, basements or confined areas. Water spray may be used to reduce vapor.
Lime (Calcium Oxide)	Toxic and/or corrosive (noncombustible/water sensitive)	Personnel will not get water inside containers, all ignition sources will be removed; water spray may be used to reduce vapors or divert vapor cloud drift. Material will be shoveled into waste disposal container. Dilute acid will be used to neutralize residuals.

(continued)

Table 7.4-1. Spill Response Measures for Specific Reagents (completed)

Process Plant Reagent	Description	Description of Reagent-specific Spill Response Measures
Ferric Chloride (FeCl ₃)	Toxic and/or corrosive (non-combustible)	In case of spill, material will be put into an appropriate waste disposal container or absorb with an inert material (e.g., vermiculite, dry sand, earth); contact with water, and contact with runoff will be prevented.
Calcium Chloride (CaCl ₂)	Normally stable; very soluble in water; not combustible; not corrosive	In case of spill, dust generation will be avoided, spilled material will be shoveled into containers, and the area will be flushed with water. Measures will be taken so that drainages or waterways are not contaminated.
Copper Chloride (CuCl ₂ ·2H ₂ O)	Toxic and/or corrosive (non-combustible)	In case of spill, material will be put into an appropriate waste disposal container or absorb with an inert material (e.g., vermiculite, dry sand, earth). Contact with water, and contact with runoff will be prevented.
Antifoam	Proprietary reagent	Spill response measures specific for this reagent will be developed and outlined in the MSDS.
Liquid Chlorine (Sodium Hypochlorite)	Toxic and/or corrosive (non-combustible)	Wear self-contained breathing apparatus and protective clothing. Spills may be absorbed and neutralized into solutions of caustic soda or lime and placed in containers of suitable material.

Source: Reagent (MSDS; Transport Canada 2008)